

9-275-I	10/24/08	U.S. DEPARTMENT OF THE INTERIOR				Meas. No.	
Station Number		U.S. Geological Survey				Processed by	
		ADCP Discharge Measurement Notes				Checked by	
Station Name		Birds Point					
Date		06-05, 20 11		Party		BR/ZM	
Width	Area / Rated Area	Velocity	Index Vel.	Gage Height	Discharge		
449	7,477	-0.001	—	—	Ø		
Gage Height Change		Meas. plots	From rating	Shift	ADCP Sync'd to WT		
in hrs.		% diff	No.:		Y at _____ or N		
ADCP Mfr / Model / Frequency			Serial No.	Firmware	Software		
RSM9			2010	1.50	2.50		
Boat/Motors Used			GPS Used	ADCP Depth	Diag. Test / Errors?		
			NO	0.3	<input checked="" type="checkbox"/> Y or <input checked="" type="checkbox"/> N		
Compass Calib. & Total Error		Mag. Var	MagVar Method		Moving Bed?		
Y or N		M20P	-1.6		On-site Model Previous		Y or N
Meas. Water Temp		ADCP Water Temp	Weather / Air Temp		Wind Speed / Dir.		
87 °F / C at		91 °F / C at			°F / C		
Gage Readings				Site Conditions			
Time				Inside	Outside	Max Water Depth	
						Max Water Speed	
1410						Max Boat Speed	
						Water Mode	
1415						Bottom Mode	
						Streambed material	
						Salinity	
						ppt at	
Weighted MGH						Checkbar found	
GH corrections						Checkbar changed to:	
Correct MGH						at	
Wading, cable, ice, boat, upstr., downstr., side bridge				ft., mi. upstr., downstr. of gage			
Measurement rated:		excellent (2%), good (5%), fair (8%), poor (>8%)				based on following conditions	
Flow							
Cross section:							
Control:							
Gage operating:		Y or N	Record removed:	Y or N	Filename:		
Battery voltage		V	Intakes/Orifice cleaned/purged:				
Bubble-gage psi:		Tank		Line		Bubble rate	/ min
Extreme-GH indicators:		Max		Min		CSG Checked	Y or N
HWM on stick			Ref elev.		HWM elevation		
GH of zero flow = GH			- depth at control		=	ft, Rated=	
Sheet No.					of		sheets

Discharge Measurement Summary

Date Measured: Sunday, June 05, 2011

Site Information		Measurement Information	
Site Name	birdspoint	Party	bcr/zwm
Station Number		Boat/Motor	
Location		Meas. Number	

System Information		System Setup		Units	
System Type	RS-M9	Transducer Depth (ft)	0.30	Distance	ft
Serial Number	2010	Salinity (ppt)	0.0	Velocity	ft/s
Firmware Version	1.50	Magnetic Declination (deg)	-1.6	Area	ft2
Software Version	2.50			Discharge	cfs
				Temperature	degF

Discharge Calculation Settings				Discharge Results	
Track Reference	Bottom-Track	Left Method	Sloped Bank	Width (ft)	448.88
Depth Reference	Vertical Beam	Right Method	Sloped Bank	Area (ft2)	7,477.2
Coordinate System	ENU	Top Fit Type	Power Fit	Mean Speed (ft/s)	-0.001
		Bottom Fit Type	Power Fit	Total Q (cfs)	1.622

Measurement Results																	
Tr	Time		Distance				Mean Vel		Discharge							% Measured	
#	Time	Duration	Temp.	Track	DMG	Width	Area	Boat	Water	Left	Right	Top	Middle	Bottom	Total	LCTotal	
3	L 2:10:20 PM	0:02:46	91.1	471.14	429.43	449.43	7,940.7	2.838	0.018	0.30	0.74	6.81	99.48	38.27	145.601	--	68.3
4	R 2:13:27 PM	0:02:43	91.3	436.28	428.33	448.33	7,013.7	2.677	-0.020	-0.43	0.62	10.16	-96.01	-36.38	142.357	--	67.4
		Mean	91.2	453.71	428.88	448.88	7,477.2	2.757	-0.001	-0.07	0.68	-1.68	1.74	0.94	1.622	0.000	67.9
		Std Dev	0.1	17.43	0.55	0.55	463.5	0.081	0.019	0.36	0.06	8.48	97.74	37.33	143.979	0.000	0.4
		COV	0.0	0.038	0.001	0.001	0.062	0.029	19.701	5.571	0.086	5.057	56.248	39.542	88.766	0.000	0.007

Exposure Time: 0:05:29

Tr3=20110605141019.riv; Tr4=20110605141326.riv;

Comments																	
Tr3=20110605141019.riv - ; Tr4=20110605141326.riv - ;																	

Compass Calibration																	
File Name: CompassCal20110605140202.txt																	
Results: PASS																	
Score is excellent.																	
Magnetic interference is very low.																	
Calibration score: M2.00Q9																	

System Test																	
Not Loaded																	

Parameters and settings marked with a * are not constant for all files.

Report generated using SonTek RiverSurveyor Live v2.50