

CONTENTS

Abstract	1
Introduction	2
Purpose and Scope	2
Previous Investigations.....	2
Acknowledgments	4
Description of Study Area.....	4
Geology	4
Climate	6
Hydrology.....	8
Water Use	10
Land Use	10
Streamflow.....	14
Flow Durations and Estimates of August Median Streamflow	14
Long-Term Stations	17
Short-Term Stations.....	17
Factors Affecting Streamflow	34
Surficial Geology.....	34
Bedrock Geology.....	38
Climate	39
Other Physical Features.....	39
Base Flow	40
Long-Term Stations.....	40
Short-Term Stations.....	44
Ground-Water Recharge	44
Streamflow Hydrograph Analysis	47
Climatological Data Analysis.....	49
Summary and Conclusions	50
References Cited	52

FIGURES

1-3. Maps showing:

1. Location of study area in the Housatonic River Basin, western Massachusetts and parts of eastern New York and northwestern Connecticut
2. Distribution of underlying bedrock types and stratified-drift and till deposits.....
3. Location of long-term continuous and discontinued streamflow-gaging stations, ground-water observation wells, and climatological stations in and near the study area
4. Hydrographs showing water-level fluctuations for selected observation wells in the Housatonic River Basin, western Massachusetts, 1951–96.....

5, 6. Maps showing:

5. Location of surface-water and ground-water sources used for public-water supplies.....
6. Location of low-flow partial-record stations, partial-record stations, and short-term discontinued streamflow-gaging stations used in flow-duration analysis.....

TABLES

1.	Site descriptions and water levels measured in U.S. Geological Survey observation wells completed in stratified-drift deposits in the Housatonic River Basin, western Massachusetts, 1994–96	11
2.	Water use by municipalities within the Massachusetts part of the Housatonic River Basin, 1994–95	15
3.	Description of long-term continuous and discontinued streamflow-gaging stations used in streamflow, base-flow, and ground-water-recharge analyses in and near the Housatonic River Basin, western Massachusetts and parts of eastern New York and northwestern Connecticut	18
4.	Streamflows for selected flow durations and August median streamflows at long-term continuous and discontinued streamflow-gaging stations.....	19
5.	Streamflows per square mile for selected flow durations and August median streamflows per square mile at long-term continuous and discontinued streamflow-gaging stations	20
6.	Description of low-flow partial-record stations, partial-record stations, and short-term discontinued streamflow-gaging stations, for which streamflow estimates are provided	22
7.	Summary of flow-duration analysis at low-flow partial-record stations, partial-record stations, and short-term discontinued streamflow-gaging stations	24
8.	Estimated streamflows for selected flow durations and estimated August median streamflows at low-flow partial-record stations, partial-record stations, and short-term discontinued streamflow-gaging stations	27
9.	Standard errors of estimated streamflows for selected flow durations and estimated August median streamflows at low-flow partial-record stations, partial-record stations, and short-term discontinued streamflow-gaging stations.....	29
10.	Estimated streamflows per square mile for selected flow durations and estimated August median streamflows at low-flow partial-record stations, partial-record stations, and short-term discontinued streamflow-gaging stations.....	32
11.	Correlation coefficients for the relations between streamflow and basin characteristics at low-flow partial-record stations, partial-record stations, short-term discontinued streamflow-gaging stations, and long-term continuous and discontinued streamflow-gaging stations	35
12.	Correlation coefficients for the relations between streamflow and basin characteristics at partial-record stations, short-term discontinued streamflow-gaging stations, and long-term continuous and discontinued streamflow-gaging stations.....	36
13.	Correlation coefficients for the relations between streamflow and basin characteristics at long-term continuous and discontinued streamflow-gaging stations	37
14.	Estimates of minimum, maximum, and mean annual streamflow and base flow, and base-flow indexes derived from the computer programs HYSEP and PART at long-term continuous and discontinued streamflow-gaging stations.....	41
15.	Correlation coefficients for the relation of base-flow and ground-water-recharge characteristics to basin characteristics at long-term continuous and discontinued streamflow-gaging stations	43
16.	Streamflow, base flow, and ratio of base flow to streamflow for selected flow durations derived from the computer program HYSEP at long-term continuous and discontinued streamflow-gaging stations	45
17.	Estimates of minimum, maximum, and mean annual ground-water recharge and recharge indexes derived from the computer program RORA at long-term continuous and discontinued streamflow-gaging stations	47
18.	Estimates of mean annual potential evapotranspiration and ground-water recharge derived from the Thornthwaite and Mather (1957) method at climatological stations.....	49

19. Water budget for the Green River subbasin, western Massachusetts and part of eastern New York, water years 1952–71 and 1995	50
20. Basin characteristics determined by using a geographic information system at low-flow partial-record stations, partial-record stations, short-term discontinued streamflow-gaging stations, and long-term continuous and discontinued streamflow-gaging stations.....	59
21. Streamflow measurements made and used in analyses at low-flow partial-record stations, partial-record stations, and short- and long-term discontinued streamflow-gaging stations, water years 1963–96	63

CONVERSION FACTORS AND VERTICAL DATUM

CONVERSION FACTORS

Multiply	By	To obtain
cubic foot per second (ft^3/s)	0.02832	cubic meter per second
cubic foot per second per square mile [$(\text{ft}^3/\text{s})/\text{mi}^2$]	0.01093	cubic meter per second per square kilometer
foot (ft)	0.3048	meter
foot per mile (ft/mi)	0.1894	meter per kilometer
gallon per minute (gal/min)	6.309×10^{-5}	cubic meter per second
inch (in.)	25.4	millimeter
inch per year (in/yr)	2.54	centimeter per year
mile (mi)	1.609	kilometer
mile per square mile (mi/mi^2)	0.6212	kilometer per square kilometer
million gallons per day (Mgal/d)	0.04381	cubic meter per second
square mile (mi^2)	2.590	square kilometer
square mile per mile (mi^2/mi)	1.609	square kilometer per kilometer

Temperature in degrees Fahrenheit ($^{\circ}\text{F}$) can be converted to degrees Celsius ($^{\circ}\text{C}$) as follows: $^{\circ}\text{C} = 5/9 (^{\circ}\text{F} - 32)$.

VERTICAL DATUM

Sea Level: In this report “sea level” refers to the National Geodetic Vertical Datum of 1929 (NGVD of 1929)—a geodetic datum derived from a general adjustment of the first-order level nets of the United States and Canada, formerly called Sea Level Datum of 1929.

