

**SOURCE CODE FOR THE COMPUTER PROGRAM AND SAMPLE
DATA SET FOR THE SIMULATION OF CYLINDRICAL FLOW TO A
WELL USING THE U.S. GEOLOGICAL SURVEY MODULAR
FINITE-DIFFERENCE GROUND-WATER FLOW MODEL**

U.S. GEOLOGICAL SURVEY

Open-File Report 92-659



**SOURCE CODE FOR THE COMPUTER PROGRAM AND SAMPLE
DATA SET FOR THE SIMULATION OF CYLINDRICAL FLOW TO A
WELL USING THE U.S. GEOLOGICAL SURVEY MODULAR
FINITE-DIFFERENCE GROUND-WATER FLOW MODEL**

by Thomas E. Reilly and Arlen W. Harbaugh

U.S. GEOLOGICAL SURVEY

Open-File Report 92-659



Reston, Virginia
1993

U.S. DEPARTMENT OF THE INTERIOR

BRUCE BABBITT, Secretary

U.S. GEOLOGICAL SURVEY

Dallas L. Peck, Director

For additional information
write to:

U.S. Geological Survey
National Center, MS 431
12201 Sunrise Valley Drive
Reston, Virginia 22092

Copies of this report may be
purchased from:

Books and Open-File Reports Section
U.S. Geological Survey
Federal Center, Building 810
Box 25425
Denver, Colorado 80225

CONTENTS

Abstract	1
Introduction	1
References	2
Appendixes	2
Appendix 1 - Program listing	3
Appendix 2 - Preprocessor input instructions	6
Appendix 3 - Preprocessor input data for sample problem	7
Diskette	in pocket

SOURCE CODE FOR THE COMPUTER PROGRAM AND SAMPLE DATA SET
FOR THE SIMULATION OF CYLINDRICAL FLOW TO A WELL USING THE
U.S. GEOLOGICAL SURVEY MODULAR FINITE-DIFFERENCE
GROUND-WATER FLOW MODEL

by

Thomas E. Reilly and Arlen W. Harbaugh

ABSTRACT

Cylindrical (axisymmetric) flow to a well is an important specialized topic of ground-water hydraulics and has been applied by many investigators to determine aquifer properties and determine heads and flows in the vicinity of the well. A recent modification to the U.S. Geological Survey Modular Three-Dimensional Finite-Difference Ground-Water Flow Model provides the opportunity to simulate axisymmetric flow to a well. The theory involves the conceptualization of a system of concentric shells that are capable of reproducing the large variations in gradient in the vicinity of the well by decreasing their area in the direction of the well. The computer program documented in this report serves as a preprocessor to the U.S. Geological Survey model by creating the input data file needed to implement the axisymmetric conceptualization. This report contains a listing of the computer code, a disk containing the computer code, and a description of the data input requirements to this preprocessor.

INTRODUCTION

The original U.S. Geological Survey (USGS) Modular Ground-Water Flow Model (McDonald and Harbaugh, 1988), known as MODFLOW, assumed that model nodes are in the center of rectangular cells and that transmissivity is constant within a cell. Based on these assumptions, the model calculates coefficients, called conductance, that are multiplied by head difference to determine flow between cells. A generalized finite-difference capability was developed for the USGS model (Harbaugh, 1992) to allow the model program to read conductance as input instead of calculating it internally under the assumption of block-centered finite-difference discretization.

This generalized finite-difference capability allows the conductances to be calculated externally using a node-centered radial discretization (as described in Bennett and others, 1990; and Reilly and Harbaugh, 1993) for input to the flow model. This report documents a preprocessor computer program that calculates conductances and storage capacities for a radial axisymmetric node-cen-

tered finite-difference grid. The calculated conductances and storage capacities can then be included as the input to MODFLOW to simulate axisymmetric flow to a well.

COMPUTER PROGRAM

The theory and logic of the computer program are described in Reilly and Harbaugh (1993), along with an example of the use of the preprocessor. A listing of the computer program used in Reilly and Harbaugh (1993) is provided in this document to make the program available and to provide a record of the original program. An MS-DOS¹ compatible, 1.2 megabyte diskette that contains the computer readable text files is included with this report .

The files three files contained on the diskette are: 1. RAD_MOD.FOR, 2. RAD_MOD.TXT, and 3. NEUMAN.DAT. These computer readable files are listed in the three appendixes. Appendix 1 is a listing of the file RAD_MOD.FOR which is the Fortran source code of the preprocessor contained on the diskette. Appendix 2 is a listing of the file RAD_MOD.TXT which provides the input instructions for the input to the program as described in Reilly and Harbaugh (1993). Appendix 3 is a listing of the file NEUMAN.DAT which is the input data set used in the sample problem described in Reilly and Harbaugh (1993).

REFERENCES

- Bennett, G.D., Reilly, T.E., and Hill, M.C., 1990, Technical training note in ground-water hydrology: Radial flow to a well: U.S. Geological Survey Water-Resources Investigations Report 89-4134, 83 p.
- Harbaugh, A.W., 1992, A generalized finite-difference formulation for the U.S. Geological Survey modular three-dimensional finite-difference ground-water flow model: U. S. Geological Survey Open-File Report 91-494, 60 p.
- McDonald, M.G., and Harbaugh, A.W., 1988, A modular three-dimensional finite-difference ground-water flow model: Techniques of Water-Resources Investigations of the U.S. Geological Survey, book 6, chap. A1, 586 p.
- Reilly, T.E., and Harbaugh, A.W., 1993, Simulation of cylindrical flow to a well using the U.S. Geological Survey modular finite-difference ground-water flow model: Ground Water, v. 31, no. 3, p.489-494.

1. The use of brand names in this report is for identification purposes only and does not constitute endorsement by the U.S. Geological Survey.

APPENDIXES

Appendix 1 -- Program listing

```
C      PREPROCESSOR TO CALCULATE CONDUCTANCES AND STORAGE CAPACITIES
C      FOR A RADIAL SIMULATION USING THE GENERAL FINITE-DIFFERENCE
C      (GFD) PACKAGE OF THE U.S.G.S. MODULAR MODEL
C
C      BY THOMAS E. REILLY AND ARLEN W. HARBAUGH
C      VERSION 1.0  -- APRIL 1992
C
C      PARAMETER (MXCOL=200,MXROW=100)
C      DIMENSION R(MXCOL),AREA(MXCOL),DELZ(MXROW),KR(MXROW),KZ(MXROW),
1      SS(MXROW),SC(MXROW,MXCOL),CR(MXROW,MXCOL),CC(MXROW,MXCOL)
C      CHARACTER*80 IFNAME,OFNAM1,OFNAM2
C      REAL*4 KR,KZ
C      PI=3.14159
C
C      Ask for file names and open the files
C      INUNIT=10
C      IOUTU1=11
C      IOUTU2=12
C      WRITE(*,1)
1      FORMAT(5X,'ENTER INPUT FILE NAME')
C      READ(*,2) IFNAME
2      FORMAT(A)
C      OPEN(INUNIT,FILE=IFNAME,STATUS='OLD')
C      WRITE(*,3)
3      FORMAT(5X,'ENTER GFD PACKAGE OUTPUT FILE NAME')
C      READ(*,2) OFNAM1
C      OPEN(IOUTU1,FILE=OFNAM1)
C      WRITE(*,4)
4      FORMAT(5X,'ENTER OUTPUT FILE NAME FOR LATERAL GRID SPACING')
C      READ(*,2) OFNAM2
C      OPEN(IOUTU2,FILE=OFNAM2)
C
C      Read first record, and check that arrays are dimensioned large enough
C      READ(INUNIT,10) ALPHA,RW,NCOL,NROW,LOCAT
10     FORMAT(2F10.0,3I5)
C      IF(NCOL.GT.MXCOL .OR. NROW.GT.MXROW) THEN
C          WRITE(*,*) ' NCOL GREATER THAN MXCOL OR NROW GREATER THAN MXROW'
C          STOP
C      END IF
C
C      Calculate lateral node location
C      R(1)=RW
C      DO 11 I=2,NCOL
C          R(I)=ALPHA*R(I-1)
11     CONTINUE
C
C      Calculate cell area
C      ASQ=ALPHA*ALPHA
```

```

RINTER=ALPHA*RW*SQRT(2./(ASQ+1.))
AREA(1)=PI*(RINTER*RINTER-RW*RW)
AREA(2)=AREA(1)*ASQ*2.
NNC=NCOL-1
DO 12 I=3,NNC
    AREA(I)=AREA(I-1)*ASQ
12 CONTINUE
    AREA(NCOL)=AREA(NNC)*ASQ/2.
C
C READ VERTICAL CHARACTERISTICS
DO 25 J=1,NROW
    READ(INUNIT,21) IR,DELZ(IR),KR(IR),KZ(IR),SS(IR)
21 FORMAT(I5,4F10.0)
25 CONTINUE
C
C GENERATE CR, CC, AND SC ARRAYS
DO 30 J=1,NROW
DO 29 I=1,NCOL
    SC(J,I)=SS(J)*AREA(I)*DELZ(J)
    IF(I.EQ.NCOL) THEN
        CR(J,I)=0.0
    ELSE
        CR(J,I)=2.*PI*KR(J)*DELZ(J)/ALOG(ALPHA)
    END IF
    IF(J.EQ.NROW) THEN
        CC(J,I)=0.0
    ELSE
        A=2.*KZ(J)*AREA(I)/DELZ(J)
        IF(J.EQ.1) A=KZ(J)*AREA(I)/DELZ(J)
        B=2.*KZ(J+1)*AREA(I)/DELZ(J+1)
        IF(J+1.EQ.NROW) B=KZ(J+1)*AREA(I)/DELZ(J+1)
        C=1./A + 1./B
        CC(J,I)=1./C
    END IF
29 CONTINUE
30 CONTINUE
C
C WRITE GFD FILE
C ISS,IGFDCB
    WRITE(IOUTU1,41)
41 FORMAT(9X,'0',9X,'0',2X,'ISS,IGFDCB')
C LAYCON
    WRITE(IOUTU1,42) 0
42 FORMAT(I2)
C DELR
    WRITE(IOUTU1,43) LOCAT,'DELR'
43 FORMAT(I10,7X,'1.0',1X,'(5F15.0)',20X,'0',2X,A)
    WRITE(IOUTU1,44) (AREA(I),I=1,NCOL)
44 FORMAT(1P,5E15.5)
C DELC
    WRITE(IOUTU1,43) LOCAT,'DELC'
    WRITE(IOUTU1,44) 1.,(0.0,I=2,NROW)
C SC
    WRITE(IOUTU1,43) LOCAT,'SC'

```

```

        DO 50 J=1,NROW
        WRITE(IOUTU1,44) (SC(J,I),I=1,NCOL)
50     CONTINUE
C     CR
        WRITE(IOUTU1,43) LOCAT,'CR'
        DO 52 J=1,NROW
        WRITE(IOUTU1,44) (CR(J,I),I=1,NCOL)
52     CONTINUE
C     CC
        WRITE(IOUTU1,43) LOCAT,'CC'
        DO 53 J=1,NROW
        WRITE(IOUTU1,44) (CC(J,I),I=1,NCOL)
53     CONTINUE
C
C Write lateral node locations
        WRITE(IOUTU2,60)
60     FORMAT(1X,'Lateral node location:')
        WRITE(IOUTU2,44) (R(I),I=1,NCOL)
C
        STOP
        END

```

Appendix 2 --Preprocessor input instructions

INPUT TO PROGRAM:

Data set 1:

ALPHA,RW,NCOL,NROW,LOCAT

Format (2F10.0,3I5)

Data set 2 (one record for each layer in the model):

IR,DELZ(IR),KR(IR),KZ(IR),SS(IR)

Format (I5,4F10.0)

Where:

ALPHA= $R(I+1)/R(I)$, This is the ratio of the lateral distance between neighboring nodes
{usually between 1.1 and 2.0},

RW=Radius of the well

NCOL=Number of nodes laterally (variable NCOL in MODFLOW) {must be greater
than 4 and is usually greater than 15}

NROW=Number of layers (variable NROW in MODFLOW)

LOCAT = Unit number for reading GFD data in MODFLOW

IR=Layer number

DELZ=Thickness of layer IR

KR=Radial hydraulic conductivity in layer IR

KZ=Vertical hydraulic conductivity in layer IR

SS=Specific storage of material in layer IR (L^{-1}), can be set to $S_y/DELZ$ for the top layer
to represent the water table, where S_y is the specific yield (dimensionless).

Note: The output from this program is all of the required input data for the General Finite-Difference Package (GFD). The value for IGFDCB (Harbaugh, 1992, p.13) is specified as zero. This can be changed, if desired, with an editor after the GFD data file has been created by the preprocessor.

Appendix 3 -- Preprocessor input data for sample problem

	1.50	.936	40	11	12
1	5.	100.0		10.0	.04
2	10.	100.0		10.0	.000005
3	10.	100.0		10.0	.000005
4	10.	100.0		10.0	.000005
5	10.	100.0		10.0	.000005
6	10.	100.0		10.0	.000005
7	10.	100.0		10.0	.000005
8	10.	100.0		10.0	.000005
9	10.	100.0		10.0	.000005
10	10.	100.0		10.0	.000005
11	5.	100.0		10.0	.000005