

PRMS-IV, the Precipitation-Runoff Modeling System, Version 4

By Steven L. Markstrom, R. Steven Regan, Lauren E. Hay, Roland J. Viger, Richard M. T. Webb, Robert A. Payn, and Jacob H. LaFontaine

Updated tables from version 4.0.3 to version 5.0.0

May 30, 2019

Suggested citation:

Markstrom, S.L., Regan, R.S., Hay, L.E., Viger, R.J., Webb, R.M.T., Payn, R.A., and LaFontaine, J.H., 2015, PRMS-IV, the precipitation-runoff modeling system, version 4: U.S. Geological Survey Techniques and Methods, book 6, chap. B7, 158 p.

Any use of trade, product, or firm names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

Table 2. Description of modules implemented in the Precipitation-Runoff Modeling System, version 5 (PRMS-V).

[green highlight indicates new for PRMS-V; strikethrough indicates items removed]

Module name Description				
	Basin definition process			
basin	Defines shared watershed-wide and hydrologic response unit (HRU) physical parameters and variables.			
	Cascading flow process			
cascade	Determines computational order of the HRUs and groundwater reservoirs for routing flow downslope.			
Solar table process				
soltab	Compute potential solar radiation and sunlight hours for each HRU for each day of year.			
	Time series data process			
obs	Reads and stores observed data from all specified measurement stations.			
dynamic_param_read	Read and makes available dynamic parameters by HRU from pre-processed files.			
water_use_read	Read and makes available water-use data (diversions and gains) from pre-processed files.			
	Temperature distribution process			
temp_1sta	Distributes maximum and minimum temperatures to each HRU by using temperature data measured at one station and specified monthly lapse rates.			
temp_laps	Distributes maximum and minimum temperatures to each HRU by computing a daily lapse rate with temperature data measured at a base station and a lapse station with differing altitudes.			
temp_dist2	Distributes maximum and minimum temperatures to each HRU by using a basin-wide lapse rate applied to the temperature data, adjusted for distance, measured at each station.			
temp_sta	Distributes maximum and minimum temperatures to each HRU by using temperature data measured at one station, similar to temp_1sta except there is no lapse rate.			
climate_hru	Reads distributed temperature values directly from files.			
	Precipitation distribution process			
precip_1sta	Determines the form of precipitation and distributes it from one or more stations to each HRU by using monthly correction factors to account for differences in altitude, spatial variation, topography, and measurement gage efficiency.			
precip_laps	Determines the form of precipitation and distributes it to each HRU by using monthly lapse rates.			
precip_dist2	Determines the form of precipitation and distributes it to each HRU by using an inverse distance			
climate_hru	weighting scheme. Reads distributed precipitation values directly from files.			
	Combined climate distribution process			
ide_dist	Determines the form of precipitation and distributes precipitation and temperatures to each HRU on the basis of measurements at stations with closest elevation or shortest distance to the respective			
xyz_dist	HRU. Determines the form of precipitation and distributes precipitation and temperatures to each HRU by using a multiple linear regression of measured data from a group of measurement stations or from			
climate_hru	atmospheric model simulation. Reads distributed climate values directly from files.			
	Solar radiation distribution process			
ddsolrad	Distributes solar radiation to each HRU and estimates missing solar radiation data using a maximum temperature per degree-day relation.			

ccsolrad	Distributes solar radiation to each HRU and estimates missing solar radiation data using a relation					
climate_hru	between solar radiation and cloud cover. Reads distributed solar radiation values directly from files.					
	Transpiration period process					
transp_frost	Determines whether the current time step is in a period of active transpiration by the killing frost method.					
transp_tindex	Insp_tindex Determines whether the current time step is in a period of active transpiration by the temperature index method.					
climate_hru	Reads the state of transpiration directly from files.					
	Potential evapotranspiration process					
potet_hamon	Computes the potential evapotranspiration by using the Hamon formulation (Hamon, 1961).					
potet_jh	Computes the potential evapotranspiration by using the Jensen-Haise formulation (Jensen and Haise, 1963).					
potet_hs	Computes the potential evapotranspiration by using the Hargreaves-Samani formulation (Hargreaves and Samani, 1982).					
potet_pt	Computes the potential evapotranspiration by using the Priestley-Taylor formulation (Priestley and Taylor, 1972).					
potet_pm	Computes the potential evapotranspiration by using the Penman-Monteith formulation (Penman, 1948; Monteith, 1965); requires windspeed and humidity specified in CBH Files.					
potet_pm_sta	Computes the potential evapotranspiration by using the Penman-Monteith formulation (Penman, 1948; Monteith, 1965); requires windspeed and humidity specified in the Data File.					
potet_pan climate_hru	Computes the potential evapotranspiration for each HRU by using pan-evaporation data. Reads distributed potential evapotranspiration values directly from files.					
	Canopy Interception process					
intcp	Computes volume of intercepted precipitation, evaporation from intercepted precipitation, and throughfall that reaches the soil or snowpack.					
	Snow process					
snowcomp	Initiates development of a snowpack and simulates snow accumulation and depletion processes by using an energy-budget approach.					
	Surface runoff process					
srunoff_smidx	Computes surface runoff and infiltration for each HRU by using a nonlinear variable-source-area method allowing for cascading flow.					
srunoff_carea	Computes surface runoff and infiltration for each HRU by using a linear variable-source-area method allowing for cascading flow.					
	Soil-zone process					
soilzone	Computes inflows to and outflows from soil zone of each HRU and includes inflows from					
	infiltration, groundwater, and upslope HRUs, and outflows to gravity drainage, interflow, and surface runoff to down-slope HRUs.					
	Groundwater process					
gwflow	Sums inflow to and outflow from PRMS groundwater reservoirs; outflow can be routed to downslope groundwater reservoirs and stream segments.					
	Streamflow process					
muskingum	Computes flow in the stream network using the Muskingum routing method.					
muskingum_lake	Computes flow in the stream network using the Muskingum routing method and flow and storage in on-channel lake using several methods.					
routing	Computes common segment routing flows for modules strmflow_in_out and Muskingum.					
strmflow	Computes daily streamflow as the sum of surface runoff, shallow-subsurface flow (interflow), detention reservoir flow, and groundwater flow.					
strmflow_in_out	Routes water between segments in the stream network by setting the outflow to the inflow.					

strmflow_lake	Computes basin on channel reservoir storage and outflows.
	Summary process
basin_sum basin_summary	Computes daily, monthly, yearly, and total flow summaries of volumes and flows for all HRUs. Write user-selected results for variables of dimension one to separate CSV Files at daily, monthly, mean monthly, mean yearly, and yearly total time steps when control parameter basinOutON_OFF is specified equal to 1.
convert_params	Writes values for new PRMS-V parameters to a file based on a PRMS-IV Parameter File when control parameter model_mode is specified equal to CONVERT. Writes values for old PRMS-IV parameters to a file based on a PRMS-V Parameter File when control parameter model_mode is specified equal to CONVERT4.
frost_date	Writes a parameter file of the last spring frost and first fall frost for each HRU based on the simulation time period and distributed temperature as required by the transp_frost module; land, subsurface, and stream processes are not computed.
map_results	Writes HRU summaries to a user specified target map at weekly, monthly, yearly, and total time steps.
nhru_summary	Write user-selected results dimensioned by the value of dimension nhru to separate CSV Files at daily, monthly, mean monthly, mean yearly, and yearly total time steps when control parameter nhruOutON_OFF is specified equal to 1.
nsegment_summary	Write user-selected results dimensioned by the value of dimension nsegment to separate CSV Files at daily, monthly, mean monthly, mean yearly, and yearly total time steps when control parameter nsegmentOutON_OFF is specified equal to 1 or 2.
nsub_summary	Write user-selected results dimensioned by the value of dimension nsub to separate CSV Files at daily, monthly, mean monthly, mean yearly, and yearly total time steps when control parameter nsubOutON_OFF is specified equal to 1 or 2.
prms_summary	Writes selected basin area-weighted results to a Comma-Seperated Values (CSV) File when control parameter csvON_OFF is specified equal to 1.
subbasin write_climate_hru	Computes streamflow at internal basin nodes and variables by subbasin. Writes climate-by-HRU Files of user-selected climate variables on the basis of distributed climate; land, subsurface, and stream processes are not computed.

Table 1-1. Dimensions used in the Precipitation-Runoff Modeling System, version 5 (PRMS-V).

[HRU, hydrologic response unit; GWR, groundwater reservoir; >, greater than; POI, points-of-interest; control parameters temp_module, precip_module, solrad_module, et_module, strmflow_module, subbasin_flag, cascade_flag, cascadegw_flag, and mapOutON_OFF defined in table 1-2; parameter hru_solsta defined in table 1-3; green highlight indicates new for PRMS-V]

Dimension ³	Description	Default	Required/Condition
	Spatial dimensions		
ngw^2	Number of GWRs	1	required
ngwcell	Number of spatial units in the target map for mapped results	0	$mapOutON_OFF = 1$
nhru	Number of hydrologic response units	1	required
nhrucell	Number of unique intersections between HRUs and spatial units of a target map for mapped results	0	mapOutON_OFF = 1
nlake	Number of lakes	0	required when any HRU has hru_type specified equal to 2
nsegment	Number of stream-channel segments	0	<pre>strmflow_module = muskingum_lake, muskingum,</pre>
			or strmflow_in_out or cascade_flag = 1 or 2 or
			cascadegw_flag = 1 or 2
$nssr^2$	Number of subsurface reservoirs	1	required
nsub	Number of internal subbasins	0	subbasin_flag = 1
	Time-series input data dimension	ns¹	
nconsumed	Number of consumptive water-use destinations	0	optional
nevap	Number of pan-evaporation data sets	0	<pre>et_module = potet_pan</pre>
nexternal	Number of external water-use sources or destinations	0	optional
nhumid	Number of relative humidity measurement stations	0	optional
nlakeelev	Maximum number of lake elevations for any rating table data set	0	strmflow_module = muskingum_lake
nobs	Number of streamflow-measurement stations	0	<pre>replacement flow when strmflow_module = muskingum_lake, muskingum, or strmflow_in_out</pre>
npoigages	Number of points-of-interest streamflow gages	0	optional
nrain	Number of precipitation-measurement stations	0	<pre>precip_module = precip_1sta, precip_laps, precip_dist2, ide_dist, or xyz_dist</pre>
nratetbl	Number of rating-table data sets for lake elevations	0	strmflow_module = muskingum_lake
nsnow	Number of snow-depth measurement stations	0	optional
nsol	Number of solar-radiation measurement stations	0	computation of solar radiation distribution using parameter hru_solsta
ntemp	Number of air-temperature-measurement stations	0	<pre>temp_module = temp_1sta, temp_sta, temp_laps, temp_dist2, ide_dist, or xyz_dist</pre>
nwind	Number of wind-speed measurement stations	0	Optional

Dimension ³	Description	Default	Required/Condition
	Computation dimensions		
ncascade	Number of HRU links for cascading flow	0	$cascade_flag = 1 \text{ or } 2$
ncascdgw	Number of GWR links for cascading flow	0	$cascadegw_flag = 1 \text{ or } 2$
ndepl	Number of snow-depletion curves	1	required
ndeplval	Number of values in all snow-depletion curves (set to ndepl *11)	11	required
	Lake computation dimensions		
mxnsos	Maximum number of storage/outflow table values for storage-detention reservoirs and lakes connected to the stream network using Puls routing	0	strmflow_module = muskingum_lake
ngate	Maximum number of reservoir gate-opening values (columns) for lake rating table 1	0	<pre>strmflow_module = muskingum_lake and nratetbl > 0</pre>
ngate2	Maximum number of reservoir gate-opening values (columns) for lake rating table 2	0	strmflow_module = muskingum_lake and nratetbl > 1
ngate3	Maximum number of reservoir gate-opening values (columns) for lake rating table 3	0	strmflow_module = muskingum_lake and nratetbl > 2
ngate4	Maximum number of reservoir gate-opening values (columns) for lake rating table 4	0	<pre>strmflow_module = muskingum_lake and nratetbl > 3</pre>
nstage	Maximum number of lake elevations values (rows) for lake rating table 1	0	<pre>strmflow_module = muskingum_lake and nratetbl > 0</pre>
nstage2	Maximum number of lake elevations values (rows) for lake rating table 2	0	<pre>strmflow_module = muskingum_lake and nratetbl > 1</pre>
nstage3	Maximum number of lake elevations values (rows) for lake rating table 3	0	strmflow_module = muskingum lake and nratetbl > 2
nstage4	Maximum number of lake elevations values (rows) for lake rating table 4	0	<pre>strmflow_module = muskingum_lake and nratetbl > 3</pre>
	Fixed dimensions		
ndays	Maximum number of days in a year	366	optional
nlapse	Number of lapse rates in X, Y, and Z directions	3	<pre>precip_module = xyz_dist</pre>
nmonths	Number of months in a year	12	optional
one	Dimension of scalar parameters and variables	1	optional

¹All associated data specified in Data File can be used for calibration purposes.

²Use of **nssr** and **ngw** not equal to **nhru** is deprecated.

³Dimensions that do not have an associated parameter specified in the Parameter File or variable specified in the Data File are optional.

Table 1-2. Parameters specified in the Control File for the Precipitation-Runoff Modeling System, version 4 (PRMS-IV). [Data Type: 1=integer, 2=single precision floating point (real), 3=double precision floating point (double); 4=character string; HRU, hydrologic response unit; GWR, groundwater reservoir; CBH, climate-by-HRU; ET, evapotranspiration; >, greater than; dimensions **ncascade**, **ncascdgw**, and **nsub** defined in table 1-1; the first two blocks of control parameters listed in the table are recommended for every simulation, though all parameters are optional depending appropriateness of the default values; **green** highlight indicates new for PRMS-V]

Parameter name	Description	Option	Number of Values	Data type	Default value
	Simulation execution and required input	and output files			
data_file ²	Pathname(s) for measured input Data File(s), typically a single Data File is specified	measured input	number of Data Files	4	prms.data
end_time	Simulation end date and time specified in order in the control item as: year, month, day, hour, minute, second	time period	6	1	2001, 9, 30, 0, 0, 0
model_mode	Flag to indicate the simulation mode (PRMS or GSFLOW=version IV parameters; PRMS5 or GSFLOW5=version V parameters; FROST=growing season for each HRU; WRITE_CLIMATE=write CBH files of minimum and maximum air temperature (variables <i>tminf</i> and <i>tmaxf</i> -Fahrenheit); precipitation (variable <i>hru_ppt</i> -inches); solar radiation (variable <i>swrad</i> -Langleys); potential ET (variable <i>potet</i> -inches); and/or transpiration flag (variable <i>transp_on</i> -none); POTET=simulate to potential ET; TRANSPIRE=simulate to transpiration period; DOCUMENTATION=write files of all declared parameters and variables in the executable)	simulation mode selection	1	4	PRMS
model_output_file2	Pathname for Water-Budget File for results module basin sum	simulation output	1	4	prms.out
param_file ²	Pathname(s) for Parameter File(s)	parameter input	number of Parameter Files	4	prms.params
prms_warmup	Number of years to simulate before writing mapped results, Basin, nhru , nsub , or nsegment Summary Output Files	map_resultsON_OFF = 1, basinOutON_OFF = 1, nsubOutON_OFF = 1, nsegmentOutON_OFF = 1 or 2, or nhruOutON_OFF = 1 or 2	1	1	1
start_time	Simulation start date and time specified in order in the control item as: year, month, day, hour, minute, second	time period	6	1	2000, 10, 1, 0, 0, 0
	Module selection and simulation	options			
cascade_flag	Flag to indicate if HRU cascades are computed (0=no; 1=yes; 2=simple cascades defined by parameter hru_segment)	cascade flow with ncascade > 0	1	1	1

Parameter name	Description	Option	Number of Values	Data type	Default value
cascadegw_flag	Flag to indicate if GWR cascades are computed (0=no; 1=yes; 2 = GWR cascades are set equal to the HRU cascades and parameters gw_up_id , gw_strmseg_down_in , gw_down_id , and gw_pct_up are not required)	cascade flow with ncascdgw > 0	1	1	1
dprst_flag	Flag to indicate if depression-storage simulation is computed (0=no; 1=yes)	surface-depression storage	1	1	0
et_module	<pre>Module name for potential evapotranspiration method (climate_hru, potet_jh, potet_hamon, potet_hs, potet_pt, potet_pm, potet_pm_sta, or potet_pan</pre>	module selection	1	4	potet_jh
gwr_swale_flag	Flag to indicate if GWR swales are allowed (0=no; 1=groundwater flow goes to groundwater sink; 3=groundwater flow goes to stream segment specified using parameter hru_segment	swales	1	1	0
precip_module	Module name for precipitation-distribution method (climate_hru, ide_dist, precip_1sta, precip_dist2, precip_laps, or xyz_dist)	module selection	1	4	precip_1sta
solrad_module	Module name for solar-radiation-distribution method (ccsolrad or ddsolrad)	module selection	1	4	ddsolrad
srunoff_module	Module name for surface-runoff/infiltration computation method (srunoff_carea or srunoff_smidx)	module selection	1	4	srunoff_smidx
strmflow_module	Module name for streamflow routing simulation method (strmflow, muskingum, strmflow_in_out, or muskingum lake)	module selection	1	4	strmflow
subbasin_flag	Flag to indicate if internal subbasin are computed (0=no; 1=yes)	nsub > 0	1	1	1
temp_module	<pre>Module name for temperature-distribution method (climate_hru, temp_lsta, temp_sta, temp_dist2, temp_laps, ide_dist, or xyz_dist)</pre>	module selection	1	4	temp_1sta
transp_module	Module name for transpiration simulation method (climate_hru, transp_frost, or transp_tindex)	module selection	1	4	transp_tindex
	Climate-by-HRU Files				
cbh_binary_flag	Flag to specify whether to input CBH files in a binary format using the samer order of values as the text file version (0=no; 1=yes)	input options	1	1	0
humidity_day ²	Pathname of the CBH file of pre-processed humidity input data for each HRU to specify variable <i>humidity_hru</i> -percentage	<pre>et_module = potet_pm</pre>	1	4	humidity.day
orad_flag	Flag to specify whether or not the variable <i>orad</i> is specified as the last column of the swrad_day CBH file (0=no; 1=yes)	<pre>solrad_module = climate_hru</pre>	1	1	1
potet_day ²	Pathname of the CBH file of pre-processed potential-ET input data for each HRU to specify variable <i>potet</i> -inches	<pre>et_module = climate_hru</pre>	1	4	potet.day

Parameter name	Description	Option	Number of Values	Data type	Default value
precip_day ²	Pathname of the CBH file of pre-processed precipitation input data for each HRU to specify variable <i>precip</i> -inches	<pre>precip_module = climate_hru</pre>	1	4	precip.day
swrad_day ²	Pathname of the CBH file of pre-processed solar-radiation input data for each HRU to specify variable <i>swrad</i> -Langleys	<pre>solrad_module = climate_hru</pre>	1	4	swrad.day
tmax_day ²	Pathname of the CBH file of pre-processed maximum air temperature input data for each HRU to specify variable <i>tmaxf</i> -degrees Fahrenheit	<pre>temp_module = climate_hru</pre>	1	4	tmax.day
tmin_day ²	Pathname of the CBH file of pre-processed minimum air temperature input data for each HRU to specify variable <i>tminf</i> -degrees Fahrenheit	<pre>temp_module = climate_hru</pre>	1	4	tmin.day
transp_day ²	Pathname of the CBH file of pre-processed transpiration on or off flag for each HRU file to specify variable <i>transp_on</i> -none	<pre>transp_module = climate_hru</pre>	1	4	transp.day
windspeed_day ²	Pathname of the CBH file of pre-processed wind speed input data for each HRU to specify variable windspeed_hru-meters/second	<pre>et_module = potet_pm</pre>	1	4	windspeed.day
	Dynamic Parameter Inp				
covden_sum_dynamic	Pathname of the time series of pre-processed values for summer plant-cover density used to set values of covden_sum for each HRU	dyn_covden_flag = 1 or 3	1	4	dyncovsum
covden_win_dynamic	Pathname of the time series of pre-processed values for winter plant-cover density used to set values of covden_win for each HRU	dyn_covden_flag = 2 or 3	1	4	dyncovwin
covtype_dynamic	Pathname of the time series of pre-processed values used to set values of cov_type for each HRU	dyn_covtype_flag = 1	1	4	dyncovtype
dprst_depth_dynamic	Pathname of the time series of pre-processed values used to set values of dprst_depth_avg	<pre>dyn_dprst_flag = 2 or 3</pre>	1	4	dyndprst_depth
dprst_frac_dynamic	Pathname of the time series of pre-processed values used to set values of dprst_frac	$dyn_dprst_flag = 1 \text{ or } 3$	1	4	<pre>dyndprst_frac</pre>
dyn_covden_flag	Flag to indicate if a time series of plant-canopy density values are input in a Dynamic Parameter File(s) (0=no; 1=file covden_sum_dynamic ; 2=file covden_win_dynamic ; 3=both)	dynamic canopy cover density	1	1	0
dyn_covtype_flag	Flag to indicate if a time series of plant-canopy type values are input in Dynamic Parameter File covtype_dynamic (0=no; 1=yes)	dynamic canopy cover type	1	1	0
dyn_dprst_flag	Flag to indicate if a time series of surface-depression values are input in a Dynamic Parameter File(s) (0=no; 1=file dprst_frac_dynamic; 2=file dprst_depth_dynamic; 3=both)	dynamic surface depression	1	1	0
dyn_fallfrost_flag	Flag to indicate if a time series of transpiration start Julian day values are input in a Dynamic Parameter File(s) (0=no; 1 =file fallfrost_dynamic)	<pre>dynamic transpiration and transp_module = transp_frost</pre>	1	1	0

Parameter name	Description	Option	Number of Values	Data type	Default value
dyn_imperv_flag	Flag to indicate if a time series of impervious values are input in a Dynamic Parameter File(s) (0=no; 1=file imperv_frac_dynamic; 2=file imperv_stor_dynamic; 3=both)	dynamic impervious	1	1	0
dyn_intcp_flag	Flag to indicate if a time series of plant canopy interception values are input in a Dynamic Parameter File(s) (0=no; 1=file wrain_intcp_dynamic; 2=file srain_intcp_dynamic; 4=file snow_intcp_dynamic; additive combinations)	dynamic interception	1	1	0
dyn_potet_flag	Flag to indicate if a time series of potential ET coefficient values are input in Dynamic Parameter File potet_coef_dynamic to update coefficients for the specified month for the selected potential ET module specified by control parameter et_module (0=no; 1=parameter jh_coef , pt_alpha , hs_krs , hamon_coef , epan_coef , potet_cbh_adj , and pm_n_coef used in potet_jh, potet_pt, potet_hs, potet_hamon, potet_pan, climate_hru, potet_pm, and potet_pm_sta modules, respectively; 2=parameter jh_coef_hru , pm_d_coef used in potet_jh, potet_pm, and potet_pm_sta modules, respectively)	dynamic potential ET	1	1	0
dyn_radtrncf_flag	Flag to indicate if a time series of solar radiation values are input in Dynamic Parameter File radtrncf_dynamic (0=no; 1=yes)	dynamic solar radiation transmission	1	1	0
dyn_soil_flag	Flag to indicate if a time series of soil-water capacity values are input in a Dynamic Parameter File(s) (0=no; 1=file soilmoist_dynamic only, 2=file soilrechr_dynamic only; 3=both)	dynamic soil moisture	1	1	0
dyn_springfrost_flag	Flag to indicate if a time series of transpiration start Julian day values are input in a Dynamic Parameter File(s) (0=no; 1=file springfrost_dynamic)	<pre>dynamic transpiration and transp_module = transp_frost</pre>	1	1	0
dyn_sro2dprst_perv_flag	Flag to indicate if a time series of fraction of surface runoff from the pervious portion of an HRU are input in Dynamic Parameter File sro2dprst_perv_dyn (0=no; 1=yes)	dynamic surface depression	1	1	0
dyn_sro2dprst_imperv_flag	Flag to indicate if a time series of fraction of surface runoff from the impervious portion of an HRU are input in Dynamic Parameter File sro2dprst_imperv_dynamic (0=no; 1=yes)	dynamic surface depression	1	1	0
dyn_transp_flag	Flag to indicate if a time series of transpiration month values are input in a Dynamic Parameter File(s) (0=no; 1=file transpbeg_dynamic ; 2=file transpend_dynamic only, 3=both)	<pre>dynamic transpiration and transp_module = transp_tindex</pre>	1	1	0
fallfrost_dynamic	Pathname of the time series of pre-processed values for dynamic parameter fall_frost	<pre>dyn_fallfrost_flag = 1 and transp_module = transp_frost</pre>	1	4	dynfallfrost
imperv_frac_dynamic	Pathname of the time series of pre-processed values for dynamic	$\mathbf{dyn_imperv_flag} = 1 \text{ or } 3$	1	4	dynimperv

Parameter name	Description	Option	Number of Values	Data type	Default value
	parameter hru_percent_imperv				
imperv_stor_dynamic	Pathname of the time series of pre-processed values for dynamic parameter imperv_stor_max	dyn_imperv_flag = 2 or 3	1	4	dynimperv
potet_coef_dynamic	Pathname of the time series of pre-processed potential evapotranspiration coefficient values where the parameter is dependent on the value of et_module	$dyn_potet_flag = 1 \text{ or } 2$	1	4	dynpotetcoef
radtrncf_dynamic	Pathname of the time series of pre-processed values for dynamic parameter rad_trncf	$dyn_radtrncf_flag = 1$	1	4	dynradtrncf
snow_intcp_dynamic	Pathname of the time series of pre-processed values for dynamic parameter snow_intcp	dyn_intcp_flag = 4, 5, 6, or 7	1	4	dynsnowintcp
soilmoist_dynamic	Pathname of the time series of pre-processed values for dynamic parameter soil_moist_max	$dyn_soil_flag = 1 \text{ or } 3$	1	4	dynsoilmoist
soilrechr_dynamic	Pathname of the time series of pre-processed values for dynamic parameter soil_rechr_max_frac	dyn_soil_flag = 2 or 3	1	4	dynsoilrechr
springfrost_dynamic	Pathname of the time series of pre-processed values for dynamic parameter spring_frost	<pre>dyn_springfrost_flag = 1 and transp_module = transp_frost</pre>	1	4	dynspringfrost
srain_intcp_dynamic	Pathname of the time series of pre-processed values for dynamic parameter srain_intcp	dyn_intcp_flag = 2, 3, 6, or 7	1	4	dynsrainintcp
sro2dprst_perv_dynamic	Pathname of the time series of pre-processed values for dynamic parameter sro_to_dprst_perv	dyn_sro2dprst_perv_flag = 1	1	4	dynsrotodprst_ perv
sro2dprst_imperv_dynamic	Pathname of the time series of pre-processed values for dynamic parameter sro_to_dprst_imperv		1	4	<pre>dynsrotodprst_ imperv</pre>
transpbeg_dynamic	Pathname of the time series of pre-processed values for dynamic parameter transp_beg	<pre>dyn_transp_flag = 1 or 3 and transp_module = transp_tindex</pre>	1	4	dyntranspbeg
transpend_dynamic	Pathname of the time series of pre-processed values for dynamic parameter transp_end	<pre>dyn_transp_flag = 2 or 3 and transp_module = transp_tindex</pre>	1	4	dyntranspend
wrain_intcp_dynamic	Pathname of the time series of pre-processed values for dynamic parameter wrain_intcp	dyn_intcp_flag = 1, 3, 5, or 7	1	4	dynwrainintcp
	Water Use Input				
dprst_transfer_file	Pathname of the time series of pre-processed flow rates for transfers from surface-depression storage	<pre>dprst_transferON_OFF = 1 and dprst_flag = 1</pre>	1	4	dprst.transfer
dprst_transferON_OFF	Flag to indicate to use time series of surface-depression transfer flow rates from the dprst_transfer_file (0=no; 1=yes)	surface depression transfer and dprst_flag = 1	1	1	0
external_transfer_file	Pathname of the time series of pre-processed flow rates for transfers	external_transferON_OFF	1	4	ext.transfer

Parameter name	Description	Option	Number of Values	Data type	Default value
	from external sources	= 1			
external_transferON_OFF	Flag to indicate to use external transfer flow rates from the external_transfer_file (0=no; 1=yes)	external transfer	1	1	0
gwr_transfer_file	Pathname of the time series of pre-processed flow rates for transfers from groundwater reservoir storage	gwr_transferON_OFF = 1	1	4	gwr.transfer
gwr_transferON_OFF	Flag to indicate to use groundwater transfer flow rates from the gwr_transfer_file (0=no; 1=yes)	groundwater transfer	1	1	0
lake_transfer_file	Pathname of the time series of pre-processed flow rates for transfers from lake HRUs	lake_transferON_OFF = 1	1	4	lake.transfer
lake_transferON_OFF	Flag to indicate to use lake HRU transfer flow rates from the lake_transfer_file (0=no; 1=yes)	lake water transfer	1	1	0
segment_transfer_file	Pathname of the time series of pre-processed flow rates for transfers from stream segments	segment_transferON_OFF = 1	1	4	seg.transfer
segment_transferON_OFF	Flag to indicate to use stream segment transfer flow rates from the segment_transfer_file (0=no; 1=yes)	stream water transfer	1	1	0
	Debug options				
cbh_check_flag	Flag to indicate if CBH values are validated each time step (0=no; 1=yes)	CBH input	1	1	1
parameter_check_flag	Flag to indicate if selected parameter values validation checks are treated as warnings or errors (0=no; 1=yes; 2=check parameters and then stop)	parameter validation check	1	1	1
print_debug ¹	Flag to indicate type of debug output	debug output	1	1	0
	(-2=minimal output to screen and no model_output_file; -1				
	=minimize screen output; 0=none; 1=water balances; 2=basin module; 4=basin sum module; 5=soltab module;				
	7=soilzone module; 9=snowcomp module; 13=cascade				
	module; 14=subbasin module)				
	Statistic Variables (statvar) F				
nstatVars	Number of variables to include in Statistics Variables File and names specified in statVar_names	statsON_OFF = 1	1	1	0
stat_var_file ²	Pathname for Statistics Variables File	$statsON_OFF = 1$	1	4	statvar.out
statsON_OFF	Switch to specify whether or not the Statistics Variables File is generated (0=no; 1=statvar text format; 2=CSV format)	$\mathbf{statsON_OFF} = 1$	1	1	0
statVar_element	List of identification numbers corresponding to variables specified in statVar_names list (1 to variable's dimension size)	$\mathbf{statsON_OFF} = 1$	nstatVars	4	none
statVar_names	List of variable names for which output is written to Statistics Variables File	$\mathbf{statsON_OFF} = 1$	nstatVars	4	none

Parameter name	Description	Option	Number of Values	Data type	Default value
	Initial Condition Files				
init_vars_from_file	Flag to specify whether or not the Initial Conditions File is specified as an input file (0=no; 1=yes; 2=yes and use parameters dprst_frac_init, snowpack_init, segment_flow_init, elevlake_init, gwstor_init, and (soil_rechr_init, soil_moist_init, ssstor_init for model_mode=PRMS or GSFLOW) or (soil_rechr_init_frac, soil_moist_init_frac, ssstor_init_frac for model_mode=PRMS5 or GSFLOW5); 3=yes and use parameter snowpack_init; 4=yes and use parameter elevlake_init; 5=yes and use parameters (soil_rechr_init, soil_moist_init, ssstor_init for model_mode=PRMS or GSFLOW) or (soil_rechr_init_frac, soil_moist_init_frac, soil_moist_init_frac for model_mode=PRMS5 or GSFLOW5); 6=yes and use parameter gwstor_init; 7=yes and use parameter dprst_frac_init)	initial condtions	1	1	0
save_vars_to_file	Flag to determine if an Initial Conditions File will be generated at the end of simulation $(0=no; 1=yes)$	initial condtions	1	1	0
var_init_file ²	Pathname for Initial Conditions input file	init_vars_from_file = 1	1	4	prms_ic.in
var_save_file ²	Pathname for the Initial Conditions File to be generated at end of simulation	save_vars_to_file = 1	1	4	prms_ic.out
	Animation Files				
ani_output_file ²	Pathname for Animation Files(s) to which a filename suffix based on dimension name associated with selected variables is appended	aniOutON_OFF = 1	1	4	animation.out
aniOutON_OFF	Switch to specify whether or not Animation File(s) are generated (0=no; 1=yes)	animation output	1	1	0
aniOutVar_names	List of variable names for which all values of the variable (that is, the entire dimension size) for each time step are written Animation Dimension Files(s)	aniOutON_OFF = 1	naniOutVars	4	none
naniOutVars	Number of output variables specified in the aniOutVar_names list	${\bf aniOutON_OFF}=1$	1	1	0
	Basin Summary Results File				
basinOutBaseFileName ²	String to define the prefix for each basin summary output file.	${\bf basinOutON_OFF}=1$	1	4	none
basinOutON_OFF	Switch to specify whether or not basin summary output files are generated (0=no; 1=yes)	basin summary results	1	1	0
basinOutVar_names	List of variable names for which output is written to basin summary Comma Separated Values (CSV) output file(s). Each variable is written to files in the order specified in basinOutVars with the prefix of each file equal to the value of basinOutBaseFileName . The suffix of the files is based on the value of basinOut_freq and will be .csv; _meanyearly.csv; _yearly.csv; _meanmonthly.csv; or	basinOutON_OFF = 1	basinOutVars	4	none

Parameter name	Description	Option	Number of Values	Data type	Default value
	_monthly.csv. Variables must be of type real or double				
basinOutVars	Number of variables to include in basin summary output file(s)	$\mathbf{basinOutON_OFF} = 1$	1	1	0
basinOut_freq	Output frequency and type (1=daily; 2=monthly; 3=both; 4=mean monthly; 5=mean yearly; 6=yearly)	basinOutON_OFF = 1	1	1	1
	Mapped Results Files				
mapOutON_OFF	Switch to specify whether or not mapped output file(s) by a specified number of columns (parameter ncol) of daily, monthly, yearly, or total simulation results is generated (0=no; 1=yes)	mapped results	1	1	0
mapOutVar_names	List of variable names for which output is written to mapped output files(s); variables must be of type real or double.	map_resultsON_OFF = 1	nmapOutVars	4	none
nmapOutVars	Number of variables to include in mapped output file(s)	$map_resultsON_OFF = 1$	1	1	0
	Nhru Summary Results Fil	es			
$nhruOutBaseFileName^2\\$	String to define the prefix for each nhru summary output file.	nhruOutON_OFF = 1 or 2	1	4	none
nhruOutON_OFF	Switch to specify whether or not nhru summary output files are generated (0=no; 1=yes; 2=yes and use values of nhm_id as column heading)	nhru summary results	1	1	0
nhruOutVar_names	List of variable names for which output is written to nhru summary Comma Separated Values (CSV) output files(s). Each variable is written to a separate file with the prefix of each file equal to the value of nhruOutBaseFileName ; variables must be of type real or double. Each variable is written to a separate file with the prefix of each file equal to the value of nhruOutBaseFileName . The suffix of the files is based on the value of nhruOut_freq and will be .csv; _meanyearly.csv; _yearly.csv; _meanmonthly.csv; or _monthly.csv. Variables must be of type real or double	nhruOutON_OFF = 1 or 2	nhruOutVars	4	none
nhruOutVars	Number of variables to include in nhru summary output file(s)	nhruOutON_OFF = 1 or 2	1	1	0
nhruOut_format	Format of values (1=scientific notation with 4 significant digits (default); 2=2 decimal places; 3=3 decimal places; 4=4 decimal places; 5=5 decimal places)	nhruOutON_OFF = 1 or 2	1	1	1
nhruOut_freq	Output frequency and type (1=daily; 2=monthly; 3=both; 4=mean monthly; 5=mean yearly; 6=yearly)	nhruOutON_OFF = 1 or 2	1	1	1
	Nsub Summary Results Fil				
nsubOutBaseFileName ²	String to define the prefix for each nsub summary output file.	$nsubOutON_OFF = 1$	1	4	none
nsubOutON_OFF	Switch to specify whether or not nsub summary output files are generated (0=no; 1=yes)	nsub summary results	1	1	0
nsubOutVar_names	List of variable names for which output is written to nsub summary Comma Separated Values (CSV) output files(s). Each variable is	nsubOutON _OFF = 1	nsubOutVars	4	none

Parameter name	Description	Option	Number of Values	Data type	Default value
	written to a separate file with the prefix of each file equal to the value of nsubOutBaseFileName ; variables must be of type real or double. Each variable is written to a separate file with the prefix of each file equal to the value of nsubOutBaseFileName . The suffix of the files is based on the value of nsubOut_freq and will be .csv; _meanyearly.csv; _yearly.csv; _meanmonthly.csv; or _monthly.csv. Variables must be of type real or double				
nsubOutVars	Number of variables to include in nsub summary output file(s)	$\mathbf{nsubOutON} \ _\mathbf{OFF} = 1$	1	1	0
nsubOut_format	Format of values (1=scientific notation with 4 significant digits (default); 2=2 decimal places; 3=3 decimal places; 4=4 decimal places; 5=5 decimal places)	nsubOutON_OFF = 1	1	1	1
nsubOut_freq	Output frequency and type (1=daily; 2=monthly; 3=both; 4=mean monthly; 5=mean yearly; 6=yearly)	nsubOutON _OFF = 1	1	1	1
	Nsegment Summary Results				
nsegmentOutBaseFileName ²	String to define the prefix for each nsegment summary output file.	nsegmentOutON_OFF = 1 or 2	1	4	none
nsegmentOutON_OFF	Switch to specify whether or not nsegment summary output files are generated (0=no; 1=yes; 2=yes and use values of nhm_seg as column heading)	nsegment summary results	1	1	0
nsegmentOutVar_names	List of variable names for which output is written to nsegment summary Comma Separated Values (CSV) output files(s). Each variable is written to a separate file with the prefix of each file equal to the value of nsegmentOutBaseFileName ; variables must be of type real or double. Each variable is written to a separate file with the prefix of each file equal to the value of nsegmentOutBaseFileName . The suffix of the files is based on the value of nsegmentOut_freq and will be .csv; _meanyearly.csv; _yearly.csv; _meanmonthly.csv; or _monthly.csv. Variables must be of type real or double	nsegmentOutON_OFF = 1 or 2	nsubOutVars	4	none
nsegmentOutVars	Number of variables to include in nsegment summary output file(s)	nsegmentOutON_OFF = 1 or 2	1	1	0
nsegmentOut_format	Format of values (1=scientific notation with 4 significant digits (default); 2=2 decimal places; 3=3 decimal places; 4=4 decimal places; 5=5 decimal places)	nsegmentOutON_OFF = 1 or 2	1	1	1
nsegmentOut_freq	Output frequency and type (1=daily; 2=monthly; 3=both; 4=mean monthly; 5=mean yearly; 6=yearly)	nsegmentOutON_OFF = 1 or 2	1	1	1
	PRMS Summary Results 1	Files			
csvON_OFF	Switch to specify whether or not common-separated values (CSV)	PRMS summary results	1	1	0

Parameter name	Parameter name Description		Number of Values	Data type	Default value	
	summary output files are generated (0=no; 1=yes)					
csv_output_file ²	Pathname of CSV output file	$\mathbf{csvON_OFF} = 1$	1	4	none	
	Runtime graphs					
dispGraphsBuffSize	Number of time steps to wait before updating the runtime graph	ndispGraphs > 0	1	1	50	
dispVar_element	List of identification numbers corresponding to variables specified in dispVar_names list (1 to variable's dimension size)	ndispGraphs > 0	number of variables	4	none	
dispVar_names	List of variable names for which plots are output to the runtime graph	ndispGraphs > 0	number of variables	4	none	
dispVar_plot	List of variable names for which plots are output to the runtime graph	ndispGraphs > 0	number of variables	4	none	
executable_desc	Descriptive text to identify the PRMS executable	ndispGraphs > 0	1	4	MOWS executable	
executable_model ²	Pathname (full or relative) of the PRMS executable	ndispGraphs > 0	1	4	prmsIV	
initial_deltat	Initial time step for the simulation	ndispGraphs > 0	1	2	24.0	
ndispGraphs	Number of plots included in the runtime graph	graphical output	1	1	0	

¹File and screen output options: 1=water balance output files written in current directory, for intop module file intop.wbal; for snowcomp module snowcomp.wbal; for srunoff module srunoff_smidx.wbal or srunoff_carea.wbal; for soilzone module soilzone.wbal; for gwflow module gwflow.wbal; 2=basin module output written to screen; 4=basin_sum debug information written to file basin_sum.dbg in current directory; 5=soltab module output written to the file soltab_debug in current directory; 7=soilzone debug information concerning input parameter consistency written to file soilzone.dbg in current directory; 9=arrays of net_rain, net_snow, and snowmelt written to screen; 13=subbasin error and warning messages and cascade paths are written to the file cascade.msgs in current directory; 14=subbasin computation order written to file tree_structure in current directory.

²Pathnames for all files can have a maximum of 256 characters.

Table 1-3. Parameters listed by usage with the associated modules in which they are used for the Precipitation-Runoff Modeling System, version 4 (PRMS-IV).

[HRU, hydrologic response unit; GWR, groundwater reservoir; cfs, cubic feet per second; cms, cubic meters per second; ET, evapotranspiration; dday, degree-day, the amount a day's average temperature departed from 65 degrees Fahrenheit; POI, point-of-interest; >, greater than; dimensions defined in table 1-1; control parameters **temp_module**, **precip_module**, **solrad_module**, **et_module**, **transp_module**, **srunoff_module**, **strmflow_module**, **model_mode**, **dprst_flag**, **subbasin_flag**, **cascade_flag**, **cascadegw_flag**, and **mapOutON_OFF** defined in table 1-2; **green** highlight indicates new for PRMS-V; **blue** highlight indicates deprecated but retaine for PRMS-IV downward compatibility; **strikethrough** indicates items removed]

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
	Basic	physical attributes					
elev_units	Flag to indicate the units of elevation values (0=feet; 1=meters)	one	integer	none	0 or 1	0	required
hru_area	Area of each HRU	nhru	real	acres	0.0001 to 1.0E9	1.0	required
hru_aspect	Aspect of each HRU	nhru	real	angular degrees	0.0 to 360.0	0.0	required ⁶
hru_elev	Mean elevation for each HRU	nhru	real	elev_units	-1,000.0 to 30,000.0	0.0	required
hru_lat	Latitude of each HRU	nhru	real	degrees North	-90.0 to 90.0	40.0	required ⁶
hru_lon	Longitude of each HRU	nhru	real	degrees East	-360.0 to 360.0	-105.0	optional
hru_slope	Slope of each HRU	nhru	real	decimal fraction	0.0 to 10.0	0.0	required ⁶
hru_type ⁵	Type of each HRU (0=inactive; 1=land; 2=lake; 3=swale)	nhru	integer	none	0 to 3	1	required
nhm_id	National Hydrologic Model HRU ID	nhru	integer	none	1 to 9999999	1	optional
nhm_seg	National Hydrologic Model segment ID	nsegment	integer	none	1 to 9999999	1	optional
parent_gw	Lumen index in parent model for each GWR	ngw	integer	none	1 to 9999999	1	optional
parent_hru	Lumen index in parent model for each HRU	nhru	integer	none	1 to 9999999	1	optional
parent_poigages	Lumen index in parent model for each POI gage	npoigages	integer	none	1 to 9999999	1	optional
parent_segment	Lumen index in parent model for each segment	nsegment	integer	none	1 to 9999999	1	optional

Parameter name	Description	Dimension ¹	Туре	Units	Range	Default	Required/condition
parent_ssr	Lumen index in parent model for each SSR	nssr	integer	none	1 to 9999999	1	optional
	Me	asured input					
outlet_sta	Index of measured streamflow station corresponding to the basin outlet	one	integer	none	0 to nobs	0	nobs > 0
precip_units	Flag to indicate the units of measured precipitation values (0=inches; 1=mm)	one	integer	none	0 or 1	0	required
rad_conv	Conversion factor to Langleys for measured solar radiation	one	real	Langleys/ radiation units	0.1 to 100.0	1.0	nsol > 0
rain_code	Monthly (January to December) flag indicating rule for precipitation measurement station use (1=only precipitation if the regression stations have precipitation; 2=only precipitation if any station in the basin has precipitation; 3=precipitation if module xyz_dist computes any; 4=only precipitation if rain_day variable is set to 1; 5=only precipitation if psta_freq_nuse stations have precipitation)	nmonths	integer	none	1 to 5	2	<pre>precip_module = xyz_dist</pre>
runoff_units	Measured streamflow units (0=cfs; 1=cms)	one	integer	none	0 or 1	0	nobs > 0
temp_units	Flag to indicate the units of measured air-temperature values (0=Fahrenheit; 1=Celsius)	one	integer	none	0 or 1	0	required
irr_type	Method of application of water for each application time-series (0=sprinkler (intercep applies); 1=furrow/drip (no intercept); 2=ignore)	er Use input nhru	real	none	0 to 2	0	nwateruse = 1
	Air temperature a	nd precipitation d	istribution				
adjmix_rain	Monthly (January to December) factor to adjust rain proportion in a mixed rain/snow event	nhru, nmonths	real	decimal fraction	0.0 to 3.0	1.0	required
adjust_rain	Monthly (January to December) rain downscaling adjustment factor for each precipitation measurement station	nrain, nmonths	real	decimal fraction	-0.5 to 0.5	-0.4	<pre>precip_module = ide_dist or xyz dist</pre>
adjust_snow	Monthly (January to December) snow downscaling adjustment factor for each precipitation measurement station	nrain, nmonths	real	decimal fraction	-0.5 to 0.5	-0.4	<pre>precip_module = ide_dist or xyz dist</pre>
basin_tsta	Index of temperature station used to compute basin temperature values	one	integer	none	0 to ntemp	0	<pre>temp_module = temp_1sta, temp_sta, temp_dist2, or temp_laps</pre>

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
conv_flag	Elevation conversion flag (0=none; 1=feet to meters; 2=meters to feet)	one	integer	none	0 to 2	0	<pre>precip_module and temp_module = xyz dist</pre>
dist_exp	Exponent for inverse distance calculations	one	real	none	0.0 to 10.0	2.0	<pre>precip_module and temp_module = ide_dist</pre>
dist_max	Maximum distance from an HRU to a measurement station for use in calculations	one	real	feet	0.0 to 1.0E9	1.0E9	<pre>precip_module = precip_dist2 and/or temp_module = temp_dist2</pre>
hru_plaps	Index of the lapse precipitation measurement station used for lapse rate calculations for each HRU	nhru	integer	none	0 to nrain	0	<pre>precip_module = precip laps</pre>
hru_psta	Index of the base precipitation measurement station used for lapse rate calculations for each HRU	nhru	integer	none	0 to nrain	0	<pre>precip_module = precip_1sta or precip_laps</pre>
hru_tlaps	Index of the lapse temperature station used for lapse rate calculations	nhru	integer	none	0 to ntemp	0	<pre>temp_module = temp_laps</pre>
hru_tsta	Index of the base temperature station used for lapse rate calculations	nhru	integer	none	0 to ntemp	0	<pre>temp_module = temp_1sta, temp_sta, or temp_laps</pre>
hru_x	Longitude (X) for each HRU in albers projection	nhru	real	meters	-1.0E7 to 1.0E7	0.0	<pre>precip_module and temp_module = ide_dist or xyz_dist</pre>
hru_xlong	Longitude of each HRU for the centroid, State Plane Coordinate System	nhru	real	feet	-1.0E9 to 1.0E9	0.0	<pre>temp_module = temp_dist2 or precip_module = precip_dist2</pre>
hru_y	Latitude (Y) for each HRU in albers projection	nhru	real	meters	-1.0E7 to 1.0E7	0.0	<pre>precip_module and temp_module = ide_dist or xyz dist</pre>
hru_ylat	Latitude of each HRU for the centroid, State Plane Coordinate System	nhru	real	feet	-1.0E9 to 1.0E9	0.0	temp_module = temp_dist2 and/or precip_module = precip_dist2
lapsemax_max	Monthly (January to December) maximum lapse rate to constrain lowest maximum lapse rate based on historical daily air temperatures for all air temperature-	nmonths	real	temp_units/ feet	-3.0 to 3.0	2.0	<pre>temp_module = temp_dist2</pre>

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
1	measurement stations	41	1	4	7.04	<i>(5</i>	A
lapsemax_min	Monthly (January to December) maximum lapse rate to constrain lowest minimum lapse rate on the basis of historical daily air temperatures for all air temperature-measurement stations	nmonths	real	temp_units/ feet	-7.0 to -3.0	-6.5	<pre>temp_module = temp_dist2</pre>
lapsemin_max	Monthly (January to December) minimum lapse rate to constrain lowest maximum lapse rate on the basis of historical daily air temperatures for all air temperature- measurement stations	nmonths	real	temp_units/ feet	-2.0 to 4.0	3.0	<pre>temp_module = temp_dist2</pre>
lapsemin_min	Monthly (January to December) minimum lapse rate to constrain lowest minimum lapse rate on the basis of historical daily air temperatures for all air temperature-measurement stations	nmonths	real	temp_units/ feet	-7.0 to -3.0	-4.0	<pre>temp_module = temp_dist2</pre>
max_lapse	Monthly (January to December) maximum air temperature lapse rate for each direction (X, Y, and Z))	nlapse, nmonths	real	none	-100.0 to 100.0	0.0	temp_module = xyz_dist
max_missing	Maximum number of consecutive missing values allowed for any air temperature measurement station; missing value set to last valid value; 0=unlimited	one	integer	none	0 to 10	3	<pre>temp_module = temp_1sta, temp_sta, or temp_laps</pre>
max_psta	Maximum number of precipitation measurement stations to distribute to an HRU	one	integer	none	0 to nrain	0	<pre>precip_module = precip dist2</pre>
max_tsta	Maximum number of air temperature measurement stations to use for distributing temperature to any HRU	one	integer	none	0 to ntemp	0	<pre>temp_module = temp_dist2</pre>
maxday_prec	Maximum measured precipitation value above which precipitation is assumed to be in error	one	real	precip_units	0.0 to 20.0	15.0	<pre>precip_module = precip dist2</pre>
min_lapse	Monthly (January to December) minimum air temperature lapse rate for each direction (X, Y, and Z)	nlapse, nmonths	real	none	-100.0 to 100.0	0.0	<pre>temp_module = xyz_dist</pre>
monmax	Monthly maximum air temperature to constrain lowest maximum air temperatures for bad values on the basis of historical temperature for all measurement stations	nmonths	real	temp_units	0.0 to 115.0	100.0	<pre>temp_module = temp_dist2</pre>
monmin	Monthly minimum air temperature to constrain lowest maximum air temperatures for bad values on the basis of historical temperature for all measurement stations	nmonths	real	temp_units	-60.0 to 65.0	-60.0	<pre>temp_module = temp_dist2</pre>
ndist_psta	Number of precipitation measure stations for inverse distance calculations	one	integer	none	0 to nrain	0	<pre>precip_module = ide_dist</pre>
ndist_tsta	Number of air temperature measurement stations for inverse distance calculations	one	integer	none	0 to ntemp	0	<pre>temp_module = ide_dist</pre>
padj_rn	Monthly (January to December) factor to adjust precipitation lapse rate computed between station hru_psta and station hru_plaps ; positive factors are	nrain, nmonths	real	precip_units	-2.0 to 10.0	1.0	<pre>precip_module = precip_laps</pre>

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
	multiplied times the lapse rate and negative factors are made positive and substituted for the computed lapse rate						
padj_sn	Monthly (January to December) factor to adjust precipitation lapse rate computed between station hru_psta and station hru_plaps ; positive factors are multiplied times the lapse rate and negative factors are made positive and substituted for the computed lapse rate	nrain, nmonths	real	precip_units	-2.0 to 10.0	1.0	<pre>precip_module = precip_laps</pre>
pmn_mo	Mean monthly (January to December) precipitation for each lapse precipitation measurement station	nrain, nmonths	real	precip_units	0.00001 to 100.0	1.0	<pre>precip_module = precip_laps</pre>
potet_cbh_adj	Monthly (January to December) adjustment factor to potential evapotranspiration specified in CBH Files for each HRU	nhru, nmonths	real	decimal fraction	0.5 to 1.5	1.0	<pre>et_module = climate_hru</pre>
ppt_add	Mean value for the precipitation measurement station transformation equation	one	real	precip_units	-10.0 to 10.0	0.0	<pre>precip_module = xyz_dist</pre>
ppt_div	Standard deviation for the precipitation measurement station transformation equation (not 0.0)	one	real	precip_units	-10.0 to 10.0	1.0	<pre>precip_module = xyz_dist</pre>
ppt_lapse	Monthly (January to December) precipitation lapse rate for each direction (X, Y, and Z)	nlapse, nmonths	real	none	-10.0 to 10.0	0.0	<pre>precip_module = xyz_dist</pre>
prcp_wght_dist	Monthly (January to December) precipitation weighting function for inverse distance calculations	nmonths	real	decimal fraction	0.0 to 1.0	0.5	<pre>precip_module = ide_dist</pre>
psta_elev	Elevation of each precipitation measurement station	nrain	real	elev_units	-300.0 to 30,000.0	0.0	<pre>precip_module = ide_dist, xyz_dist, or precip laps</pre>
psta_freq_nuse	The subset of precipitation measurement stations used to determine if there is precipitation in the basin (0=station not used; 1=station used)	nrain	integer	none	0 or 1	1	<pre>precip_module = xyz_dist</pre>
psta_mon	Monthly (January to December) factor to precipitation at each measured station to adjust precipitation distributed to each HRU to account for differences in elevation, and so forth	nrain, nmonths	real	precip_units	0.0 to 50.0	1.0	<pre>precip_module = precip_dist2</pre>
psta_month_ppt	Average monthly (January to December) maximum precipitation at each precipitation measurement station	nrain, nmonths	real	precip_units	0.0 to 20.0	0.0	<pre>precip_module = xyz_dist</pre>
psta_nuse	The subset of precipitation measurement stations used in the distribution regression (0=station not used; 1=station used)	nrain	integer	none	0 or 1	1	<pre>precip_module = ide_dist or xyz_dist</pre>
psta_x	Longitude (X) for each precipitation measurement station in albers projection	nrain	real	meters	-1.0E7 to 1.0E7	0	<pre>precip_module = ide_dist or</pre>

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
							xyz_dist
psta_xlong	Longitude of each precipitation measurement station, State Plane Coordinate System	nrain	real	feet	-1.0E9 to 1.0E9	0.0	<pre>precip_module = precip dist2</pre>
psta_y	Latitude (Y) for each precipitation measurement station in albers projection	nrain	real	meters	-1.0E7 to 1.0E7	0	<pre>precip_module = ide_dist or xyz_dist</pre>
psta_ylat	Latitude of each precipitation measurement station, State Plane Coordinate System	nrain	real	feet	-1.0E9 to 1.0E9	0.0	<pre>precip_module = precip dist2</pre>
rain_adj	Monthly (January to December) factor to adjust measured precipitation on each HRU to account for differences in elevation, and so forth	nhru, nmonths	real	decimal fraction	0.5 to 2. <mark>5</mark>	1.0	<pre>precip_module = precip_1sta</pre>
rain_cbh_adj	Monthly (January to December) adjustment factor to measured precipitation determined to be rain on each HRU to account for differences in elevation, and so forth	nhru, nmonths	real	decimal fraction	0.5 to 2.0	1.0	<pre>precip_module = climate_hru</pre>
rain_mon	Monthly (January to December) factor to rain on each HRU to adjust precipitation distributed to each HRU to account for differences in elevation, and so forth	nhru, nmonths	real	precip_units	0.0 to 50.0	1.0	<pre>precip_module = precip_dist2</pre>
snow_adj	Monthly (January to December) factor to adjust measured precipitation on each HRU to account for differences in elevation, and so forth	nhru, nmonths	real	decimal fraction	0.5 to 2. <mark>5</mark>	1.0	<pre>precip_module = precip_1sta</pre>
snow_cbh_adj	Monthly (January to December) adjustment factor to measured precipitation determined to be snow on each HRU to account for differences in elevation, and so forth	nhru, nmonths	real	decimal fraction	0.5 to 2.0	1.0	<pre>precip_module = climate_hru</pre>
snow_mon	Monthly (January to December) factor to snow on each HRU to adjust precipitation distributed to each HRU to account for differences in elevation, and so forth	nhru, nmonths	real	precip_units	0.0 to 50.0	1.0	<pre>precip_module = precip_dist2</pre>
solrad_elev	Elevation of the solar radiation station used for the degree-day curves to distribute temerature	one	real	meters	-300.0 to 30,000.0	0.0	<pre>temp_module = ide_dist or xyz dist</pre>
temp_wght_dist	Monthly (January to December) temperature weighting function for inverse distance calculations	nmonths	real	decimal fraction	0.0 to 1.0	0.5	temp_module = ide dist
tmax_add	Mean value for the air-temperature measurement station transformation equation for maximum air temperature	one	real	temp_units	-100.0 to 100.0	0.0	temp_module = xyz dist
tmax_adj	Adjustment to maximum air temperature for each HRU, estimated on the basis of slope and aspect	nhru, nmonths	real	temp_units	-10.0 to 10.0	0.0	<pre>temp_module = temp_1sta, temp_sta, temp_laps, temp_dist2, ide_dist or xyz_dist</pre>

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
tmax_allrain	Monthly (January to December) maximum air temperature when precipitation is assumed to be rain; if HRU air temperature is greater than or equal to this value, precipitation is rain	nhru, nmonths	real	temp_units	-8.0 to 75.0	38.0	model_mode = PRMS or GSFLOW
tmax_allrain_dist	Monthly (January to December) maximum air temperature when precipitation is assumed to be rain; if HRU air temperature is greater than or equal to this value, precipitation is rain	nmonths	real	temp_units	-8.0 to 75.0	38.0	<pre>temp_module = xyz_dist</pre>
tmax_allrain_offset	Monthly (January to December) maximum air temperature when precipitation is assumed to be rain; if HRU air temperature is greater than or equal to tmax_allsnow plus this value, precipitation is rain	nhru, nmonths	real	temp_units	0.0 to 50.0	38.0	<pre>model_mode = PRMS5 or GSFLOW5</pre>
tmax_allrain_sta	Monthly (January to December) maximum air temperature when precipitation is assumed to be rain; if precipitation measurement air temperature is greater than or equal to this value, precipitation is rain	nrain, nmonths	real	temp_units	-8.0 to 75.0	38.0	<pre>temp_module = ide_dist</pre>
tmax_allsnow	Monthly (January to December) maximum air temperature when precipitation is assumed to be snow; if HRU air temperature is less than or equal to this value, precipitation is snow	nhru, nmonths	real	temp_units	-10.0 to 40.0	32.0	required
tmax_allsnow_dist	Maximum air temperature when precipitation is assumed to be snow; if mean air temperature is less than or equal to this value, precipitation is snow	one	real	temp_units	-10.0 to 40.0	38.0	<pre>temp_module = xyz_dist</pre>
tmax_allsnow_sta	Monthly (January to December) maximum air temperature when precipitation is assumed to be snow; if precipitation measurement air temperature is less than or equal to this value, precipitation is snow	nrain, nmonths	real	temp_units	-10.0 to 40.0	38.0	<pre>temp_module = ide_dist</pre>
tmax_cbh_adj	Monthly (January to December) adjustment factor to maximum air temperature for each HRU, estimated on the basis of slope and aspect	nhru, nmonths	real	temp_units	-10.0 to 10.0	0.0	<pre>temp_module = climate_hru</pre>
tmax_div	Standard deviation for the air-temperature-measurement station transformation equation for maximum air temperature (not 0.0)	one	real	temp_units	-100.0 to 100.0	1.0	<pre>temp_module = xyz_dist</pre>
tmax_lapse	Monthly (January to December) values representing the change in maximum air temperature per 1,000 elev_units of elevation change for each HRU	nhru, nmonths	real	temp_units/ elev_units	-20.0 to 20.0	3.0	<pre>temp_module = temp_1sta</pre>
tmin_add	Mean value for the air-temperature-measurement station transformation equation for minimum air temperature	one	real	temp_units	-100.0 to 100.0	0.0	<pre>temp_module = xyz_dist</pre>
tmin_adj	Adjustment to minimum air temperature for each HRU, estimated on the basis of slope and aspect	nhru, nmonths	real	temp_units	-10.0 to 10.0	0.0	<pre>temp_module = temp_1sta,</pre>

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
							temp_sta,
							temp_laps,
							temp_dist2,
							ide_dist or
tmin abb adi	Monthly (January to December) adjustment factor to	nhru,	rool	tomp units	-10.0 to	0.0	xyz_dist temp_module =
tmin_cbh_adj	minimum air temperature for each HRU, estimated on the basis of slope and aspect	nmonths	real	temp_units	10.0 to	0.0	climate_hru
tmin_div	Standard deviation for the air-temperature-measurement	one	real	$temp_units$	-100.0 to	1.0	temp_module =
	station transformation equation for minimum air				100.0		xyz_dist
4	temperature (not 0.0)	1	1	4	20.04-	2.0	A Jl.
tmin_lapse	Monthly (January to December) values representing the change in minimum air temperature per 1,000	nhru,	real	temp_units/ elev_units	-20.0 to 20.0	3.0	<pre>temp_module = temp_1sta</pre>
	elev_units of elevation change for each HRU	nmonths		elev_uiits	20.0		cemp_rsca
tsta_elev	Elevation of each air-temperature-measurement station	ntemp	real	elev_units	-300.0 to		
0 50 0 _010	Zio i unioni di duan uni domponiuni di mondiun di mondiuni di unioni	р	1001	010 (_01110)	30,000.0		
tsta_month_max	Average monthly (January to December) maximum air	ntemp,	real	temp_units	-100.0 to	0.0	temp_module =
	temperature at each air-temperature-measurement station	nmonths		-	100.0		xyz_dist
tsta_month_min	Average monthly (January to December) minimum air	ntemp,	real	temp_units	-100.0 to	0.0	temp_module =
	temperature at each air-temperature-measurement station	nmonths			100.0		xyz_dist
tsta_nuse	The subset of temperature stations used in the	ntemp	integer	none	0 or 1	0	temp_module =
	distribution regression (0=station not used; 1=station						ide_dist or
tata w	used)	ntomn	maa1	matana	-1.0E7 to	0.0	xyz_dist
tsta_x	Longitude (X) for each air-temperature-measurement station in albers projection	ntemp	real	meters	-1.0E7 to 1.0E7	0.0	<pre>temp_module = ide dist or</pre>
	station in alocis projection				1.027		xyz dist
tsta_xlong	Longitude of each air-temperature-measurement station,	ntemp	real	feet	-1.0E9 to	0.0	temp_module =
usua_mong	State Plane Coordinate System	пстр	Tour	1000	1.0E9	0.0	temp_modele temp_dist2
tsta_y	Latitude (Y) for each air-temperature-measurement	ntemp	real	meters	-1.0E7 to	0.0	temp_module =
•	station in albers projection	_			1.0E7		ide_dist or
							xyz_dist
tsta_ylat	Latitude of each air-temperature-measurement station,	ntemp	real	feet	-1.0E9 to	0.0	temp_module =
	State Plane Coordinate System		_		1.0E9		temp_dist2
x_add	Mean value for the climate station transformation	one	real	meters	-1.0E7 to	0.0	precip_module and
	equation for the longitude (X) coordinate				1.0E7		<pre>temp_module = xyz dist</pre>
x_div	Standard deviation for the climate station transformation	one	real	meters	-1.0E7 to	1.0	precip_module and
A_UIV	equation for the longitude (X) coordinate (not 0.0)	OHE	icai	meters	1.0E7 to	1.0	temp_module =
	equation for the fongitude (11) coordinate (not 0.0)				1.01		xyz_dist
y_add	Mean value for the climate station transformation	one	real	meters	-1.0E7 to	0.0	precip_module and
-							

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
	equation for the latitude (Y) coordinate				1.0E7		temp_module = xyz dist
y_div	Standard deviation for the climate station transformation equation for the latitude (Y) coordinate	one	real	meters	-1.0E7 to 1.0E7	1.0	precip_module and temp_module = xyz dist
z_add	Mean value for the climate station transformation equation for the elevation (Z) coordinate	one	real	meters	-1.0E7 to 1.0E7	0.0	precip_module and temp_module = xyz dist
z_div	Standard deviation for the climate station transformation equation for the elevation (Z) coordinate (not 0.0)	one	real	meters	-1.0E7 to 1.0E7	1.0	<pre>precip_module and temp_module = xyz dist</pre>
		ar radiation					
basin_solsta	Index of solar radiation station used to compute basin radiation values; used when dimension nsol >0	one	integer	none	0 to nsol	0	nsol > 0
ccov_intcp	Monthly (January to December) intercept in cloud-cover relationship	nhru, nmonths	real	none	0.0 to 5.0	1.83	<pre>solrad_module =</pre>
ccov_slope	Monthly (January to December) coefficient in cloud- cover relationship	nhru, nmonths	real	none	-0.5 to -0.01	-0.13	<pre>solrad_module =</pre>
crad_coef	Coefficient(B) in Thompson (1976) equation; varies by region, contour map of values in reference	nhru, nmonths	real	none	0.1 to 0.7	0.4	<pre>solrad_module =</pre>
crad_exp	Exponent(P) in Thompson (1976) equation	nhru, nmonths	real	none	0.2 to 0.8	0.61	<pre>solrad_module =</pre>
dday_intcp	Monthly (January to December) intercept in degree-day equation for each HRU	nhru, nmonths	real	dday	-60.0 to 10.0	-40.0	<pre>solrad_module = ddsolrad</pre>
dday_slope	Monthly (January to December) slope in degree-day equation for each HRU	nhru, nmonths	real	dday/ temp_units	0.1 to 1.4	0.4	<pre>solrad_module = ddsolrad</pre>
hru_solsta	Index of solar radiation station associated with each HRU	nhru	integer	none	0 to nsol	0	nsol > 0
ppt_rad_adj	Monthly minimum precipitation, if HRU precipitation exceeds this value, radiation is multiplied by radj_sppt or radj_wppt precipitation adjustment factor	nhru, nmonths	real	inches	0.0 to 0.5	0.02	Required
radadj_intcp	Monthly (January to December) intercept in air temperature range adjustment to degree-day equation for each HRU	nhru, nmonths	real	dday	0.0 to 1.0	1.0	<pre>solrad_module = ddsolrad</pre>
radadj_slope	Monthly (January to December) slope in air temperature range adjustment to degree-day equation for each HRU	nhru, nmonths	real	dday/ temp_units	0.0 to 1.0	0.0	<pre>solrad_module = ddsolrad</pre>
radj_sppt	Adjustment factor for computed solar radiation for summer day with greater than ppt_rad_adj inches precipitation for each HRU	nhru	real	decimal fraction	0.0 to 1.0	0.44	required
radj_wppt	Adjustment factor for computed solar radiation for	nhru	real	decimal	0.0 to 1.0	0.5	required

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
	winter day with greater than ppt_rad_adj inches precipitation for each HRU			fraction			
radmax	Monthly (January to December maximum fraction of the potential solar radiation that may reach the ground due to haze, dust, smog, and so forth, for each HRU	nhru, nmonths	real	decimal fraction	0.1 to 1.0	0.8	required
tmax_index	Monthly (January to December) index temperature used to determine precipitation adjustments to solar radiation for each HRU	nhru, nmonths	real	temp_units	-10.0 to 110.0	50.0	<pre>solrad_module = ddsolrad</pre>
	Potential evapor	transpiration dist	ribution				
crop_coef	Monthly (January to December) crop coefficient for each HRU	nhru, nmonths	real	decimal fraction	0.0 to 2.0	1.0	<pre>et_module = potet_pm or potet_pm_sta</pre>
epan_coef	Monthly (January to December) evaporation pan coefficient for each HRU	nhru, nmonths	real	decimal fraction	0.01 to 3.0	1.0	et_module = potet pan
hamon_coef	Monthly (January to December) air temperature coefficient used in Hamon potential ET computations for each HRU	nhru, nmonths	real	none	0.004 to 0.008	0.0055	<pre>et_module = potet_hamon</pre>
hru_humidity_sta	Index of humidity measurement station for each HRU	nhru	integer	none	0 to nhumid	0	<pre>et_module = potet_pm_sta and nhumid > 0</pre>
hru_pansta	Index of pan evaporation station used to compute HRU potential ET	nhru	integer	none	0 to nevap	0	<pre>et_module = potet_pan and nevapl > 0</pre>
hru_windspeed_sta	Index of wind speed measurement station for each HRU	nhru	integer	none	0 to nwind	0	et_module = potet_pm_sta and nwind > 0
hs_krs	Monthly (January to December) adjustment factor used in Hargreaves-Samani potential ET computations for each HRU	nhru, nmonths	real	decimal fraction	0.01 to 0.24	0.0135	et_module = potet_hs
humidity_percent	Monthy humidity for each HRU	nhru, nmonths	real	percentage	0.0 to 100.0	0.0	<pre>et_module = potet_pm or potet_pt and humidity is not specified in a CBH</pre>
jh_coef	Monthly (January to December) air temperature coefficient used in Jensen-Haise potential ET computations for each HRU	nhru, nmonths	real	per degrees Fahrenheit	-0.5 to 1.5	0.014	File et_module = potet_jh
jh_coef_hru	Air temperature coefficient used in Jensen-Haise potential ET computations for each HRU	nhru	real	per degrees Fahrenheit	-99.0 to 150.0	13.0	<pre>et_module = potet_jh</pre>

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
pm_d_coef	Monthly (January to December) Penman-Monteith	nhru,	real	seconds/	0.25 to 0.45	0.34	et_module =
	potential ET D wind speed coefficient for each HRU	nmonths		meter			potet_pm or
pm_n_coef	Monthly (January to December) Penman-Monteith	nhru,	real	degrees	850.0 to 950.0	900.0	<pre>potet_pm_sta et_module =</pre>
F	potential ET N temperature coefficient for each HRU	nmonths		Celsius per		, , , , ,	potet_pm or
	N. 11 (7)			day	0.5 . 1.5	1.0	<pre>potet_pm_sta</pre>
potet_cbh_adj	Monthly (January to December) adjustment factor to potential evapotranspiration specified in CBH Files for	nhru,	real	degrees decimal	0.5 to 1.5	1.0	et_module =
	each HRU	nmonths		fraction			climate_hru
pt_alpha	Monthly (January to December) adjustment factor used	nhru,	real	decimal	1.0 to 2.0	1.26	et module =
1 - 1	in Priestly-Taylor potential ET computations for each HRU	nmonths		fraction			potet_pt
	Evapotranspi	ration and sublim	ation				
fall_frost	The solar date (number of days after winter solstice) of the first killing frost of the fall	nhru	integer	solar date	1 to 366	264	<pre>transp_module = transp_frost</pre>
frost_temp	Temperature of killing frost	nhru	real	temp_units	-10.0 to 32.0	28.0	model_mode = FROST
potet_sublim	Fraction of potential ET that is sublimated from snow in the canopy and snowpack for each HRU	nhru	real	decimal fraction	0.1 to 0.75	0.5	required
rad_trncf	Transmission coefficient for short-wave radiation through the winter vegetation canopy	nhru	real	decimal fraction	0.0 to 1.0	0.5	required
soil_type	Soil type of each HRU (1=sand; 2=loam; 3=clay)	nhru	integer	none	1 to 3	2	required
spring_frost	The solar date (number of days after winter solstice) of the last killing frost of the spring	nhru	integer	solar date	1 to 366	111	<pre>transp_module = transp_frost</pre>
transp_beg	Month to begin summing maximum air temperature for each HRU; when sum is greater than or equal to transp_tmax , transpiration begins	nhru	integer	month	1 to 12	1	<pre>transp_module = transp_tindex</pre>
transp_end	Month to stop transpiration computations; transpiration is computed thru end of previous month	nhru	integer	month	1 to 13	13	<pre>transp_module = transp tindex</pre>
transp_tmax	Temperature index to determine the specific date of the start of the transpiration period;' the maximum air temperature for each HRU is summed starting with the first day of month transp_beg ; when the sum exceeds this index, transpiration begins	nhru	real	temp_units	0.0 to 1,000.0	1.0	<pre>transp_module = transp_tindex</pre>
	Ir	terception					
cov_type	Vegetation cover type for each HRU (0=bare soil; 1=grasses; 2=shrubs; 3=trees; 4=coniferous)	nhru	integer	none	0 to 4	3	required
covden_sum	Summer vegetation cover density for the major vegetation type in each HRU	nhru	real	decimal fraction	0.0 to 1.0	0.5	required
covden_win	Winter vegetation cover density for the major vegetation	nhru	real	decimal	0.0 to 1.0	0.5	required

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
	type in each HRU			fraction			
snow_intcp	Snow interception storage capacity for the major vegetation type in each HRU	nhru	real	inches	0.0 to 1.0	0.1	required
srain_intcp	Summer rain interception storage capacity for the major vegetation type in each HRU	nhru	real	inches	0.0 to 1.0	0.1	required
wrain_intcp	Winter rain interception storage capacity for the major vegetation type in each HRU	nhru	real	inches	0.0 to 1.0	0.1	required
		v computaions					
albset_rna	Fraction of rain in a mixed precipitation event above which the snow albedo is not reset; applied during the snowpack accumulation stage	one	real	decimal fraction	0.5 to 1.0	0.8	required
albset_rnm	Fraction of rain in a mixed precipitation event above which the snow albedo is not reset; applied during the snowpack melt stage	one	real	decimal fraction	0.4 to 1.0	0.6	required
albset_sna	Minimum snowfall, in water equivalent, needed to reset snow albedo during the snowpack accumulation stage	one	real	inches	0.01 to 1.0	0.05	required
albset_snm	Minimum snowfall, in water equivalent, needed to reset snow albedo during the snowpack melt stage	one	real	inches	0.1 to 1.0	0.2	required
cecn_coef	Monthly (January to December) convection condensation energy coefficient for each HRU	nhru, nmonths	real	calories per degree Celsius > 0	0.02.0 to 20.0	5.0	required
den_init	Initial density of new-fallen snow	one	real	grams/cubic centimeters	0.01 to 0.5	0.1	required
den_max	Average maximum snowpack density	one	real	grams/cubic centimeters	0.1 to 0.8	0.6	required
emis_noppt	Average emissivity of air on days without precipitation for each HRU	nhru	real	decimal fraction	0.757 to 1.0	0.757	required
freeh2o_cap	Free-water holding capacity of snowpack expressed as a decimal fraction of the frozen water content of the snowpack (<i>pk_ice</i>) for each HRU	nhru	real	decimal fraction	0.01 to 0.2	0.05	required
hru_deplcrv	Index number for the snowpack areal depletion curve associated with each HRU	nhru	integer	none	1 to ndepl	1	required
melt_force	Julian date to force snowpack to spring snowmelt stage; varies with region depending on length of time that permanent snowpack exists for each HRU	nhru	integer	Julian day	1 to 366	140	required
melt_look	Julian date to start looking for spring snowmelt stage; varies with region depending on length of time that permanent snowpack exists for each HRU	nhru	integer	Julian day	1 to 366	90	required
settle_const	Snowpack settlement time constant	one	real	decimal fraction	0.01 to 0.5	0.1	required

Parameter name	Description	Dimension ¹	Туре	Units	Range	Default	Required/condition
snarea_curve	Snow area depletion curve values, 11 values for each curve (0.0 to 1.0 in 0.1 increments)	ndeplval	real	decimal fraction	0.0 to 1.0	1.0	required
snarea_thresh	Maximum threshold snowpack water equivalent below which the snow-covered-area curve is applied	nhru	real	inches	0.0 to 200.0	50.0	required
snowpack_init	Storage of snowpack in each HRU at the beginning of a simulation	nhru	real	inches	0.0 to 5000.0	0.0	required
tstorm_mo	Monthly indicator for prevalent storm type (0=frontal storms; 1=convective storms) for each HRU	nhru, nmonths	integer	none	0 or 1	0	required
	Hortonian surface runoff,	infiltration, and im	pervious st	orage			
carea_max	Maximum possible area contributing to surface runoff expressed as a portion of the HRU area	nhru	real	decimal fraction	0.0 to 1.0	0.6	required
carea_min	Minimum possible area contributing to surface runoff expressed as a portion of the area for each HRU	nhru	real	decimal fraction	0.0 to 1.0	0.2	<pre>srunoff_module = srunoff_carea</pre>
hru_percent_imperv ²	Fraction of each HRU area that is impervious	nhru	real	decimal fraction	0.0 to 0.999	0.0	required
imperv_stor_max	Maximum impervious area retention storage for each HRU	nhru	real	inches	0.0 to 0.5	0.05	required
smidx_coef	Coefficient in non-linear contributing area algorithm for each HRU	nhru	real	decimal fraction	0.0 to 1.0	0.005	<pre>srunoff_module = srunoff_smidx</pre>
smidx_exp	Exponent in non-linear contributing area algorithm for each HRU	nhru	real	1/inch	0.0 to <mark>5.0</mark>	0.3	<pre>srunoff_module = srunoff_smidx</pre>
snowinfil_max	Maximum snow infiltration per day for each HRU	nhru	real	inches/day	0.0 to 20.0	2.0	required
		lepression storage	е				
dprst_area	Aggregate sum of surface-depression storage areas of each HRU (recommend that dprst_frac_hru be used instead of dprst_area)	nhru	real	acres	0.0 to 1.0E9	0.0	dprst_flag = 1 and model_mode = PRMS
dprst_depth_avg	Average depth of storage depressions at maximum storage capacity	nhru	real	inches	0.0 to 500.0	132.0	$\mathbf{dprst_flag} = 1$
dprst_et_coef	Fraction of unsatisfied potential evapotranspiration to apply to surface-depression storage	nhru	real	decimal fraction	0.5 to 1.5	1.0	$\mathbf{dprst_flag} = 1$
dprst_flow_coef	Coefficient in linear flow routing equation for open surface depressions for each HRU	nhru	real	fraction/day	0.00001 to 0.5	0.05	$\mathbf{dprst_flag} = 1$
dprst_frac_hru	Fraction of each HRU area that has surface depressions (If specified the parameter dprst_area is ignored if it also is specified, default of -1.0 means use dprst_area)	nhru	real	decimal fraction	<mark>-1.0</mark> to 0.999	-1.0	dprst_flag = 1 and model_mode = PRMS or GSFLOW
dprst_frac	Fraction of each HRU area that has surface depressions (If specified the parameter dprst_area is ignored if it also is specified)	nhru	real	decimal fraction	<mark>0.0</mark> to 0.999	0.0	<pre>dprst_flag = 1 and model_mode = PRMS5 or GSFLOW5</pre>
dprst_frac_init	Fraction of maximum surface-depression storage that	nhru	real	decimal	0.0 to 1.0	0.5	$dprst_flag = 1$

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
dprst_frac_open	contains water at the start of a simulation Fraction of open surface-depression storage area within an HRU that can generate surface runoff as a function of	nhru	double	fraction decimal fraction	0.0 to 1.0	1.0	dprst_flag = 1
dprst_seep_rate_clos	storage volume Coefficient used in linear seepage flow equation for closed surface depressions for each HRU	nhru	real	fraction/day	0.0 to 0.2	0.02	$\mathbf{dprst_flag} = 1$
dprst_seep_rate_open	Coefficient used in linear seepage flow equation for open surface depressions for each HRU	nhru	real	fraction/day	0.0 to 0.2	0.02	$\mathbf{dprst_flag} = 1$
op_flow_thres	Fraction of open depression storage above which surface runoff occurs; any water above maximum open storage capacity spills as surface runoff	nhru	real	decimal fraction	0.01 to 1.0	1.0	$\mathbf{dprst_flag} = 1$
sro_to_dprst_imperv	Fraction of impervious surface runoff that flows into surface-depression storage; the remainder flows to a stream network for each HRU	nhru	real	decimal fraction	0.0 to 1.0	0.2	$\mathbf{dprst_flag} = 1$
sro_to_dprst	Fraction of pervious surface runoff that flows into surface-depression storage; the remainder flows to a stream network for each HRU	nhru	real	decimal fraction	0.0 to 1.0	0.2	<pre>dprst_flag = 1 and model_mode = PRMS or GSFLOW</pre>
sro_to_dprst_perv	Fraction of pervious surface runoff that flows into surface-depression storage; the remainder flows to a stream network for each HRU	nhru	real	decimal fraction	0.0 to 1.0	0.2	<pre>dprst_flag = 1 and model_mode = PRMS5 or GSFLOW5</pre>
va_clos_exp	Coefficient in the exponential equation relating maximum surface area to the fraction that closed depressions are full to compute current surface area for each HRU; 0.001 is an approximate rectangle; 1.0 is a triangle	nhru	real	none	0.0001 to 10.0	0.001	dprst_flag = 1
va_open_exp	Coefficient in the exponential equation relating maximum surface area to the fraction that open depressions are full to compute current surface area for each HRU; 0.001 is an approximate rectangle; 1.0 is a triangle	nhru	real	none	0.0001 to 10.0	0.001	dprst_flag = 1
	Soil zone storage, interflow, g	ravity drainage, d	unnian surf	ace runoff			
fastcoef_lin	Linear coefficient in equation to route preferential-flow storage downslope for each HRU	nhru	real	fraction/day	0.0 to 1.0	0.1	required ⁸
fastcoef_sq	Non-linear coefficient in equation to route preferential- flow storage downslope for each HRU	nhru	real	none	0.0 to 1.0	0.8	required ⁸
pref_flow_den	Fraction of the soil zone in which preferential flow occurs for each HRU	nhru	real	decimal fraction	0.0 to 0.5	0.0	required ⁸
sat_threshold	Water holding capacity of the gravity and preferential- flow reservoirs; difference between field capacity and total soil saturation for each HRU	nhru	real	inches	0.00001 to 999.0	999.0	required ⁸

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
slowcoef_lin	Linear coefficient in equation to route gravity-reservoir storage downslope for each HRU	nhru	real	fraction/day	0.0 to 1.0	0.015	required ⁸
slowcoef_sq	Non-linear coefficient in equation to route gravity- reservoir storage downslope for each HRU	nhru	real	none	0.0 to 1.0	0.1	required ⁸
soil_moist_init	Initial value of available water in capillary reservoir for each HRU	nhru	real	inches	0.0 to 10.0	3.0	model_mode = PRMS or GSFLOW
soil_moist_init_frac	Initial fraction of available water in the capillary reservoir (fraction of soil_moist_max for each HRU	nhru	real	decimal fraction	0.0 to 1.0	0.0	<pre>model_mode = PRMS5 or GSFLOW5</pre>
soil_moist_max	Maximum available water holding capacity of capillary reservoir from land surface to rooting depth of the major vegetation type of each HRU	nhru	real	inches	0.00001 to 20.0	2.0	required
soil_rechr_init	Initial storage for soil recharge zone (upper part of capillary reservoir where losses occur as both evaporation and transpiration) for each HRU; must be less than or equal to soil_moist_init	nhru	real	inches	0.0 to 10.0	1.0	model_mode = PRMS or GSFLOW
soil_rechr_init_frac	Initial fraction of available water in the capillary reservoir where losses occur as both evaporation and transpiration (upper zone of capillary reservoir) for each HRU	nhru	real	decimal fraction	0.0 to 1.0	0.0	<pre>model_mode = PRMS5 or GSFLOW5</pre>
soil_rechr_max	Maximum storage for soil recharge zone (upper portion of capillary reservoir where losses occur as both evaporation and transpiration) of must be less than or equal to soil_moist_max	nhru	real	inches	0.00001 to 5.0	1.5	model_mode = PRMS or GSFLOW
soil_rechr_max_frac	Fraction of the capillary reservoir water-holding capacity (soil_moist_max) where losses occur as both evaporation and transpiration (upper zone of capillary reservoir) for each HRU	nhru	real	decimal fraction	0.00001 to 1.0	1.0	required
soil2gw_max	Maximum amount of the capillary reservoir excess that is routed directly to the GWR for each HRU	nhru	real	inches	0.0 to 5.0	0.0	required
ssr2gw_exp	Non-linear coefficient in equation used to route water from the gravity reservoirs to the GWR for each HRU	nssr	real	none	0.0 to 3.0	1.0	required
ssr2gw_rate	Linear coefficient in equation used to route water from the gravity reservoir to the GWR for each HRU	nssr	real	fraction/day	0.0001 to 1.0	0.1	required
ssstor_init	Initial storage of the gravity and preferential-flow reservoirs for each HRU	nssr	real	inches	0.0 to 5.0	0.0	model_mode = PRMS or GSFLOW
ssstor_init_frac	Initial fraction of available water in the gravity plus preferential-flow reservoirs (fraction of sat_threshold) for each HRU	nssr	real	decimal fraction	0.0 to 1.0	0.0	required
_		ındwater flow					
gwflow_coef	Linear coefficient in the equation to compute	ngw	real	fraction/day	0.0 to 0.5	0.015	required

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
	groundwater discharge for each GWR						
gwsink_coef	Linear coefficient in the equation to compute outflow to the groundwater sink for each GWR	ngw	real	fraction/day	0.0 to 1.0	0.0	required
gwstor_init	Storage in each GWR at the beginning of a simulation	ngw	real	inches	0.0 to <mark>50.0</mark>	2.0	required
gwstor_min	Minimum storage in each GWR to ensure storage is greater than specified value to account for inflow from deep aquifers or injection wells with the water source outside the basin	ngw	real	inches	0.0 to 1.0	0.0	required
	\$	Streamflow					
hru_segment	Segment index to which an HRU contributes lateral flows (surface runoff, interflow, and groundwater discharge)	nhru	integer	none	0 to nsegment	0	<pre>strmflow_module = muskingum, strmflow_in_out , or muskingum_lake</pre>
K_coef	Travel time of flood wave from one segment to the next downstream segment, called the Muskingum storage coefficient; enter 1.0 for reservoirs, diversions, and segment(s) flowing out of the basin	nsegment	real	hours	0.01 to 24.0	1.0	strmflow_module = muskingum
obsin_segment	Index of measured streamflow station that replaces inflow to a segment	nsegment	integer	none	0 to nobs	0	<pre>strmflow_module = muskingum, strmflow_in_out , or muskingum_lake</pre>
obsout_segment	Index of measured streamflow station that replaces outflow from a segment	nsegment	integer	none	0 to nobs	0	<pre>strmflow_module = muskingum, strmflow_in_out , or muskingum_lake</pre>
segment_flow_init	Initial flow in each stream segment	nsegment	real	cfs	0 to 1.0E7	0.0	<pre>strmflow_module = muskingum, strmflow_in_out , or muskingum_lake</pre>
segment_type	Segment type (0=segment; 1= headwater; 2=lake; 3=replace inflow; 4=inbound to NHM; 5=outbound from NHM; 6=inbound to region; 7=outbound from region; 8=drains to ocean; 9=sink; 10=inbound from Great Lakes; 11=outbound to Great Lakes, add 100 to flag that the value is updated)	nsegment	integer	none	0 to 111	0	<pre>strmflow_module = muskingum, strmflow_in_out , or muskingum_lake</pre>

Parameter name	Description	Dimension ¹	Туре	Units	Range	Default	Required/condition
tosegment	Index of downstream segment to which the segment streamflow flows; for segments that do not flow to another segment enter 0	nsegment	integer	none	-11 to 1000000	0	<pre>strmflow_module = muskingum, strmflow_in_out , or muskingum_lake</pre>
tosegment_nhm	National Hydrologic Model downstream segment ID	nsegment	integer	none	0 to 9999999	0	optional
x_coef	The amount of attenuation of the flow wave, called the Muskingum routing weighting factor; enter 0.0 for reservoirs, diversions, and segment(s) flowing out of the basin	nsegment	real	decimal fraction	0.0 to 0.5	0.2	strmflow_module = muskingum
	La	ake routing					
elev_outflow	Elevation of the main outflow point for each lake using broad-crested weir routing	nlake	real	feet	-300.0 to 10,000.0	0.0	strmflow_module = muskingum_lake
elevlake_init	Initial lake surface elevation for each lake using broad- crested weir routing or gate opening routing	nlake	real	feet	-300.0 to 10,000.0	1.0	strmflow_module = muskingum_lake
gw_seep_coef	Linear coefficient in equation to compute lakebed seepage to the GWR and groundwater discharge to each lake using broad-crested weir routing or gate opening routing	<mark>ngw</mark>	real	fraction/day	0.001 to 0.05	0.015	<pre>strmflow_module = muskingum_lake</pre>
lake_coef	Coefficient in equation to route storage to streamflow for each lake using linear routing	nlake	real	fraction/day	0.0001 to 1.0	0.1	<pre>strmflow_module = muskingum lake</pre>
lake_din1	Initial inflow to each lake using Puls or linear storage routing	nlake	real	cfs	0.0 to 1.0E7	0.1	<pre>strmflow_module = muskingum lake</pre>
lake_evap_adj	Monthly (January to December) adjustment factor for potential ET for each lake	nhru	real	decimal fraction	0.5 to 1.0	1.0	strmflow_modu muskingum lake
lake_hru	Index of HRU for each lake	nlake	integer	none	0 to nhru	0	<pre>strmflow_module = strmflow lake</pre>
lake_hru_id	Identification number of the lake associated with an HRU; more than one HRU can be associated with each lake	nhru	integer	none	0 to nlake	0	strmflow_module = muskingum_lake
lake_init	Initial storage in each lake using Puls or linear storage routing	nlake	real	cfs-days	0.0 to 1.0E7	0.0	<pre>strmflow_module = muskingum lake</pre>
lake_out2	Switch to specify a second outflow point from each lake using gate opening routing (0=no; 1=yes)	nlake	integer	none	0 or 1	0	strmflow_module = muskingum_lake
lake_out2_a	Coefficient A in outflow equation for each lake with a second outlet using gate opening routing	nlake	real	cfs/feet	0.0 to 10,000.0	1.0	strmflow_module = muskingum_lake
lake_out2_b	Coefficient B in outflow equation for each lake with a second outlet using gate opening routing	nlake	real	cfs	0.0 to 10,000.0	100.0	strmflow_module = muskingum lake
lake_qro	Initial daily mean outflow from each lake	nlake	real	cfs	0.0 to	0.1	strmflow_module =

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
lake_seep_elev	Elevation over which lakebed seepage to the GWR occurs for lake HRUs using broad-crested weir routing or gate opening routing	nlake	real	feet	1.0E7 -300.0 to 10,000.0	1.0	<pre>muskingum_lake strmflow_module = muskingum_lake</pre>
lake_segment_id	Index of lake associeated with a segment	nsegment	integer	none	0 to nlake	0	<pre>strmflow_module = muskingum_lake</pre>
lake_type	Type of lake routing method (1=Puls routing; 2=linear routing; 3=flow through; 4=broad crested weir; 5=gate opening; and 6=measured flow)	nlake	integer	none	1 to 6	1	<pre>and cascade_flag = 1 strmflow_module = muskingum_lake</pre>
lake_vol_init	Initial lake volume for each lake using broad-crested weir or gate opening routing	nlake	real	acre-feet	0.0 to 1.0E7	0.0	strmflow_module = muskingum lake
nsos	Number of storage/outflow values in table for each lake using Puls routing	mxnsos, nlake	integer	none	0 to	0	strmflow_module = muskingum lake
02	Outflow values in outflow/storage tables for each lake using Puls routing	mxnsos, nlake	real	cfs	0.0 to 1.0E7	0.0	strmflow_module = muskingum lake
obsout_lake	Index of streamflow measurement station that specifies outflow from each lake using measured flow replacement	nlake	integer	none	0 to nobs	0	strmflow_module = muskingum_lake
rate_table	Rating table with stage (rows) and gate opening (cols) for rating table 1 for lakes using gate opening routing and nratetbl >0	nstage, ngate	real	cfs	-100.0 to 1,000.0	5.0	strmflow_module = muskingum_lake
rate_table2	Rating table with stage (rows) and gate opening (cols) for rating table 2 for lakes using gate opening routing and nratetbl >1	nstage2, ngate2	real	cfs	-100.0 to 1,000.0	5.0	strmflow_module = muskingum_lake
rate_table3	Rating table with stage (rows) and gate opening (cols) for rating table 3 for lakes using gate opening routing and nratetbl >2	nstage3, ngate3	real	cfs	-100.0 to 1,000.0	5.0	strmflow_module = muskingum_lake
rate_table4	Rating table with stage (rows) and gate opening (cols) for rating table 4 for lakes using gate opening routing and nratetbl >3	nstage4, ngate4	real	cfs	-100.0 to 1,000.0	5.0	strmflow_module = muskingum_lake
ratetbl_lake	Index of lake associated with each rating table for each lake using gate opening routing	nratetbl	integer	none	0 to nlake	0	strmflow_module = muskingum lake
s2	Storage values in outflow/storage table for each lake using Puls routing	mxnsos, nlake	real	cfs	0.0 to 1.0E7	0.0	strmflow_module = muskingum lake
tbl_gate	Gate openings for each column for rating table 1 for lakes using gate opening routing and nratetbl >0	ngate	real	inches	0.0 to 20.0	0.0	strmflow_module = muskingum lake
tbl_gate2	Gate openings for each column for rating table 2 for lakes using gate opening routing and nratetbl >1	ngate2	real	inches	0.0 to 20.0	0.0	strmflow_module = muskingum lake
tbl_gate3	Gate openings for each column for rating table 3 for	ngate3	real	inches	0.0 to 20.0	0.0	strmflow_module =

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
	lakes using gate opening routing and nratetbl> 2						muskingum_lake
tbl_gate4	Gate openings for each column for rating table 4 for lakes using gate opening routing and nratetbl >3	ngate4	real	inches	0.0 to 20.0	0.0	strmflow_module = muskingum_lake
tbl_stage	Stage values for each row for rating table 1 for lakes using gate opening routing and nratetbl> 0	nstage	real	feet	-100.0 to 1,000.0	5.0	<pre>strmflow_module = muskingum lake</pre>
tbl_stage2	Stage values for each row for rating table 2 for lakes using gate opening routing and nratetbl >1	nstage2	real	feet	-100.0 to 1,000.0	5.0	strmflow_module = muskingum lake
tbl_stage3	Stage values for each row for rating table 3 for lakes using gate opening routing and nratetbl> 2	nstage3	real	feet	-100.0 to 1,000.0	5.0	<pre>strmflow_module = muskingum lake</pre>
tbl_stage4	Stage values for each row for rating table 4 for lakes using gate opening routing and nratetbl >3	nstage4	real	feet	-100.0 to 1,000.0	5.0	strmflow_module = muskingum lake
weir_coef	Coefficient for lakes using broad-crested weir routing	nlake	real	none	2.0 to 3.0	2.7	strmflow_module = muskingum lake
weir_len	Weir length for lakes using broad-crested weir routing	nlake	real	feet	1.0 to 1,000.0	5.0	<pre>strmflow_module = muskingum_lake</pre>
print_freq	Flag to select the output frequency; for combinations, add index numbers, e.g., daily plus yearly = 10; yearly plus total = 3 (0=none; 1=run totals; 2=yearly;	tput options one	integer	none	0 to 15	3	required
print_type	4=monthly; 8=daily; or additive combinations) Flag to select the type of results written to the output file (0=measured and simulated flow only; 1=water balance table; 2=detailed output)	one	integer	none	0 to 2	1	required
		sin parameters					
hru_subbasin	Index of subbasin assigned to each HRU	nhru	integer	none	0 to user defined	0	$subbasin_flag = 1$
subbasin_down	Index number for the downstream subbasin whose inflow is outflow from this subbasin	nsub	integer	none	0 to nsub	0	$subbasin_flag = 1$
	Mapped I	esults parameter	S				
gvr_cell_id ⁹	Index of the grid cell associated with each gravity reservoir default of -1 means HRUs and grid cells are	nhrucell	integer	none	-1 to 999999999	<mark>-1</mark>	mapOutON_OFF = 1
gvr_cell_pct ⁹	equivalent) Proportion of the grid cell area associated with each gravity reservoir	nhrucell	real	decimal fraction	0.0 to 1.0	1.0	mapOutON_OFF = 1
gvr_hru_id ⁹	Index of the HRU associated with each gravity reservoir	nhrucell	integer	none	0 to nhrucell	1	$\mathbf{mapOutON_OFF} = 1$
mapvars_freq	Flag to specify the output frequency (0=none; 1=monthly; 2=yearly; 3=total; 4=monthly and yearly; 5=monthly, yearly, and total; 6=weekly; 7=daily)	one	integer	none	0 to 7	0	mapOutON_OFF = 1

Parameter name	Description	Dimension ¹	Туре	Units	Range	Default	Required/condition
mapvars_units	Flag to specify the output units of mapped results (0=units of the variable; 1=inches to feet; 2=inches to	one	integer	none	0 to 3	0	mapOutON_OFF = 1
ncol prms_warmup	centimeters; 3=inches to meters; as states or fluxes) Number of columns for each row of the mapped results Number of years to simulate before writing mapped results	one one	integer integer	none years	1 to 50000 0 to user defined	1 1	mapOutON_OFF = 1 mapOutON_OFF = 1 or nhruOutON_OFF =-1
	Summary resu	ılts CSV file parar	meters				
poi_gage_id	USGS stream gage for each POI gage	npoigages	string	none	user defined	0	npoigages > 0 and $\mathbf{csvON_OFF} = 1$
poi_gage_segment	Segment index for each POI gage	npoigages	integer	none	0 to nsegment	0	<pre>npoigages > 0 and csvON_OFF = 1</pre>
poi_type	Type code for each POI gage	npoigages	integer	none	1	1	optional
		cascading-flow sir	mulation				
cascade_flg	Flag to indicate cascade type (0=allow many to many; 1=force one to one)	one	integer	none	0 or 1	0	cascade_flag = 1 and ncascade > 0 and/or cascadegw_flag = 1
cascade_tol	Cascade area below which a cascade link is ignored	one	real	acres	0.0 to 0.75% of hru_area	5.0	ncascdgw > 0 cascade_flag = 1 and ncascade > 0 and/or cascadegw_flag = 1 ncascdgw > 0
circle_switch	Switch to check for circles (0=no check; 1=check)	one	integer	none	0 or 1	1	cascade_flag = 1 and ncascade > 0 and/or cascadegw_flag = 1 ncascdgw > 0
gw_down_id ³	Index number of the downslope GWR to which the upslope GWR contributes flow	ncascdgw	integer	none	0 to ngw	0	cascadegw_flag = 1 and ncascdgw > 0
gw_pct_up	Fraction of GWR area used to compute flow contributed to a downslope GWR or stream segment for cascade area	ncascdgw	real	decimal fraction	0.0 to 1.0	1.0	cascadegw_flag = 1 and ncascdgw > 0
gw_strmseg_down_id	Index number of the stream segment that cascade area contributes flow	ncascdgw	integer	none	0 to nsegment	0	cascadegw_flag = 1 and ncascdgw > 0
gw_up_id	Index of GWR containing cascade area	ncascdgw	integer	none	1 to ngw	0	$\mathbf{cascadegw_flag} = 1$ and $\mathbf{ncascdgw} > 0$
hru_down_id ⁴	Index number of the downslope HRU to which the upslope HRU contributes flow	ncascade	integer	none	0 to nhru	0	cascade_flag = 1 and ncascade > 0
hru_pct_up	Fraction of HRU area used to compute flow contributed to a downslope HRU or stream segment for cascade area	ncascade	real	decimal fraction	0.0 to 1.0	1.0	$\mathbf{cascade_flag} = 1 \text{and} \\ \mathbf{ncascade} > 0$

Parameter name	Description	Dimension ¹	Type	Units	Range	Default	Required/condition
hru_strmseg_down_id	Index number of the stream segment that cascade area contributes flow	ncascade	integer	none	0 to nsegment	0	$\mathbf{cascade_flag} = 1 \text{and} \\ \mathbf{ncascade} > 0$
hru_up_id	Index of HRU containing cascade area	ncascade	integer	none	0 to nhru	0	$\mathbf{cascade_flag} = 1 \text{and} \\ \mathbf{ncascade} > 0$

¹Dimensions defined in table 1-1.

³ If the value of **gw_strmseg_down_id**>0 for cascade link, this value is ignored.

⁴If the value of **hru_strmseg_down_id**>0 for cascade link, this value is ignored.

⁵Parameter can be modified if the code determines an HRU is a swale, based on values of the cascade parameters.

⁹Parameter name is based on parameter of same name specified for the Groundwater and Surface-Water Flow (GSFLOW) model (Markstrom and others, 2008). Only required if the HRU map is different than the target map, that is, dimension **nhru** not equal to **ngwcell**.

Table 1-4. Time-series input variables that may be included in the Data File for the Precipitation-Runoff Modeling System, version 5 (PRMS-V). [cfs, cubic feet per second; cms, cubic meters per second; **runoff_units**, 0=cfs; 1=cms; **precip_units**, 0=inches; 1=millimeters; **temp_units**, 0=degrees Fahrenheit; 1=degrees Celsius; >=, greater than or equal to]

Variable	Definition	Units	Valid range	Dimension ¹
gate_ht	Height of the gate opening at each dam with a gate	inches	>=0.0	nratetbl
humidity	Relative humidity at each measurement station	percentage	0.0 to 1.0	nhumid
lake_elev	Elevation of each simulated lake surface	feet	unlimited	nlakeelev
pan_evap	Pan evaporation at each measurement station	inches	>=0.0	nevap
precip	Precipitation at each measurement station	precip_units	>=0.0	nrain
rain_day	Flag to set the form of any precipitation to rain (0=determine form; 1=rain)	none	0 or 1	one
runoff	Streamflow at each measurement station	runoff_units	>=0.0	nobs
snowdepth	Snow depth at each measurement station	inches	>=0.0	nsnow
solrad	Solar radiation at each measurement station	Langleys	>=0.0	nsol
tmax	Maximum air temperature at each measurement station	temp_units	-99.0 to 150.0	ntemp
tmin	Minimum air temperature at each measurement station	temp_units	-99.0 to 150.0	ntemp
wind_speed	Wind speed at each measurement station	miles per hour	0.0 to 500.0	nwind

¹Dimensions defined in table 1-1.

Table 1-5. Input and output variables for the Precipitation-Runoff Modeling System, version 5 (PRMS-V).

[HRU, hydrologic response unit; GWR, groundwater reservoir; CBH, climate-by-HRU; ET, evapotranspiration; cfs: cubic feet per second; cms: cubic meters per second; >, greater than; runoff_units, 0=cfs; 1=cms; precip_units, 0=inches; 1=millimeters; temp_units, 0=degrees Fahrenheit; 1=degrees Celsius; control parameters temp_module, precip_module, et_module, strmflow_module, model_mode, dprst_flag, subbasin_flag, cascade_flag, and cascadegw_flag defined in table 1-2; green highlight indicates new for PRMS-V water_use_flag = 1 if segment_transferON_OFF=1 or gwr_transferON_OFF=1 or external_transferON_OFF=1 or dprst_transferON_OFF=1 or lake_transferON_OFF=1 or nconsumed>0 or nwateruse>0; strikethrough indicates items removed]

Variable name	Description	Dimension ¹	Units	Data type	Availabilty/condition
	Climate distribut	ion			
basin_lakeprecip	Basin area-weighted average precipitation on lake HRUs	one	inches	double	$\mathbf{nlake} > 0$
basin_lapse_max	Basin area-weighted average maximum air temperature lapse rate per 1,000 feet	one	temp_units/ feet	real	<pre>temp_module = temp_dist2</pre>
basin_lapse_min	Basin area-weighted average minimum air temperature lapse rate per 1,000 feet	one	temp_units/ feet	real	<pre>temp_module = temp_dist2</pre>
basin_max_temp_mo	Monthly basin area-weighted average maximum air temperature	one	temp_units	double	always
basin_max_temp_tot	Total simulation basin area-weighted average maximum air temperature	one	temp_units	double	always
basin_max_temp_yr	Yearly basin area-weighted average maximum air temperature	one	temp_units	double	always
basin_min_temp_mo	Monthly basin area-weighted average minimum air temperature	one	temp_units	double	always
basin_min_temp_tot	Total simulation basin area-weighted average minimum air temperature	one	temp_units	double	always
basin_min_temp_yr	Yearly basin area-weighted average minimum air temperature	one	temp_units	double	always
basin_net_ppt	Basin area-weighted average throughfall	one	inches	double	always
basin_net_ppt_mo	Monthly basin area-weighted average net precipitation	one	inches	double	always
basin_net_ppt_yr	Yearly basin area-weighted average net precipitation	one	inches	double	always
basin_obs_ppt	Basin area-weighted measured average precipitation	one	inches	double	always
basin_ppt	Basin area-weighted average precipitation	one	inches	double	always
basin_ppt_mo	Monthly basin area-weighted average precipitation	one	inches	double	always
basin_ppt_tot	Total simulation basin area-weighted average precipitation	one	inches	double	always
basin_ppt_yr	Yearly basin area-weighted average precipitation	one	inches	double	always
basin_rain	Basin area-weighted average rainfall	one	inches	double	always
basin_snow	Basin area-weighted average snowfall	one	inches	double	always
basin_temp	Basin area-weighted average air temperature	one	temp_units	double	always
basin_tmax	Basin area-weighted maximum air temperature	one	temp_units	double	always
basin_tmin	Basin area-weighted minimum air temperature	one	temp_units	double	always
hru_ppt	Precipitation distributed to each HRU	nhru	inches	real	always

hru_rain	Rain distributed to each HRU	nhru	inches	real	always
hru_snow	Snow distributed to each HRU	nhru	inches	real	always
humidity	Relative humidity at each measurement station	nhumid	percentage	real	nhumid > 0
humidity_hru	Relative humidity for each HRU	nhru	percentage	real	<pre>et_module = potet_pm, or potet_pt</pre>
is_rain_day	Flag to indicate if it is raining anywhere in the basin	one	none	integer	<pre>precip_module = ide_dist or xyz dist</pre>
lake_precip	Total precipitation into each lake HRU	nlake	cfs	double	<pre>strmflow_module = muskingum_lake</pre>
newsnow ²	Flag to indicate if new snow fell on each HRU (0=no; 1=yes)	nhru	none	integer	always
pptmix ²	Flag to indicate if precipitation is a mixture of rain and snow for each HRU (0=no; 1=yes)	nhru	none	integer	always
precip	Precipitation at each measurement station	nrain	precip_units	real	nrain > 0
prmx	Fraction of rain in a mixed precipitation event for each HRU	nhru	decimal fraction	real	always
subinc_precip	Area-weighted average precipitation on associated HRUs to each subbasin	nsub	inches	double	$subbasin_flag = 1$
subinc_rain	Area-weighted average rain from associated HRUs to each subbasin	nsub	inches	double	$subbasin_flag = 1$
subinc_snow	Area-weighted average snow on associated HRUs to each subbasin	nsub	inches	double	$subbasin_flag = 1$
subinc_tavgc	Area-weighted average air temperature for associated HRUs to each subbasin	nsub	degrees Celsius	double	$subbasin_flag = 1$
subinc_tmaxc	Area-weighted average maximum air temperature for associated HRUs to each subbasin	nsub	degrees Celsius	double	$subbasin_flag = 1$
subinc_tminc	Area-weighted average minimum air temperature for associated HRUs to each subbasin	nsub	degrees Celsius	double	$\mathbf{subbasin_flag} = 1$
tavgc	Average air temperature distributed to each HRU	nhru	degrees Celsius	real	always
tavgf	Average air temperature distributed to each HRU	nhru	degrees Fahrenheit	real	always
tmax	Maximum air temperature at each measurement station	ntemp	temp_units	real	ntemp > 0
tmax_rain_sta	Maximum air temperature distributed to the precipitation stations	nrain	degrees Fahrenheit	real	<pre>precip_module = ide_dist</pre>
4	Manimum air tarrangatura distributed to sock HDII	l	dannan Calaina	1	or xyz_dist
tmaxc	Maximum air temperature distributed to each HRU Maximum air temperature distributed to each HRU	nhru nhru	degrees Celsius degrees Fahrenheit	real	always
tmaxf tmin	Minimum air temperature at each measurement station		temp_units	real real	always ntemp > 0
tmin_hru	Minimum air temperature distributed to each HRU	ntemp nhru	temp_units	real	always
tmin_rain_sta	Minimum air temperature distributed to the precipitation	nrain	degrees Fahrenheit	real	<pre>precip_module = ide dist</pre>
mm_ram_sta	measurement stations	मा बाप	degrees Fameinien	icai	or xyz_dist
tminc	Minimum air temperature distributed to each HRU	nhru	degrees Celsius	real	always
tminf	Minimum air temperature distributed to each HRU	nhru	degrees Fahrenheit	real	always

wind_speed	Wind speed at each measurement station	nwind	miles per hour	real	nwind > 0					
wind_speed_hru	Wind speed for each HRU	nhru	miles per hour	real	<pre>et_module = potet_pm</pre>					
Solar radiation distribution										
basin_cloud_cover	Basin area-weighted average cloud cover proportion	one	decimal fraction	double	$solrad_module = ccsolrad$					
basin_horad	Potential shortwave radiation for the basin centroid	one	Langleys	double	always					
basin_orad	Basin area-weighted average shortwave radiation on a horizontal surface	one	Langleys	double	<pre>solrad_module = ccsolrad or ddsolrad</pre>					
basin_potsw	Basin area-weighted average shortwave radiation	one	Langleys	double	always					
basin_radadj	Basin area-weighted average potential radiation adjustment for cloud cover	one	decimal fraction	double	<pre>solrad_module = ccsolrad</pre>					
basin_swrad	Basin area-weighted average shortwave radiation	one	Langleys	double	always					
cloud_cover_hru	Cloud cover proportion of each HRU	nhru	decimal fraction	double	<pre>solrad_module = ccsolrad</pre>					
cloud_radadj	Radiation adjustment for cloud cover of each HRU	nhru	decimal fraction	double	<pre>solrad_module = ccsolrad</pre>					
lwrad_net	Net long-wave radiation for each HRU	nhru	Megajoules/m**2/day	real	<pre>et_module = potet_pm, potet_pm_sta, or potet_pt</pre>					
orad	Measured or computed solar radiation on a horizontal surface	one	Langleys	real	solrad_module = ccsolrad or ddsolrad					
orad_hru	Solar radiation on a horizontal surface for each HRU	one	Langleys	double	<pre>solrad_module = ccsolrad or ddsolrad</pre>					
seginc_swrad	Area-weighted average solar radiation for each segment from HRUs contributing flow to the segment	nsegment	Langleys	double	nsegment > 0					
solrad	Solar radiation at each measurement station	nsol	Langleys	real	nsol > 0					
solrad_tmax ⁵	Basin maximum air temperature for use with solar radiation calculations	one	temp_units	real	always					
solrad_tmin ⁵	Basin minimum air temperature for use with solar radiation calculations	one	temp_units	real	always					
soltab_horad_potsw	Potential solar radiation on a horizontal plane for each Julian Day, for each HRU	ndays, nhru	Langleys	double	always					
soltab_potsw	Potential solar radiation for each Julian Day, for each HRU	ndays, nhru	Langleys	double	always					
subinc_swrad	Area-weighted average shortwave radiation distributed to associated HRUs of each subbasin	nsub	Langleys	double	$subbasin_flag = 1$					
swrad	Shortwave radiation distributed to each HRU	nhru	Langleys	real	always					
	Water Use									
basin_hru_apply	Basin area-weighted average canopy_gain	one	inches	double	$\mathbf{water_use_flag} = 1$					
basin_net_apply	Basin area-weighted average <i>net_apply</i>	one	inches	double	$\mathbf{water_use_flag} = 1$					
canopy_gain	Transfer gain to the canopy reservoir for each HRU for each time	nhru	cfs	real	$\mathbf{water_use_flag} = 1$					

	step				
canopy_gain_tot	Transfer gain to the canopy reservoir for each HRU for the simulation	nconsumed	cfs	real	<pre>water_use_flag = 1 and nconsumed > 0</pre>
consumed_gain	Transfer gain to each water-use consumption destination for each time step	nconsumed	cfs	real	$water_use_flag = 1$ and $nconsumed > 0$
consumed_gain_tot	Transfer gain to each water-use consumption destination for the simulation	nconsumed	cfs	real	$water_use_flag = 1$ and $nconsumed > 0$
dprst_gain	Transfer gain to surface-depression storage for each HRU for each time step	nhru	cfs	real	dprst_transferON_OFF = 1 and dprst_flag = 1
dprst_gain_tot	Transfer gain to surface-depression storage for each HRU for the simulation	nhru	cfs	real	dprst_transferON_OFF = 1 and dprst_flag = 1
dprst_transfer	Transfer flow rate from surface-depression storage for each HRU for each time step	nhru	cfs	real	dprst_transferON_OFF = 1 and dprst_flag = 1
dprst_transfer_tot	Transfer flow rate from surface-depression storage for each HRU for the simulation	nhru	cfs	real	dprst_transferON_OFF = 1 and dprst_flag = 1
external_gain	Transfer gain to each external location for each time step	nexternal	cfs	real	external_transferON_OFF = 1 and nexternal > 1
external _gain_tot	Transfer gain to each external location for the simulation	nexternal	cfs	real	external_transferON_OFF = 1 and nexternal > 1
external_transfer	Transfer flow rate from each external location for each time step	nexternal	cfs	real	external_transferON_OFF = 1 and nexternal > 1
external _transfer_tot	Transfer flow rate from each external location for the simulation	nexternal	cfs	real	external_transferON_OFF = 1 and nexternal > 1
gwr_gain	Transfer gain to the groundwater reservoir of each HRU for each time step	nhru	cfs	real	$water_use_flag = 1$
gwr_gain _tot	Transfer gain to the groundwater reservoir of each HRU for the simulation	nhru	cfs	real	$water_use_flag = 1$
gwr_transfer	Transfer flow rate from the groundwater reservoir of each HRU for each time step	nhru	cfs	real	gwr_transferON_OFF = 1
gwr_transfer_tot	Transfer flow rate from the groundwater reservoir of each HRU for the simulation	nhru	cfs	real	gwr_transferON_OFF = 1
lake_gain	Transfer gain to each lake HRU for each time step	nhru	cfs	real	<pre>water_use_flag = 1 and strmflow_module = muskingum_lake</pre>
lake_gain _tot	Transfer gain to each lake HRU for the simulation	nhru	cfs	real	<pre>water_use_flag = 1 and strmflow_module = muskingum lake</pre>
lake_transfer	Transfer flow rate from each lake HRU for each time step	nhru	cfs	real	lake_transferON_OFF = 1 and strmflow_module =

					muskingum_lake
lake_transfer_tot	Transfer flow rate from each lake HRU for the simulation	nhru	cfs	real	$lake_transferON_OFF = 1$ and
					${\bf strmflow_module} =$
					muskingum_lake
net_apply	canopy_gain minus interception	nhru	inches	real	$water_use_flag = 1$
segment_gain	Transfer gain to each stream segment for each time step	nhru	cfs	real	$water_use_flag = 1$ and
					${\bf strmflow_module} =$
					muskingum,
					strmflow_in_out, or
		_			muskingum_lake
segment_gain _tot	Transfer gain to each stream segment for the simulation	nhru	cfs	real	$water_use_flag = 1$ and
					strmflow_module =
					muskingum,
					strmflow_in_out, or
		1	. C.	1	muskingum_lake
segmen _transfer	Transfer flow rate from each stream segment for each time step	nhru	cfs	real	<pre>segment_transferON_OFF = 1 and strmflow_module =</pre>
					muskingum,
					strmflow in out, or
					muskingum lake
segment_transfer_tot	Transfer flow rate from each stream segment for the simulation	nhru	cfs	real	segment_transferON_OFF = 1
					and strmflow_module =
					muskingum,
					strmflow in out, or
					muskingum_lake
soilzone_gain	Transfer gain to the capillary reservoir within the soilzone for	nhru	cfs	real	$water_use_flag = 1$
	each HRU for each time step				
soilzone_gain _tot	Transfer gain to the capillary reservoir within the soilzone for	nhru	cfs	real	$water_use_flag = 1$
	each HRU for the simulation				
total_canopy_gain	Transfer gains to all canopy reservoirs for each time step	one	cfs	double	$water_use_flag = 1$
total_consumed_gain	Transfer flow rates to all water-use consumption destinations for	one	cfs	double	$water_use_flag = 1$
	each time step				
total_dprst_gain	Transfer gains to all surface-depression storage for each time step	one	cfs	double	$water_use_flag = 1$ and
					$\mathbf{dprst_flag} = 1$
total_dprst_transfer	Transfer flow rates from all surface-depression storage for each	one	cfs	double	$dprst_transferON_OFF = 1$
	time step				and $\mathbf{dprst_flag} = 1$
total_external_gain	Transfer gains to all external locations for each time step	one	cfs	double	$water_use_flag = 1$
total_external_transfer	Transfer flow rates from all external locations for each time step	one	cfs	double	${\bf external_transferON_OFF} = 1$
					and nexternal > 1

			S.		, a
total_gwr_gain	Transfer gains to all groundwater reservoir for each time step	one	cfs	double	$water_use_flag = 1$
total_gwr_transfer	Transfer flow rates from all groundwater reservoirs for each time	one	cfs	double	$water_use_flag = 1$ and
	step				gwr_transferON_OFF = 1
total_lake_gain	Transfer gains to all lake HRUs for each time step	one	cfs	double	$water_use_flag = 1$ and
					strmflow_module =
			c	1 11	muskingum_lake
total_lake_transfer	Transfer flow rates from all lake HRUs for each time step	one	cfs	double	lake_transferON_OFF = 1 and
					<pre>strmflow_module = muskingum lake</pre>
total_segment_gain	Transfer gains to all stream segments for each time step	one	cfs	double	$water_use_flag = 1$ and
ioiai_segmeni_gain	Transfer gams to an stream segments for each time step	one	CIS	double	strmflow_module =
					muskingum,
					strmflow in out, or
					muskingum_lake
total_segment_transfer	Transfer flow rates from all stream segments for each time step	one	cfs	double	$segment_transferON_OFF = 1$
					and strmflow_module =
					muskingum,
					strmflow_in_out, or
					muskingum_lake
total_soilzone_gain	Transfer gains to all capillary reservoirs for each time step	one	cfs	double	$water_use_flag = 1$
total_transfers	Transfer of all water-use transfers for each time step	one	cfs	double	$water_use_flag = 1$
transfesr_rate	Transfer of each water-use transfer for each time step	nwateruse	cfs	double	$water_use_flag = 1$
	Interception				
basin_changeover	Basin area-weighted average water released from a change over	one	inches	double	always
	of canopy cover type				
basin_intcp_stor	Basin area-weighted average interception storage	one	inches	double	always
basin_net_rain	Basin area-weighted average rain throughfall	one	inches	double	always
basin_net_snow	Basin area-weighted average snow throughfall	one	inches	double	always
canopy_covden	Canopy cover density fo each HRU	nhru	decimal fraction	real	always
hru_intcpstor	Interception storage in the canopy for each HRU	nhru	inches	real	always
intcp_changeover	Water released from a change over of canopy cover type for each HRU	nhru	inches	real	always
intcp_form	Form (rain or snow) of interception for each HRU	nhru	none	integer	always
intcp_on	Flag indicating interception storage for each HRU (0=no; 1=yes)	nhru	none	integer	always
intcp_stor	Interception storage in canopy for cover density for each HRU	nhru	inches	real	always
net_ppt	Precipitation (rain and/or snow) that falls through the canopy for each HRU	nhru	inches	real	always
net_rain	Rain that falls through canopy for each HRU	nhru	inches	real	always
_net_snow	Snow that falls through canopy for each HRU	nhru	inches	real	always

	Snow computation	S			
ai	Maximum snowpack for each HRU	nhru	inches	real	always
albedo	Snow surface albedo or the fraction of radiation reflected from the snowpack surface for each HRU	nhru	decimal fraction	real	always
basin_pk_precip	Basin area-weighted average precipitation added to snowpack	one	inches	double	always
basin_pweqv	Basin area-weighted average snowpack water equivalent	one	inches	double	always
basin_snowcov	Basin area-weighted average snow-covered area	one	decimal fraction	double	always
basin_snowmelt	Basin area-weighted average snowmelt	one	inches	double	always
basin_snowmelt_mo	Monthly basin area-weighted average snowmelt	one	inches	double	always
basin_snowmelt_tot	Total simulation basin area-weighted average snowmelt	one	inches	double	always
basin_snowmelt_yr	Yeary basin area-weighted average snowmelt	one	inches	double	always
basin_tcal	Basin area-weighted average net snowpack energy balance	one	Langleys	double	always
frac_swe	Fraction of maximum snow-water equivalent (snarea_thresh) on each HRU	nhru	decimal fraction	real	always
freeh2o	Storage of free liquid water in the snowpack on each HRU	nhru	inches	real	always
iasw	Flag indicating that snow covered area is interpolated between previous location on curve and maximum (1), or is on the defined curve (0)	nhru	none	integer	always
int_alb	Flag to indicate (1: accumulation season curve; 2: use of the melt season curve)	nhru	none	integer	always
iso	Flag to indicate if time is before (1) or after (2) the day to force melt season (melt_force)	nhru	none	integer	always
lso	Counter for tracking the number of days the snowpack is at or above 0 degrees Celsius	nhru	number of iterations	integer	always
lst	Flag indicating whether there was new snow that was insufficient to reset the albedo curve (1) (albset_snm or albset_sna), otherwise (0)	nhru	none	integer	always
mso	Flag to indicate if time is before (1) or after (2) the first potential day for melt season (melt_look)	nhru	none	integer	always
pk_def	Heat deficit, amount of heat necessary to make the snowpack isothermal at 0 degrees Celsius	nhru	Langleys	real	always
pk_den	Density of the snowpack on each HRU	nhru	grams/cubic centimeters	real	always
pk_depth	Depth of snowpack on each HRU	nhru	inches	double	always
pk_ice	Storage of frozen water in the snowpack on each HRU	nhru	inches	real	always
pk_precip	Precipitation added to snowpack for each HRU	nhru	inches	real	always
pk_temp	Temperature of the snowpack on each HRU	nhru	temp_units	real	always
pksv	Snowpack water equivalent when there is new snow and in melt phase; used to interpolate between depletion curve and 100	nhru	inches	real	always

	percent on each HRU				
pkwater_ante	Antecedent snowpack water equivalent on each HRU	nhru	inches	double	always
pkwater_equiv	Snowpack water equivalent on each HRU	nhru	inches	double	always
pptmix_nopack	Flag indicating that a mixed precipitation event has occurred with no snowpack present on an HRU (1), otherwise (0)	nhru	none	integer	always
pss	Previous snowpack water equivalent plus new snow	nhru	inches	real	always
pst	While a snowpack exists, <i>pst</i> tracks the maximum snow water equivalent of that snowpack	nhru	inches	real	always
salb	Days since last new snow to reset albedo for each HRU	nhru	days	real	always
scrv	Snowpack water equivalent plus a portion of new snow on each HRU	nhru	inches	double	always
slst	Days since last new snow for each HRU	nhru	days	real	always
snow	Snow depth at each measurement station	nsnow	inches	real	$\mathbf{nsnow} > 0$
snow_free	Fraction of snow-free surface for each HRU	nhru	decimal fraction	real	always
snowcov_area	Snow-covered area on each HRU prior to melt and sublimation unless snowpack depleted	nhru	decimal fraction	real	always
snowcov_areasv	Snow cover fraction when there is new snow and in melt phase; used to interpolate between depletion curve and 100 percent on each HRU	nhru	decimal fraction	real	always
snowmelt	Snowmelt from snowpack on each HRU	nhru	inches	real	always
snsv	Tracks the cumulative amount of new snow until there is enough to reset the albedo curve (albset_snm or albset_sna)	nhru	inches	real	always
subinc_pkweqv	Area-weighted average snowpack water equivalent from associated HRUs of each subbasin	nsub	inches	double	$subbasin_flag = 1$
subinc_snowcov	Area-weighted average snow-covered area from associated HRUs to each subbasin	nsub	decimal fraction	double	$subbasin_flag = 1$
subinc_snowmelt	Area-weighted average snowmelt from associated HRUs of each subbasin	nsub	inches	double	$subbasin_flag = 1$
tcal	Net snowpack energy balance on each HRU	nhru	Langleys	real	always
	Evapotranspiration	n			
basin_actet	Basin area-weighted average actual ET	one	inches	double	always
basin_actet_mo	Monthly basin area-weighted average actual ET	one	inches	double	always
basin_actet_tot	Total simulation basin area-weighted average actual ET	one	inches	double	always
basin_actet_yr	Yearly basin area-weighted average actual ET	one	inches	double	always
basin_dprst_evap	Basin area-weighted average evaporation from surface depression storage	one	inches	double	dprst_flag = 1
basin_fall_frost	Basin area-weighted average fall frost	one	solar date	real	model_mode = FROST
basin_humidity	Basin area-weighted average average humidity	one	percentage	double	<pre>et_module = potet_pm,</pre>
			-		<pre>potet_pm_sta, or</pre>

					potet_pt
basin_imperv_evap	Basin area-weighted average evaporation from impervious area	one	inches	double	always
basin_lakeevap	Basin area-weighted average lake evaporation	one	inches	double	nlake > 0
basin_intcp_evap	Basin area-weighted evaporation from the canopy	one	inches	double	always
basin_intcp_evap_mo	Monthly basin basin area-weighted average interception evaporation	one	inches	double	always
basin_intcp_evap_tot	Total simulation basin basin area-weighted average interception evaporation	one	inches	double	always
basin_intcp_evap_yr	Yearly basin basin area-weighted average interception evaporation	one	inches	double	always
basin_perv_et	Basin area-weighted average ET from capillary reservoirs	one	inches	double	always
basin_potet	Basin area-weighted average potential ET	one	inches	double	always
basin_potet_mo	Monthly area-weighted average potential ET	one	inches	double	always
basin_potet_tot	Total simulation area-weighted average potential ET	one	inches	double	always
basin_potet_yr	Yearly area-weighted average potential ET	one	inches	double	always
basin_snowevap	Basin area-weighted average evaporation and sublimation from snowpack	one	inches	double	always
basin_spring_frost	Basin area-weighted average spring frost	one	solar date	real	$model_mode = FROST$
basin_swale_et	Basin area-weighted average ET from swale HRUs	one	inches	double	always
basin_transp_on	Flag indicating whether transpiration is occurring anywhere in the basin (0=no; 1=yes)	one	none	integer	always
basin_windspeed	Basin area-weighted average average wind speed	one	decimal fraction	double	<pre>et_module = potet_pm or potet_pm_sta</pre>
dprst_evap_hru	Evaporation from surface-depression storage for each HRU	nhru	inches	real	$dprst_flag = 1$
fall_frost	The solar date (number of days after winter solstice) of the first killing frost of the fall	nhru	solar date	real	$model_mode = \texttt{FROST}$
hru_actet	Actual ET for each HRU	nhru	inches	real	always
hru_et_yr	Yearly area-weighted average actual ET for each HRU	nhru	inches	double	$print_freq = 2$
hru_intcpevap	Evaporation from the canopy for each HRU	nhru	inches	real	always
imperv_evap	Evaporation from impervious area for each HRU	nhru	inches	real	always
intcp_evap	Evaporation from the canopy for each HRU	nhru	inches	real	always
lake_evap	Total evaporation from each lake HRU	nlake	cfs	double	nlake > 0
pan_evap	Pan evaporation at each measurement station	nevap	inches	real	nevap > 0
perv_actet	Actual ET from the capillary reservoir of each HRU	nhru	inches	real	always
potet	Potential ET for each HRU	nhru	inches	real	always
potet_lower	Potential ET in the lower zone of the capillary reservoir for each HRU	nhru	inches	real	always
potet_rechr	Potential ET in the recharge zone of the capillary reservoir for each HRU	nhru	inches	real	always

notet nt

<mark>perv_avail_et</mark> seginc_potet	Unsatisfied ET available to the capillary reservoir of each HRU Area-weighted average potential ET for each segment from HRUs contributing flow to the segment	nhru nsegment	inches inches	real double	<pre>always strmflow_module = muskingum, strmflow_in_out, or muskingum_lake</pre>
snow_evap	Evaporation and sublimation from snowpack on each HRU	nhru	inches	real	always
spring_frost	The solar date (number of days after winter solstice) of the last killing frost of the spring	nhru	solar date	real	model_mode = FROST
subinc_actet	Area-weighted average actual ET from associated HRUs to each subbasin	nsub	inches	double	subbasin_flag = 1
subinc_potet	Area-weighted average potential ET from associated HRUs to each subbasin	nsub	inches	double	$subbasin_flag = 1$
swale_actet	Evaporation from the gravity and preferential-flow reservoirs that exceeds sat_threshold	nhru	inches	real	always
tempc_dewpt	air temperature at dew point for each HRU	nhru	degrees Celsius	real	<pre>et_module = potet_pm, potet_pm_sta, or potet_pt</pre>
transp_on	Flag indicating whether transpiration is occurring (0=no; 1=yes)	nhru	none	integer	always
unused_potet	Unsatisfied potential evapotranspiration	nhru	inches	real	always
vp_actual	Actual vapor pressure for each HRU	nhru	kilopascals	real	<pre>et_module = potet_pm, potet pm sta, or potet_pt</pre>
vp_sat	Saturation vapor pressure for each HRU	nhru	kilopascals	real	<pre>et_module = potet_pm, potet_pm sta, or potet_pt</pre>
vp_slope	Slope of saturation vapor pressure versus air temperature curve for each HRU	nhru	kilopascals/degrees Celsius	real	<pre>et_module = potet_pm, potet_pm_sta, or potet_pt</pre>
	Hortonian surface runoff, infiltration, a	and impervious	storage		
basin_cap_infil_tot	Basin area-weighted average infiltration with cascading flow into capillary reservoirs	one	inches	double	always
cap_upflow_max	Maximum infiltration and any cascading interflow and Dunnian surface runoff that can be added to capillary reservoir storage for each HRU	nhru	inches	real	always
cap_waterin	Infiltration and any cascading interflow and Dunnian surface runoff added to capillary reservoir storage for each HRU	nhru	inches	real	always
cascade_dunnianflow	Cascading Dunnian flow for each HRU	nhru	inches	real	cascade_flag = 1 and ncascade > 0
cascade_interflow	Cascading interflow for each HRU	nhru	inches	real	cascade_flag = 1 and ncascade > 0
basin_contrib_fraction	Basin area-weighted average contributing area of the pervious area of each HRU	one	decimal fraction	double	always
basin_hortonian	Basin area-weighted average Hortonian runoff	one	inches	double	always

basin_hortonian_lakes	Basin area-weighted average Hortonian surface runoff to lakes	one	inches	double	cascade_flag = 1 and ncascade > 0
basin_imperv_stor	Basin area-weighted average storage on impervious area	one	inches	double	always
basin_infil	Basin area-weighted average infiltration to the capillary reservoirs	one	inches	double	always
basin_sroff	Basin area-weighted average surface runoff to the stream network	one	inches	double	always
basin_sroff_cfs	Basin area-weighted average surface runoff to the stream network	one	cfs	double	always
basin_sroff_down	Basin area-weighted average cascading surface runoff	one	inches	double	cascade_flag = 1 and ncascade > 0
basin_sroff_mo	Monthly basin area-weighted average surface runoff	one	inches	double	always
basin_sroff_tot	Total simulation basin area-weighted average surface runoff	one	inches	double	always
basin_sroff_upslope	Basin area-weighted average cascading surface runoff received from upslope HRUs	one	inches	double	cascade_flag = 1 and ncascade > 0
basin_sroff_yr	Yearly basin area-weighted average surface runoff	one	inches	double	always
basin_sroffi	Basin area-weighted average surface runoff from impervious areas	one	inches	double	always
basin_sroffp	Basin area-weighted average surface runoff from pervious areas	one	inches	double	always
contrib_fraction	Contributing area of each HRU pervious area	nhru	decimal fraction	real	always
hortonian_flow	Hortonian surface runoff reaching stream network for each HRU	nhru	inches	real	always
hortonian_lakes	Surface runoff to lakes for each HRU	nhru	inches	double	cascade_flag = 1, ncascade > 0, and nlake > 0
hru_frac_perv	Fraction of HRU that is pervious	nhru	decimal fraction	real	always
hru_hortn_cascflow	Cascading Hortonian surface runoff leaving each HRU	nhru	inches	double	cascade_flag = 1 and ncascade > 0
hru_imperv	Area of HRU that is impervious	nhru	acres	real	always
hru_impervstor	Storage on impervious area for each HRU	nhru	inches	real	always
hru_perv	Area of HRU that is pervious	nhru	acres	real	always
hru_sroffi	Surface runoff from impervious areas for each HRU	nhru	inches	real	always
hru_sroffp	Surface runoff from pervious areas for each HRU	nhru	inches	real	always
imperv_stor	Storage on impervious area for each HRU	nhru	inches	real	always
infil	Infiltration to the capillary reservoir for each HRU	nhru	inches	real	always
seginc_sroff	Area-weighted average surface runoff for each segment from HRUs contributing flow to the segment	nsegment	cfs	double	nsegment > 0
$sroff^3$	Surface runoff to the stream network for each HRU	nhru	inches	real	always
sub_sroff	Area-weighted average Hortonian plus Dunnian surface runoff from associated HRUs to each subbasin and from upstream subbasins	nsub	cfs	double	subbasin_flag = 1
subinc_sroff	Area-weighted average Hortonian plus Dunnian surface runoff from associated HRUs to each subbasin	nsub	cfs	double	subbasin_flag = 1

upslope_hortonian	Hortonian surface runoff received from upslope HRUs	nhru	inches	double	cascade_flag = 1 and ncascade > 0
	Surface depression sto	orage			
basin_dprst_seep	Basin area-weighted average seepage surface-depression storage	one	inches	double	$\mathbf{dprst_flag} = 1$
basin_dprst_sroff	Basin area-weighted average surface runoff from open surface- depression storage	one	inches	double	$\mathbf{dprst_flag} = 1$
basin_dprst_volcl	Basin area-weighted average storage volume in closed surface depressions	one	inches	double	$\mathbf{dprst_flag} = 1$
basin_dprst_volop	Basin area-weighted average storage volume in open surface depressions	one	inches	double	$\mathbf{dprst_flag} = 1$
dprst_area_clos	Surface area of closed surface depressions based on volume for each HRU	nhru	acres	real	$\mathbf{dprst_flag} = 1$
dprst_area_clos_max	Aggregate sum of closed surface-depression storage areas of each HRU	nhru	acres	real	$\mathbf{dprst_flag} = 1$
dprst_area_max	Aggregate sum of surface-depression storage areas of each HRU	nhru	acres	real	$\mathbf{dprst_flag} = 1$
dprst_area_open	Surface area of open surface depressions based on volume for each HRU	nhru	acres	real	$\mathbf{dprst_flag} = 1$
dprst_area_open_max	Aggregate sum of open surface-depression storage areas of each HRU	nhru	acres	real	$\mathbf{dprst_flag} = 1$
dprst_insroff_hru	Surface runoff from pervious and impervious portions into surface depression storage for each HRU	nhru	inches	real	$\mathbf{dprst_flag} = 1$
dprst_seep_hru	Seepage from surface-depression storage to associated GWR for each HRU	nhru	inches	double	$\mathbf{dprst_flag} = 1$
dprst_sroff_hru	Surface runoff from open surface-depression storage for each HRU	nhru	inches	double	$\mathbf{dprst_flag} = 1$
dprst_stor	Surface-depression storage for each HRU	nhru	inches	double	$\mathbf{dprst_flag} = 1$
dprst_vol_clos	Storage volume in closed surface depressions for each HRU	nhru	acre-inches	double	$\mathbf{dprst_flag} = 1$
dprst_vol_clos_frac	Fraction of closed surface-depression storage of the maximum storage for each HRU	nhru	decimal fraction	double	$\mathbf{dprst_flag} = 1$
dprst_vol_frac	Fraction of surface-depression storage of the maximum storage for each HRU	nhru	decimal fraction	double	$\mathbf{dprst_flag} = 1$
dprst_vol_open	Storage volume in open surface depressions for each HRU	nhru	acre-inches	double	$\mathbf{dprst_flag} = 1$
dprst_vol_open_frac	Fraction of open surface-depression storage of the maximum storage for each HRU	nhru	decimal fraction	double	$\mathbf{dprst_flag} = 1$
hru_frac_perv	Fraction of HRU that has surface-depression storage	nhru	decimal fraction	real	$dprst_flag = 1$
	Soil zone storage, interflow, gravity drainag	e, 50unnian s	surface runoff		
basin_cap_infil_tot	Basin area-weighted average infiltration with cascading flow into capillary reservoirs	one	inches	double	always
basin_cap_up_max	Basin area-weighted average maximum cascade flow that flows	one	inches	double	$cascade_flag = 1$ and $ncascade$

	to capillary reservoirs				> 0
basin_capwaterin	Basin area-weighted average infiltration and any cascading interflow and Dunnian flow added to capillary reservoir storage	one	inches	double	always
basin_cpr_stor_frac	Basin area-weighted average fraction of capillary reservoir storage of the maximum storage	one	decimal fraction	double	always
basin_dncascadeflow	Basin area-weighted average cascading interflow and Dunnian surface runoff	one	inches	double	cascade_flag = 1 and ncascade > 0
basin_dndunnianflow	Basin area-weighted average cascading Dunnian flow	one	inches	double	cascade_flag = 1 and ncascade > 0
basin_dninterflow	Basin area-weighted average cascading interflow	one	inches	double	cascade_flag = 1 and ncascade > 0
basin_dunnian	Basin area-weighted average Dunnian surface runoff that flows to the stream network	one	inches	double	always
basin_dunnian_gvr	Basin area-weighted average excess flow to preferential-flow reservoirs from gravity reservoirs	one	inches	double	always
basin_dunnian_pfr	Basin area-weighted average excess infiltration to preferential-flow reservoirs from variable <i>infil</i>	one	inches	double	always
basin_dunnianflow	Basin area-weighted average cascading Dunnian flow	one	inches	double	always
basin_gvr2pfr	Basin area-weighted average excess flow to preferential-flow reservoir storage from gravity reservoirs	one	inches	double	always
basin_gvr_stor_frac	Basin area-weighted average fraction of gravity reservoir storage of the maximum storage	one	decimal fraction	double	always
basin_interflow_max	Basin area-weighted average maximum interflow that flows from gravity reservoirs	one	inches	double	always
basin_lakeinsz	Basin area-weighted average lake inflow from land HRUs	one	inches	double	cascade_flag = 1, ncascade > 0, and nlake > 0
basin_pfr_stor_frac	Basin area-weighted average fraction of preferential-flow reservoir storage of the maximum storage	one	decimal fraction	double	always
basin_pref_flow_infil	Basin area-weighted average infiltration to preferential-flow reservoir storage	one	inches	double	always
basin_pref_stor	Basin area-weighted average storage in preferential-flow reservoirs	one	inches	double	always
basin_prefflow	Basin area-weighted average interflow from preferential-flow reservoirs to the stream network	one	inches	double	always
basin_recharge	Basin area-weighted average recharge to GWRs	one	inches	double	always
basin_slowflow	Basin area-weighted average interflow from gravity reservoirs to the stream network	one	inches	double	always
basin_slstor	Basin area-weighted average storage of gravity reservoirs	one	inches	double	always

basin_sm2gvr	Basin area-weighted average excess flow from capillary reservoirs to gravity reservoir storage	one	inches	double	always
basin_sm2gvr_maxin	Basin area-weighted average maximum excess flow from capillary reservoirs that flows to gravity reservoirs	one	inches	double	always
basin_soil_lower_stor_frac	Basin area-weighted average fraction of soil lower zone storage storage of the maximum storage	one	decimal fraction	double	always
basin_soil_moist	Basin area-weighted average capillary reservoir storage	one	inches	double	always
basin_soil_moist_tot	Basin area-weighted average total soil-zone water storage	one	inches	double	always
basin_soil_rechr	Basin area-weighted average storage for recharge zone; upper portion of capillary reservoir where both evaporation and transpiration occurs	one	inches	double	always
basin_soil_rechr_stor_frac	storage storage of the maximum storage	one	decimal fraction	double	always
basin_soil_to_gw	Basin area-weighted average excess flow to capillary reservoirs that drains to GWRs	one	inches	double	always
basin_ssflow	Basin area-weighted average interflow from gravity and preferential-flow reservoirs to the stream network	one	inches	double	always
basin_ssflow_cfs	Basin area-weighted average interflow from gravity and preferential-flow reservoirs to the stream network	one	cfs	double	always
basin_ssflow_mo	Monthly basin area-weighted average interflow	one	inches	double	always
basin_ssflow_tot	Simulation total basin area-weighted average interflow	one	inches	double	always
basin_ssflow_yr	Yearly basin area-weighted average interflow	one	inches	double	always
basin_ssin	Basin area-weighted average inflow to gravity and preferential- flow reservoir storage	one	inches	double	always
basin_ssstor	Basin area-weighted average gravity and preferential-flow reservoir storage	one	inches	double	always
basin_sz2gw	Basin area-weighted average drainage from gravity reservoirs to GWRs	one	inches	double	always
basin_sz_stor_frac	Basin area-weighted average fraction of soil zone storage storage of the maximum storage	one	decimal fraction	double	always
cap_infil_tot	Infiltration and cascading interflow and Dunnian flow added to capillary reservoir storage for each HRU	nhru	inches	real	always
cap_waterin	Infiltration and any cascading interflow and Dunnian surface runoff added to capillary reservoir storage for each HRU	nhru	inches	real	always
epr_stor_frae	Fraction of capillary reservoir storage of the maximum storage for each HRU	nhru	decimal fraction	real	always
dunnian_flow	Dunnian surface runoff that flows to the stream network for each HRU	nhru	inches	real	always
gvr_stor_frac	Fraction of gravity reservoir storage of the maximum storage for each HRU	nhru	decimal fraction	real	always

hru_sz_cascadeflow	Cascading interflow and Dunnian surface runoff from each HRU	nhru	inches	real	
interflow_max	Maximum interflow for each HRU	nhru	inches	real	always
pfr_stor_frac	Fraction of preferential flow reservoir storage of the maximum storage for each HRU	nhru	decimal fraction	real	always
pref_flow	Interflow from the preferential-flow reservoir that flows to the stream network for each HRU	nhru	inches	real	always
pref_flow_in	Infiltration and flow from gravity reservoir storage to the preferential-flow reservoir	nhru	inches	real	always
pref_flow_infil	Infiltration to the preferential-flow reservoir storage for each HRU	nhru	inches	real	always
pref_flow_max	Maximum storage of the preferential-flow reservoir for each HRU	nhru	inches	real	always
pref_flow_stor	Storage in preferential-flow reservoir for each HRU	nhru	inches	real	always
pref_flow_thrsh	Soil storage threshold defining storage between field capacity and maximum soil saturation minus the any' preferential-flow storage	nhru	inches	real	always
recharge	Recharge to the associated GWR as sum of <i>soil_to_gw</i> and' <i>ssr_to_gw</i> for each HRU	nhru	inches	real	always
seginc_ssflow	Area-weighted average interflow for each segment from HRUs contributing flow to the segment	nsegment	cfs	double	nsegment > 0
slow_flow	Interflow from gravity reservoir that flows to the stream network for each HRU	nhru	inches	real	always
slow_stor	Storage of gravity reservoir for each HRU	nhru	inches	real	always
soil_lower	Storage in the lower zone of the capillary reservoir that is only available for transpiration for each HRU	nhru	inches	real	always
soil_lower_ratio	Water content ration in the lower zone of the capillary reservoir for each HRU	nhru	decimal fraction	real	always
soil_moist	Storage of capillary reservoir for each HRU	nhru	inches	real	always
soil_moist_frac	Fraction soil zone storage of the maximum storage for each HRU	nhru	decimal fraction	real	always
soil_moist_tot	Total soil-zone storage (soil_moist + ssres_stor) for each HRU	nhru	inches	real	always
soil_rechr	Storage for recharge zone (upper portion) of the capillary reservoir that is available for both evaporation and transpiration	nhru	inches	real	always
soil_rechr_ratio	Water content ration in the recharge zone of the capillary reservoir for each HRU	nhru	decimal fraction	real	always
soil_to_gw	Portion of excess flow to the capillary reservoir that drains to the associated GWR for each HRU	nhru	inches	real	always
soil_to_ssr	Portion of excess flow to the capillary reservoir that flows to the gravity reservoir for each HRU	nhru	inches	real	always
soil_zone_max	Maximum storage of all soil zone reservoirs	nhru	inches	real	always
ssr_to_gw	Drainage from the gravity-reservoir to the associated GWR for	nssr	inches	real	always

	each HRU				
ssres_flow	Interflow from gravity and preferential-flow reservoirs to the stream network for each HRU	nssr	inches	real	always
ssres_in	Inflow to the gravity and preferential-flow reservoirs for each HRU	nssr	inches	real	always
ssres_stor	Storage in the gravity and preferential-flow reservoirs for each HRU	nssr	inches	real	always
sub_interflow	Area-weighted average interflow from associated HRUs to each subbasin and from upstream subbasins	nsub	cfs	double	$\mathbf{subbasin_flag} = 1$
subinc_capstor_frac	Area-weighted average fraction of capillary reservoir water content storage for associated HRUs of each subbasin	nsub	decimal fraction	double	$\mathbf{subbasin_flag} = 1$
subinc_interflow	Area-weighted average interflow from associated HRUs to each subbasin	nsub	cfs	double	$\mathbf{subbasin_flag} = 1$
subinc_recharge	Area-weighted average recharge from associated HRUs to each subbasin	nsub	inches	double	$\mathbf{subbasin_flag} = 1$
subinc_szstor_frac	Area-weighted average fraction of soil-zone water content storage for associated HRUs of each subbasin	nsub	decimal fraction	double	$\mathbf{subbasin_flag} = 1$
upslope_dunnianflow	Cascading Dunnian surface runoff that flows to the capillary reservoir of each downslope HRU for each upslope HRU	nhru	inches	double	cascade_flag = 1 and ncascade > 0
upslope_interflow	Cascading interflow runoff that flows to the capillary reservoir of each downslope HRU for each upslope HRU	nhru	inches	double	cascade_flag = 1 and ncascade > 0
	Groundwater flow				
basin_gwflow	Basin area-weighted average groundwater flow to the stream network	one	inches	double	always
basin_gwflow_cfs	Basin area-weighted average groundwater flow to the stream network	one	cfs	double	always
basin_gwflow_mo	Monthly basin area-weighted average groundwater discharge	one	inches	double	always
basin_gwflow_tot	Total simulation basin area-weighted average groundwater discharge	one	inches	double	always
basin_gwflow_yr	Yearly basin area-weighted average groundwater discharge	one	inches	double	always
basin_gwin	Basin area-weighted average inflow to GWRs	one	inches	double	always
basin_gwsink	Basin area-weighted average GWR outflow to the groundwater sink	one	inches	double	always
basin_gwstor	Basin area-weighted average storage in GWRs	one	inches	double	always
basin_gwstor_minarea_wb	Basin area-weighted average storage added to each GWR when storage is less than gwstor_min	one	inches	double	always
gw_upslope	Groundwater flow received from upslope GWRs for each GWR	ngw	acre-inches	double	$\mathbf{cascadegw_flag} = 1 \text{and} \\ \mathbf{ncascdgw} > 0$
gwres_flow	Groundwater discharge from each GWR to the stream network	ngw	inches	real	always

gwres_in	Total inflow to each GWR from associated capillary and gravity reservoirs	ngw	acre-inches	double	always
gwres_sink	Outflow from GWRs to the groundwater sink; water is considered underflow or flow to deep aquifers and does not flow to the stream network	ngw	inches	real	always
gwres_stor	Storage in each GWR	ngw	inches	double	always
gwstor_minarea_wb	Storage added to each GWR when storage is less than gwstor_min	ngw	inches	double	always
hru_gw_cascadeflow	Cascading groundwater flow from each GWR	ngw	inches	double	$\mathbf{cascadegw_flag} = 1 \text{and} \\ \mathbf{ncascdgw} > 0$
seginc_gwflow	Area-weighted average groundwater discharge for each segment from HRUs contributing flow to the segment	nsegment	cfs	double	nsegment > 0
sub_gwflow	Area-weighted average groundwater discharge from associated GWRs to each subbasin and from upstream subbasins	nsub	cfs	double	subbasin_flag = 1
subinc_gwflow	Area-weighted average groundwater discharge from associated GWRs to each subbasin	nsub	cfs	double	subbasin_flag = 1
	Streamflow				
basin_cfs	Streamflow leaving the basin through the stream network	one	cfs	double	always
basin_cfs_mo	Monthly total streamflow to stream network	one	cfs	double	$\mathbf{print_debug} > -2$
basin_cfs_tot	Total simulation basin area-weighted average streamflow	one	cfs	double	$print_debug > -2$
basin_cfs_yr	Yearly total streamflow to stream network	one	cfs	double	$print_debug > -2$
basin_cms	Streamflow leaving the basin through the stream network	one	cms	double	always
basin_runoff_ratio	Basin area-weighted average discharge/precipitation	one	decimal fraction	double	$\mathbf{print_debug} > -2$
basin_runoff_ratio_mo	Monthly area-weighted average discharge/precipitation	one	decimal fraction	double	$print_debug > -2$
basin_segment_storage	Basin area-weighted average storage in the stream network	one	inches	double	<pre>strmflow_module = muskingum, or muskingum lake</pre>
basin_stflow_in	Basin area-weighted average lateral flow entering the stream network	one	inches	double	always
basin_stflow_mo	Monthly basin area-weighted average simulated streamflow	one	inches	double	$print_debug > -2$
basin_stflow_out	Basin area-weighted average streamflow leaving through the stream network	one	inches	double	$\mathbf{print_debug} > -2$
basin_stflow_tot	Total simulation basin area-weighted average simulated streamflow	one	inches	double	<pre>print_debug > -2</pre>
basin_stflow_yr	Yearly basin area-weighted average simulated streamflow	one	inches	double	$\mathbf{print_debug} > -2$
flow_headwater	Total flow out of headwater segments (segment_type =1)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>

flow_in_great_lakes	Total flow out into model domain from Great Lakes (segment_type=10)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>
flow_in_nation	Total flow into model domain from Mexico or Canada (segment_type=4)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>
flow_in_region	Total flow into region (segment_type =6)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>
flow_out	Total flow out of model domain	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>
flow_out_NHM	Total flow out of model domain to Mexico or Canada (segment_type=5)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>
flow_out_region	Total flow out of region (segment_type =7)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>
flow_replacement	Total flow out from replacement flow (segment_type =3)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>
flow_terminus	Total flow to terminus segments (segment_type =9)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow in out</pre>
flow_to_great_lakes	Total flow to Great Lakes (segment_type =11)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>
flow_to_lakes	Total flow to lakes (segment_type =2)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>

flow_to_ocean	Total flow to oceans (segment_type =8)	one	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>
hru_outflow	Total flow leaving each HRU	nhru	cfs	double	always
hru_streamflow_out	Total flow to stream network from each HRU	nhru	cfs	double	always
obs_runoff_mo	Monthly measured streamflow at basin outlet	one	cfs	double	$print_debug > -2$
obs_runoff_tot	Total simulation measured streamflow at basin outlet	one	cfs	double	$print_debug > -2$
obs_runoff_yr	Yearly measured streamflow at basin outlet	one	cfs	double	$print_debug > -2$
obsq_inches	Measured streamflow at specified outlet station	one	inches	double	$print_debug > -2$
obsq_inches_mo	Monthly measured streamflow at specified outlet station	one	inches	double	$print_debug > -2$
obsq_inches_tot	Total simulation basin area-weighted average measured streamflow at specified outlet station	one	inches	double	print_debug > -2
obsq_inches_yr	Yearly measured streamflow at specified outlet station	one	inches	double	$print_debug > -2$
runoff	Streamflow at each measurement station	nobs	runoff_units	real	$\mathbf{nobs} > 0$
seg_gwflow	Area-weighted average groundwater discharge for each segment from HRUs contributing flow to the segment and upstream HRUs	nsegment	inches	double	<pre>strmflow_module = muskingum, or</pre>
seg_inflow	Total flow entering a segment	nsegment	cfs	double	<pre>muskingum_lake, or strmflow_in_out strmflow_module =</pre>
seg_inflow	Total now emering a segment	nsegment	CIS	double	muskingum, or muskingum_lake, or strmflow in out
seg_lateral_inflow	Lateral inflow entering a segment	nsegment	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or</pre>
seg_outflow	Streamflow leaving a segment	nsegment	cfs	double	<pre>strmflow_in_out strmflow_module = muskingum, or muskingum_lake, or</pre>
seg_sroff	Area-weighted average surface runoff for each segment from HRUs contributing flow to the segment and upstream HRUs	nsegment	inches	double	<pre>strmflow_in_out strmflow_module = muskingum, or muskingum_lake, or strmflow in out</pre>
seg_ssflow	Area-weighted average interflow for each segment from HRUs contributing flow to the segment and upstream HRUs	nsegment	inches	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow_in_out</pre>

seg_upstream_inflow	Sum of inflow from upstream segments	nsegment	cfs	double	<pre>strmflow_module = muskingum, or muskingum_lake, or strmflow in out</pre>
segment_delta_flow	Cummulative flow minus flow out for each stream segment	nsegment	cfs	double	strmflow_module = muskingum or muskingum lake
streamflow_cfs	Streamflow at each measurement station	nobs	cfs	double	$\mathbf{nobs} > 0$
streamflow_cms	Streamflow at each measurement station	nobs	cms	double	nobs > 0
strm_seg_in ³	Flow in stream segments as a result of cascading flow in each stream segment	nsegment	cfs	double	cascade_flag = 1 and ncascade > 0
sub_cfs	Total streamflow leaving each subbasin	nsub	cfs	double	$subbasin_flag = 1$
sub_cms	Total streamflow from each subbasin	nsub	cms	double	$subbasin_flag = 1$
sub_inq	Sum of streamflow from upstream subbasins to each subbasin	nsub	cfs	double	$subbasin_flag = 1$
	Lake dynamics	i			
basin_2ndstflow	Streamflow from second output point for lake HRUs using gate opening routing	one	inches	double	strmflow_module = muskingum_lake
basin_lake_seep	Basin area-weighted average lake-bed seepage to GWRs	one	acre-feet	double	strmflow_module = muskingum_lake
basin_lake_stor	Basin volume-weighted average storage for all lakes using broad- crested weir or gate opening routing	one	inches	double	<pre>strmflow_module = muskingum_lake</pre>
din1	Inflow to each lake HRU using Puls or linear storage routing	nlake	cfs	double	<pre>strmflow_module = muskingum_lake</pre>
elevlake	Surface elevation of each lake	nlake	<mark>feet</mark>	real	<pre>strmflow_module = muskingum_lake nratetbl > 0</pre>
gate_ht	Height of the gate opening at each dam with a gate	nratetbl	inches	real	strmflow_module = muskingum_lake nratetbl > 0
gw_seep_lakein	Groundwater discharge to each lake HRU for each GWR	ngw	acre-feet	double	strmflow_module = muskingum lake
lakein_sz	Cascading interflow and Dunnian surface runoff to lake HRUs for each upslope HRU	nhru	inches	double	cascade_flag = 1, ncascade > 0, and nlake > 0
lake_2gw	Total seepage from each lake using broad-crested weir or gate	nlake	cfs	double	${\bf strmflow_module} =$

lake_elev	opening routing Elevation of each simulated lake surface	nlakeelev	feet	real	<pre>muskingum_lake strmflow_module = muskingum lake and</pre>
lake_gwflow	Total groundflow into each lake	nlake	cfs	double	nlakeelev > 0 strmflow_module =
lake_inflow	Total inflow to each lake	nlake	cfs	double	<pre>muskingum_lake strmflow_module = muskingum lake</pre>
lake_interflow	Total interflow into each lake	nlake	cfs	double	strmflow_module = muskingum lake
lake_invol	Inflow to each lake using broad-crested weir or gate opening routing	nlake	acre-feet	double	strmflow_module = muskingum lake
lake_lateral_inflow	Lateral inflow to each lake	nlake	cfs	double	strmflow_module = muskingum lake
lake_outcfs	Streamflow leaving each lake, includes any second outlet flow	nlake	cfs	double	strmflow_module = muskingum lake
lake_outcms	Streamflow leaving each lake, includes any second outlet flow	nlake	cms	double	strmflow_module = muskingum lake
lake_outflow	Evaporation and seepage from each lake	nlake	cfs	double	strmflow_module = muskingum lake
lake_outq2	Streamflow from second outlet for each lake with a second outlet	nlake	cfs	double	strmflow_module = muskingum lake
lake_outvol	Outflow to each lake using broad-crested weir or gate opening routing	nlake	acre-feet	double	strmflow_module = muskingum lake
lake_outvol_ts	Outflow from each lake using broad-crested weir or gate opening routing for the time step	nlake	acre-inches	double	strmflow_module = muskingum lake
lake_seep_in	Total seepage into each lake using broad-crested weir or gate opening routing	nlake	cfs	double	strmflow_module = muskingum lake
lake_seepage	Lake-bed seepage from each lake to the associated GWR	<mark>ngw</mark>	acre-feet	double	strmflow_module = muskingum lake
lake_seepage_gwr	Net lake-bed seepage to associated GWR	ngw	inches	double	strmflow_module = muskingum lake
lake_sroff	Total surface runoff into each lake	nlake	cfs	double	cascade_flag = 1
lake_sto	Storage in each lake using Puls or linear storage routing	nlake	cfs-days	double	strmflow_module = muskingum_lake
lake_stream_in	Total streamflow to each lake	nlake	cfs	double	strmflow_module = muskingum lake
lake_vol	Storage in each lake using broad-crested weir or gate opening routing	nlake	acre-feet	double	<pre>strmflow_module = muskingum_lake</pre>

Water balance

basin_capillary_wb	Basin area-weighted average capillary reservoir storage	one	inches	double	$print_debug = 1$
basin_dprst_wb	Basin area-weighted average surface-depresion storage	one	inches	double	$\mathbf{print_debug} = 1$
basin_gravity_wb	Basin area-weighted average gravity reservoir storage	one	inches	double	$print_debug = 1$
basin_soilzone_wb	Basin area-weighted average storage in soilzone reservoirs	one	inches	double	$print_debug = 1$
basin_storage	Basin area-weighted average storage in all water-storage reservoirs	one	inches	double	always
basin_storvol	Basin area-weighted average storage volume in all water-storage reservoirs	one	acre-inches	double	always
basin_surface_storage	Basin area-weighted average storage in all water storage reservoirs	one	inches	double	$\mathbf{csvON_OFF} = 1$
basin_total_storage	Basin area-weighted average storage in all water storage reservoirs	one	inches	double	$\mathbf{csvON_OFF} = 1$
hru_lateral_flow	Lateral flow to stream network from each HRU	nhru	cfs	double	always
hru_storage	Storage for each HRU	nhru	inches	double	always
last_basin_stor	Basin area-weighted average storage in all water storage reservoirs from previous time step	one	inches	double	$print_debug = 1$
subinc_deltastor	Change in storage for each subbasin	nsub	inches	double	$subbasin_flag = 1$
subinc_stor	Area-weighted average total water content in storage reservoirs associated HRUs of each subbasin	nsub	inches	double	$subbasin_flag = 1$
subinc_wb	Water balance for each subbasin	nsub	inches	double	$subbasin_flag = 1$
watbal_sum	Water balance aggregate	one	inches	double	always

¹Dimension variables defined in table 1-1.

²Set by precipitation distribution module and can be modified by the interception module if all precipitation captured in canopy.

³Initially set by surface runoff module and can be modified by the soilzone module if Dunnian surface runoff occurs.

⁴Reflects availability of variables based on module selections. See variable description for the reason(s) a variable is conditional or always available.

 $^{^{5}}$ Values are set to the last valid computed value; value is < -99.0 or > 150.