



The Precipitation-Runoff Modeling System, Software Release Notes Through version 5.2.1.1, December 01, 2023

By Robert S. Regan, Steven L. Markstrom, Jacob H. LaFontaine, and Parker A. Norton.

Suggested citation of PRMS software release version 5.2.1.1:
Regan, R.S., Markstrom, S.L., LaFontaine, J.H., and Norton, P.A., 2024, The precipitation-runoff modeling system, software release notes through version 5.2.1.1, October 04, 2023, U.S. Geological Survey Software Release, <https://doi.org/10.5066/P97032NH>

Any use of trade, product, or firm names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

DISCLAIMER

Any use of trade, product, or firm names is for descriptive purposes only and does not imply endorsement by the U.S. Government. This software has been approved for release by the U.S. Geological Survey (USGS). Although the software has been subjected to rigorous review, the USGS reserves the right to update the software as needed pursuant to further analysis and review. No warranty, expressed or implied, is made by the USGS or the U.S. Government as to the functionality of the software and related material nor shall the fact of release constitute any such warranty. Furthermore, the software is released on condition that neither the USGS nor the U.S. Government shall be held liable for any damages resulting from its authorized or unauthorized use. Also refer to the USGS Water Resources Software User Rights Notice (<https://water.usgs.gov/software/help/notice/>) for complete use, copyright, and distribution information.

Notices related to this software are as follows:

- This software is a product of the U.S. Geological Survey, which is part of the U.S. Government.
- This software is freely distributed. There is no fee to download and (or) use this software.
- Users do not need a license or permission from the USGS to use this software. Users can download and install as many copies of the software as they need.
- As a work of the United States Government, this USGS product is in the public domain within the United States. You can copy, modify, distribute, and perform the work, even for commercial purposes, all without asking permission. Additionally, USGS waives copyright and related rights in the work worldwide through CC0 1.0 Universal Public Domain Dedication (<https://creativecommons.org/publicdomain/zero/1.0/>).

CONTENTS

| | |
|---|----|
| DISCLAIMER..... | 2 |
| ABSTRACT | 5 |
| INTRODUCTION | 6 |
| SYSTEM REQUIREMENTS | 7 |
| DOCUMENTATION AND ADDITIONAL RESOURCES | 7 |
| Primary Documentation | 7 |
| Additional Documentation | 7 |
| Selected Application Reports | 9 |
| PRMS PROCESSES, MODULES AND UTILITY ROUTINES | 12 |
| FREQUENTLY ASKED QUESTIONS | 19 |
| CONTROLLING SCREEN OUTPUT | 19 |
| FLEXIBLE SPECIFICATION FOR PARAMETERS..... | 19 |
| INITIAL CONDITIONS FILES | 20 |
| MODEL MODES..... | 21 |
| ERROR CODES..... | 22 |
| Version 5.2.1.1 – December 01, 2023 | 23 |
| BUG FIXES | 23 |
| NEW FUNCTIONALITY..... | 24 |
| PARAMETER CHANGES..... | 24 |
| NEW VARIABLES | 24 |
| Version 5.2.1 – February 08, 2022 | 25 |
| Modifications that are more than simply code formatting are described below | 25 |
| BUG FIXES..... | 25 |
| NEW FUNCTIONALITY..... | 26 |
| PARAMETER CHANGES..... | 26 |
| NEW VARIABLES | 27 |
| Version 5.2.0 – January 20, 2021 | 27 |
| Modifications that are more than simply code formatting are described below. | 28 |
| BUG FIXES | 29 |
| NEW FUNCTIONALITY..... | 29 |
| Stop Conditions | 32 |
| NEW DIMENSIONS..... | 33 |
| PARAMETER CHANGES..... | 33 |
| New Parameters read from the Control File | 33 |
| New Parameters: read from Parameter Files | 34 |
| Updated Parameters read from a Parameter File | 35 |
| NEW VARIABLES | 35 |
| Version 5.1.0 – May 01, 2020..... | 36 |
| Modules and utilities..... | 36 |
| BUG FIXES | 36 |
| CHANGES THAT CAN AFFECT SIMULATION RESULTS..... | 37 |

| | | |
|--|----|----|
| NEW FUNCTIONALITY | 38 | |
| PARAMETER CHANGES | 39 | |
| New Control Parameters | 39 | |
| Updated Control Parameters..... | 40 | |
| Updated Parameters..... | 40 | |
| New Parameters | 40 | |
| NEW VARIABLES | 41 | |
| SMALL CHANGES THAT DO NOT AFFECT ANY COMPUTATIONS..... | 41 | |
| Version 5.0.0 – May 30, 2019 - doi:10.5066/P91FBZOB..... | | 42 |
| INITIAL CONDITIONS FILES | 42 | |
| BUG FIXES | 43 | |
| CHANGES THAT CAN AFFECT SIMULATION RESULTS..... | 45 | |
| NEW FUNCTIONALITY..... | 45 | |
| MODULE REMOVED | 48 | |
| PARAMETER CHANGES..... | 48 | |
| Parameters used when model_mode = PRMS5 | 49 | |
| Parameters used when model_mode = PRMS..... | 50 | |
| NEW VARIABLES | 50 | |
| REMOVED VARIABLES | 50 | |
| SMALL CHANGES THAT DO NOT AFFECT ANY COMPUTATIONS..... | 50 | |
| PRMS UTILITIES..... | 50 | |
| Version 4.0.3 – May 05, 2017 | | 51 |
| BUG FIXES – by module:..... | 51 | |
| SMALL CHANGES THAT DO NOT AFFECT ANY COMPUTATIONS..... | 52 | |
| NEW FUNCTIONALITY..... | 53 | |
| NEW VARIABLES | 53 | |
| Version 4.0.2 – July 29, 2016 | | 53 |
| BUG FIXES | 53 | |
| UPDATES THAT MIGHT PRODUCE SLIGHT CHANGES IN ASSOCIATED COMPUTATIONS – | | |
| general:..... | 56 | |
| NEW FUNCTIONALITY..... | 58 | |
| MODULES REMOVED..... | 59 | |
| INPUT SPECIFICATION CHANGES:..... | 59 | |
| OUTPUT FILE REMOVED | 59 | |
| Version 4.0.1 – March 11, 2015..... | | 59 |
| NEW MODULES (code taken mostly from existing modules) | 59 | |
| GENERAL..... | 60 | |
| NEW FUNCTIONALITY ADDED TO MODULES | 61 | |
| NEW PARAMETERS..... | 63 | |
| Parameters specified in the Control File..... | 63 | |
| Parameters specified in the Parameter File(s) | 64 | |

| | |
|---|----|
| NEW COMPUTED VARIABLES (available depending on which computation options are active): | 64 |
| BUG FIXES | 65 |
| CHANGES THAT MIGHT PRODUCE SLIGHT CHANGES IN ASSOCIATED COMPUTATIONS – | |
| general: | 67 |
| CHANGES THAT MIGHT PRODUCE SLIGHT CHANGES IN ASSOCIATED COMPUTATIONS – by | |
| module: | 67 |
| INPUT SPECIFICATION CHANGES – by module: | 69 |
| OUTPUT CHANGES | 72 |
| Version 3.0.5 – April 24, 2012 | 73 |
| General | 73 |
| BUG FIXES | 74 |
| Version 3.0.4 – January 15, 2012 | 75 |
| BUG FIXES | 75 |
| Version 3.0.3 – November 29, 2012 | 76 |
| Version 3.0.2 – September 22, 2012 | 76 |
| BUG FIXES | 76 |
| OUTPUT AND INPUT ISSUES | 77 |
| PARAMETER NAME CHANGES | 77 |
| Version 3.0.1 – February 06, 2012 | 78 |
| Version 3.0.0 – November 15, 2011 | 78 |
| MMS Version MMS-windows – January 26, 2007 | 79 |
| MMS Version 1.0.0 through 1.2.1 (1991 through 2002) | 79 |
| Version 2.1 – January 17, 1996 | 79 |
| Pre-version 2.0 – (1983 – 1996) | 79 |

TABLES

| | |
|--|----|
| Table 1. PRMS Modules and Utility Routines | 13 |
|--|----|

ABSTRACT

The need to assess the effects of variability in climate, biota, geology, and human activities on water availability and flow can be assessed with computer models that simulate the hydrologic cycle at a watershed scale. The Precipitation-Runoff Modeling System (PRMS) is a deterministic, distributed-parameter, physical process-based modeling system developed to evaluate the response of various combinations of climate, water use, and land use on streamflow and general watershed hydrology. The primary objectives of PRMS are: (1) simulate hydrologic processes including evaporation, transpiration, snow accumulation and melt, runoff, infiltration, and interflow as determined by the energy and water budgets of the plant canopy, soil zone, and snowpack on the basis of distributed climate information (maximum and minimum air temperature and precipitation, and depending on climate distribution options

selected, potential evapotranspiration, solar radiation, humidity, and windspeed); (2) simulate hydrologic water budgets at the watershed scale for temporal scales ranging from days to centuries; (3) integrate PRMS with other models used for natural-resource management or with models from other scientific disciplines; and (4) provide a modular design that allows for selection of alternative hydrologic-process algorithms from the standard PRMS module library. This release documents describe updates to the PRMS software from previous release through version 5.2.1.1.

INTRODUCTION

This file describes changes to the Precipitation-Runoff Modeling System (PRMS) with each official release. Modules, file names, and user input are identified by using Courier New font. Input parameters and dimensions are identified by using **bold** font. State and flux variables are identified by using *italic* font. Please also see file **PRMS_tables_5.2.1.1.pdf** included in the 'doc' directory that provides updates to PRMS-IV tables included in Markstrom and others, 2008 and a new table describing variables related to climate-by-HRU (CBH) files. See the Documentation and Additional Resource section for the full list of PRMS documentation reports and selected application reports.

This minor release (PRMS version 5.2.1.1):

1. Fixes computation of solar radiation for days where the sun does not rise (polar night), such as in Northern Alaska. Polar night conditions resulted previously in divide by zero in `ddsolrad`.
2. Fixes computation of the lateral groundwater and subsurface temperatures. They were based on the values from a single stream segment as opposed to all segments in the model domain.
3. Under specific circumstances, certain segment-based variables (i.e., "seg_lat", "seg_humidity", etc.) had been reinitialized to a value of zero during the simulation; they now retain the previous values. This change produces a notable improvement in performance of the simulation of "seg_tave_water" and related variables.
4. Adds parameter **seg_close** to specify the index of closest segment from elevation and latitude for each a segment. If not specified, **seg_close** defaults to the upstream segment.
5. The `strmflow_character` module was added to compute new variables *seg_area*, *seg_width*, and *seg_velocity* when control parameter **stream_temp_flag** is specified equal to 1.
6. Binary CBH Files are not supported, do not use control parameter **cbh_binary flag**.
7. A few minor changes and bug fixes were made and described.

See also the pared 5.2.1.1 release document showing updates to PRMS tables of modules, parameters, and variables ([PRMS tables 5.2.1.1 URL \(usgs.gov\)](#)).

These fixes, other minor updates, and new functionality are described below in the Version 5.2.1.1 – December 01, 2023 section starting on page 22.

SYSTEM REQUIREMENTS

PRMS is written in the Fortran 95 and C programming languages. The code has been used on personal computers and super computers running various versions of the Microsoft Windows and Linux operating systems. A typical small model, e.g., around 200 Hydrologic Response Units (HRUs) can be executed on almost all computers. Large models, e.g., greater than 100,000 HRUs may need at least 8 GB of RAM to run effectively. Windows and Linux executables provided in this release are built to run on 64-bit computers. The graphical-user interface (GUI) tool is provided, though no longer supported. Please refer to the Object User Interface (OUI) report (Markstrom and Koczot, 2008) that provides information related to the GUI. Java is required for the GUI, Amazon Corretto is a free Java software that can be downloaded from: <https://aws.amazon.com/corretto/>.

DOCUMENTATION AND ADDITIONAL RESOURCES

PDF Files identified in bold letters are provided in the “doc” subdirectory. Web page: [Precipitation Runoff Modeling System \(PRMS\) | U.S. Geological Survey \(usgs.gov\)](#). See [Recordings \(usgs.gov\)](#) for recordings of training course lectures.

Primary Documentation

Markstrom, S.L., Regan, R.S., Hay, L.E., Viger, R.J., Webb, R.M.T., Payn, R.A., and LaFontaine, J.H., 2015, PRMS-IV, the precipitation-runoff modeling system, version 4: U.S. Geological Survey Techniques and Methods, book 6, chap. B7, 158 p., <https://dx.doi.org/10.3133/tm6B7>. File [tm6b7_PRMS-IV.pdf](#). File **tm6-b7_prms4.pdf**. Note some tables in this report are out of date. See file **PRMS_tables_5.2.1.1.pdf** included in the ‘doc’ directory for the most recent version of these tables.

Additional Documentation

Hay, L.E., LaFontaine, J.H., Van Beusekom, A.E., Norton, P.A., Farmer, W.H., Regan, R.S., Markstrom, S.L., and Dickinson, J.E., 2023, Parameter estimation at the conterminous United States scale and streamflow routing enhancements for the National Hydrologic Model infrastructure application of the Precipitation-Runoff Modeling System (NHM-PRMS): U.S. Geological Survey Techniques and Methods 6–B10, 50 p., <https://doi.org/10.3133/tm6B10>. File **tm6-10_parameter_estimation.pdf**.

Hay, L.E., and Umemoto, Makiko, 2007, Multiple-objective stepwise calibration using Luca: U.S. Geological Survey Open-File Report 2006–1323, 25 p., <http://pubs.usgs.gov/of/2006/1323/>.

Henson, W.R., Medina, R.L., Mayers, C.J., Niswonger, R.G., and Regan, R.S., 2013, CRT—Cascade routing tool to define and visualize flow paths for grid-based watershed models: U.S. Geological Survey Techniques and Methods, book 6, chap. D2, 28 p., <https://pubs.usgs.gov/tm/tm6d2/>. File tm6d2_CRT.pdf.

Larsen, J.D., Alzraie, A., Niswonger, R.G., 2022, Integrated hydrologic model development and postprocessing for GSFLOW using pyGSFLOW: Journal of Open Source Software, 7(72), 3852. <https://doi.org/10.21105/joss.03852>.

Leavesley, G.H., Markstrom, S.L., Viger, R.J., and Hay, L.E., 2005, USGS Modular Modeling System (MMS)—Precipitation-Runoff Modeling System (PRMS) MMS-PRMS, in Sing, V., and Frevert, D., eds., Watershed Models: Boca Raton, Fla., CRC Press, p. 159–177.

Leavesley, G.H., Restrepo, P.J., Markstrom, S.L., Dixon, M., and Stannard, L.G., 1996, The Modular Modeling System (MMS): User's manual: U.S. Geological Survey Open-File Report 96-151, 142 p. <https://pubs.usgs.gov/of/1996/0151/report.pdf>.

Leavesley, G.H., Lichty, R.W., Troutman, B.M., and Saindon, L.G., 1983, Precipitation-runoff modeling system--User's manual: U.S. Geological Survey Water-Resources Investigations Report 83-4238, 207 p. <https://pubs.usgs.gov/wri/1983/4238/report.pdf>.

Markstrom, S.L., Niswonger, R.G., Regan, R.S., Prudic, D.E., and Barlow, P.M., 2008, GSFLOW—Coupled ground-water and surface-water flow model based on the integration of the Precipitation-Runoff Modeling System (PRMS) and the Modular Ground-Water Flow Model (MODFLOW-2005): U.S. Geological Survey Techniques and Methods, book 6, chap. D1, 240 p., <https://doi.org/10.3133/tm6D1>.

Markstrom, S.L., and Kocot, K.M., 2008, User's manual for the Object User Interface (OUI)—An environmental resource modeling framework: U.S. Geological Survey Open-File Report 2008–1120, 39 p., <http://pubs.usgs.gov/of/2008/1120/>.

Markstrom, S.L., Hay, L.E., and Clark, M.P., 2016, Towards simplification of hydrologic modeling—Identification of dominant processes: Hydrology and Earth System Sciences, v. 20, no. 11, p. 4655–4671, accessed February 9, 2017 at <https://doi.org/10.5194/hess-20-4655-2016>.

Mastin, M.C., and Vaccaro, J.J., 2002, Documentation of Precipitation-Runoff Modeling System modules for the Modular Modeling System modified for the Watershed and River Systems Management Program: U.S. Geological Survey Open-File Report 2002–362, 5 p., accessed September 30, 2019, at <https://doi.org/10.3133/ofr02362>.

Mastin, M.C., 2009, Watershed models for decision support for inflows to Potholes Reservoir, Washington: U.S. Geological Survey Scientific Investigations Report 2009–5081, 54 p., <https://pubs.usgs.gov/sir/2009/5081/pdf/sir20095081.pdf>. File sir20095081_cfgf.pdf.

Regan, R.S., Markstrom, S.L., Hay, L.E., Viger, R.J., Norton, P.A., Driscoll, J.M., LaFontaine, J.H., 2018, Description of the National Hydrologic Model for use with the Precipitation-Runoff

Modeling System (PRMS): U.S. Geological Survey Techniques and Methods, book 6, chap B9, 38 p., <https://doi.org/10.3133/tm6B9>. File **tm6-b9_nhm_prms.pdf**.

Regan, R.S., and LaFontaine, J.H., 2017, Documentation of the dynamic parameter, water-use, stream and lake flow routing, and two summary output modules and updates to surface-depression storage simulation and initial conditions specification options with the Precipitation-Runoff Modeling System (PRMS): U.S. Geological Survey Techniques and Methods, book 6, chap. B8, 60 p., <https://doi.org/10.3133/tm6B8>. File **tm6-b8_enhancements.pdf**.

Regan, R.S., Niswonger, R.G., Markstrom, S.L., and Barlow, P.M., 2015, Documentation of a restart option for the U.S. Geological Survey coupled groundwater and surface-water flow (GSFLOW) model: U.S. Geological Survey Techniques and Methods, book 6, chap. D3, 19 p., <https://dx.doi.org/10.3133/tm6D3/>. File **tm6d3_Restart.pdf**.

Sanders, M.J., Markstrom, S.L., Regan, R.S., and Atkinson, R.D., 2017, Documentation of a daily mean stream temperature module—An enhancement to the Precipitation-Runoff Modeling System: U.S. Geological Survey Techniques and Methods, book 6, chap. D4, 18 p., <https://doi.org/10.3133/tm6D4>. File **tm6d4_stream_temp.pdf**.

Van Beusekom, A.E., and Viger, R.J., 2015, A glacier runoff extension to the Precipitation Runoff Modeling System, *Journal of Geophysical Research: Earth Science*, 21 p., [A glacier runoff extension to the Precipitation Runoff Modeling System - Van Beusekom - 2016 - Journal of Geophysical Research: Earth Surface - Wiley Online Library](#). File **glacier_2016_VanBeusekom.pdf**

Viger, R.J., 2014, Preliminary spatial parameters for PRMS based on the Geospatial Fabric, NLCD2001 and SSURGO: U.S. Geological Survey data release, accessed September 16, 2016, at <https://doi.org/10.5066/F7WM1BF7>.

Viger, R.J., and Leavesley, G.H., 2007, Section 4—The GIS Weasel user’s manual: U.S. Geological Survey Techniques and Methods, book 6, chap. B4, 201 p., accessed September 24, 2017, at <https://doi.org/10.3133/tm6B4>.

Ward-Garrison, C.D., Markstrom, S.L., and Hay, L.E., 2009, Downsizer—A Graphical user interface based application for browsing, acquiring, and formatting time series data for hydrologic modeling: U.S. Geological Survey Open-File Report 2009–1166, 27 p., <https://pubs.usgs.gov/of/2009/1166/>.

Selected Application Reports

Ahearn, E.A., and Bjerklie, D.M., 2010, Connecticut Highlands Technical Report Documentation of the Regional Rainfall-Runoff Model: U.S. Geological Survey Open File Report 2010-1187, 43 p., <https://pubs.usgs.gov/of/2010/1187/>.

Battaglin, W.A., Hay, L.E., and Markstrom, S.L., 2011, Simulating the potential effects of climate change in two Colorado Basins and at two Colorado ski areas: *Earth Interactions*, v. 15, no. 22, p. 1-23., <https://doi.org/10.1175/2011EI373.1>.

Bjerklie, D.M., Starn, J.J., and Tamayo, Claudia, 2010, Estimation of the effects of land use and groundwater withdrawals on streamflow for the Pomperaug River, Connecticut: U.S. Geological Survey Scientific Investigations Report 2010-5114, 81 p., <https://pubs.usgs.gov/sir/2010/5114/>.

Christiansen, D.E., Haj, A.E., and Risley, J.C., 2017, Simulation of daily streamflow for 12 river basins in western Iowa using the Precipitation-Runoff Modeling System: U.S. Geological Survey Scientific Investigations Report 2017-5091, 27 p., <https://doi.org/10.3133/sir20175091>.

Christiansen, D.E., Walker, J.F., and Hunt, R.J., 2014, Basin-scale simulation of current and potential climate changed hydrologic conditions in the Lake Michigan Basin, United States: U.S. Geological Survey Scientific Investigations Report 2014-5175, 74 p., <https://dx.doi.org/10.3133/sir20145175>.

Christiansen, D.E., Markstrom, S.L., and Hay, L.E., 2011, Impacts of climate change on growing season in the United States: *Earth Interactions*, v. 15, no.33, pp. 1-17, <https://doi.org/10.1175/2011EI376.1>.

Hay, L.E., and LaFontaine, J.H., 2020, Application of the National Hydrologic Model Infrastructure with the Precipitation-Runoff Modeling System (NHM-PRMS), 1980-2016, Daymet Version 3 calibration: U.S. Geological Survey data release, accessed June 1, 2020, at <https://doi.org/10.5066/P9PGZE0S>.

Hay, L., Norton, P., Viger, R., Markstrom, S., Steven Regan, R., and Vanderhoof, M., 2018, Modelling surface-water depression storage in a Prairie Pothole Region: *Hydrological Processes*, v. 32, no. 4, p. 462-479, accessed September 28, 2019, at <https://doi.org/10.1002/hyp.11416>.

Hay, L.E., Leavesley, G.H., and Clark, M.P., 2006a, Use of remotely sensed snow-covered area in watershed model calibration for the Sprague River, Oregon, in Joint 8th Federal Interagency Sedimentation Conference and 3rd Federal Interagency Hydrologic Modeling Conference, Reno, Nev., April 2-6, 2006, Proceedings: Subcommittee on Hydrology, 8 p., accessed September 29, 2019, at [\(PDF\) Use of remotely-sensed snow covered area in watershed model calibration for the Sprague River in the Upper Klamath Basin | Lauren Hay - Academia.edu](#).

Hay, L.E., Leavesley, G.H., Clark, M.P., Markstrom, S.L., Viger, R.J., and Umemoto, M., 2006b, Step wise, multiple objective calibration of a hydrologic model for a snowmelt dominated basin: *Journal of the American Water Resources Association*, v. 42, no. 4, p. 877-890, accessed August 29, 2019, at <https://doi.org/10.1111/j.1752-1688.2006.tb04501.x>.

Hunt, R.J., Westenbroek, S.M., Walker, J.F., Selbig, W.R., Regan, R.S., Leaf, A.T., and Saad, D.A., 2016, Simulation of climate change effects on streamflow, groundwater, and stream temperature using GSFLOW and SNTMP in the Black Earth Creek Watershed, Wisconsin: U.S.

Geological Survey Scientific Investigations Report 2016–5091, 117 p., accessed June 27, 2017 at <https://doi.org/10.3133/sir20165091>.

Hunt, R.J., Walker, J.F., Selbig, W.R., Westenbroek, S.M., and Regan, R.S., 2013, Simulation of climate-change effects on streamflow, lake water budgets, and stream temperature using GSFLOW and SNTMP, Trout Lake watershed, Wisconsin: U.S. Geological Survey Scientific Investigations Report 2013–5159, 118 p., accessed June 27, 2017 at <https://pubs.usgs.gov/sir/2013/5159/>.

Koczot, K.M., Risley, J.C., Gronberg, J.M., Donovan, J.M., and McPherson, K.R., 2021, Precipitation-runoff processes in the Merced River Basin, Central California, with prospects for streamflow predictability, water years 1952–2013: U.S. Geological Survey Scientific Investigations Report 2020–5150, 61 p., <https://doi.org/10.3133/sir20205150>.

LaFontaine, J.H., Hay, L.E., Viger, R.J., Markstrom, S.L., Regan, R.S., Elliott, C.M., and Jones, J.W., 2013, Application of the Precipitation-Runoff Modeling System (PRMS) in the Apalachicola-Chattahoochee-Flint River Basin in the southeastern United States: U.S. Geological Survey Scientific Investigations Report 2013-5162, 118 p., <https://pubs.usgs.gov/sir/2013/5162/>

LaFontaine, J.H., Hart, R.M., Hay, L.E., Farmer, W.H., Bock, A.R., Viger, R.J., Markstrom, S.L., Regan, R.S., and Driscoll, J.M., 2019, Simulation of water availability in the Southeastern United States for historical and potential future climate and land-cover conditions: U.S. Geological Survey Scientific Investigations Report 2019–5039, 83 p., accessed September 19, 2019, at <https://doi.org/10.3133/sir20195039>.

LaFontaine, J.H., Hay, L.E., Viger, R.J., Regan, R.S., and Markstrom, S.L., 2015, Effects of climate and land cover on hydrology in the southeastern U.S.—Potential impacts on watershed planning: *Journal of the American Water Resources Association*, v. 51, no. 5, p. 1235–1261, accessed August 23, 2019, at <https://doi.org/10.1111/1752-1688.12304>.

Markstrom, S.L., Hay, L.E., Ward-Garrison, C.D., Risley, J.C., Battaglin, W.A., Bjerklie, D.M., Chase, K.J., Christiansen, D.E. Dudley, R.W., Hunt, R.J., Koczot, K.M., Mastin, M.C., Regan, R.S., Viger, R.J., Vining, K.C., and Walker, J.F., 2012, Integrated watershed-scale response to climate change for selected basins across the United States: U.S. Geological Survey Scientific Investigations Report 2011-5077, 143 p., [USGS Scientific Investigations Report 2011–5077: Integrated Watershed-Scale Response to Climate Change for Selected Basins Across the United States](https://pubs.usgs.gov/ofr/2012/1116/).

Markstrom, S.L., 2012, P2S—Coupled simulation with the Precipitation-Runoff Modeling System (PRMS) and the Stream Temperature Network (SNTemp) Models: U.S. Geological Survey Open-File Report 2012–1116, 19 p., accessed August 23, 2019, at <https://doi.org/10.3133/ofr20121116>.

Markstrom, S.L., Niswonger, R.G., Regan, R.S., Prudic, D.E., and Barlow, P.M., 2008, GSFLOW—Coupled ground-water and surface-water flow model based on the integration of the precipitation-runoff modeling system (PRMS) and the modular ground-water flow model

(MODFLOW–2005): U.S. Geological Survey Techniques and Methods, book 6, chap. D1, 240 p., <https://pubs.usgs.gov/tm/tm6d1/>.

LaFontaine, J.H., Hart, R.M., Hay, L.E., Farmer, W.H., Bock, A.R., Viger, R.J., Markstrom, S.L., Regan, R.S., and Driscoll, J.M., 2019, Simulation of water availability in the Southeastern United States for historical and potential future climate and land-cover conditions: U.S. Geological Survey Scientific Investigations Report 2019–5039, 83 p., <https://doi.org/10.3133/sir20195039>.

Regan, R.S., Juracek, K.E., Hay, L.E., Markstrom, S.L., Viger, R.J., Driscoll, J.M., LaFontaine, J.H., and Norton, P.A., 2019, The U. S. Geological Survey National Hydrologic Model infrastructure—Rationale, description, and application of a watershed-scale model for the conterminous United States: Environmental Modelling & Software, v. 111, p. 192–203, accessed September 13, 2019. <https://doi.org/10.1016/j.envsoft.2018.09.023>.

Rosa, S.N., and Hay, L.E., 2019, Fena Valley Reservoir watershed and water-balance model updates and expansion of watershed modeling to southern Guam (ver. 1.1, February 2019): U.S. Geological Survey Scientific Investigations Report 2017–5093, 64 p., accessed August 27, 2019, at <https://doi.org/10.3133/sir20175093>.

Viger, R.J., Hay, L.E., Markstrom, S.L., Jones, J.W., and Buell, G.R., 2011, Hydrologic effects of urbanization and climate change on the Flint River Basin, Georgia: Earth Interactions, v. 15, no. 20, p. 1–25, accessed October 17, 2017, at <https://doi.org/10.1175/2010EI369.1>.

Van Beusekom, A.E., Hay, L.E., Viger, R.J., Gould, W.A., Collazo, J.A., and Khalyani, A.H., 2014, The effects of changing land cover on streamflow simulation in Puerto Rico: Journal of the American Water Resources Association, v. 50, no. 6, p. 1575–1593, accessed August 22, 2019, at <https://doi.org/10.1111/jawr.12227>.

Van Beusekom, A.E., and Viger, R.J., 2018, A physically based daily simulation of the glacier-dominated hydrology of the Copper River Basin, Alaska: Water Resources Research, v. 54, no. 7, p. 4983–5000, accessed September 5, 2019, at <https://doi.org/10.1029/2018WR022625>.

Viger, R.J., Hay, L.E., Jones, J.W., and Buell, G.R., 2010, Effects of including surface depressions in the application of the Precipitation-Runoff Modeling System in the Upper Flint River Basin, Georgia: U.S. Geological Survey Scientific Investigations Report 2010-5062, 36 p. <https://pubs.usgs.gov/sir/2010/5062/pdf/SIR10-5062.pdf>.

PRMS PROCESSES, MODULES AND UTILITY ROUTINES

Table 1 describes available process, initialization, and output modules, and utility routines. They are listed in computation order. Modules are written in the FORTRAN programming language. Data-structure and system utility routines are written in the C programming language. Additional modules and routines can be easily added that are written in FORTRAN, C, and other languages that can be linked to FORTRAN. Modules are listed in computation order. They are written in the FORTRAN programming language. Data-structure and system utility routines are

written in the C programming language. Additional modules and routines can be easily added that are written in FORTRAN, C, and other languages that can be linked to FORTRAN.

Table 1. PRMS Modules and Utility Routines

[Procedures: SETDIM (define dimension); DECL (define parameters and variables); INIT (set parameters values and initial variable values). Changes for version 5.2.1.1 are highlighted in [blue](#)]

| Module Name | Description | Procedures | Values in Initial Condition File |
|--------------------|---|--------------------------------|---|
| call_modules | Defines computation sequence, sets dimensions and most control parameters. | all | yes |
| basin | Defines shared domain wide and HRU parameters and variables, checks validity of parameter values. | DECL and INIT | |
| cascade | Computes routing order of cascading lateral flows from and to HRUs and to stream segments. | DECL, INIT, CLEAN | |
| climateflow | Defines and initializes climate and flow parameters used by multiple modules. | DECL, INIT, and CLEAN | yes |
| soltab | Calculates clear-sky solar radiation and daylight length for each day of the year. | DECL and INIT | |
| prms_time | Sets daily time variables and saves antecedent states. | DECL, INIT, and RUN | |
| obs | Sets values read from Data File(s). | SETDIMENS, DECL, INIT, and RUN | |
| water_use_read | Sets water-use diversions and gains from input files. | DECL, INIT, and RUN | |
| dynamic_param_read | Sets dynamic parameter values. | DECL, INIT, and RUN | |
| climate_hru | Sets climate values from pre-processed climate-by-hru (CBH) Files. | DECL, INIT, and RUN | |

| | | | |
|------------|--|--------------------------------|-----|
| temp_1sta | Distributes maximum and minimum temperatures to each HRU by using temperature data measured at one station and an estimated monthly lapse rate. | DECL, INIT, RUN, and CLEAN | yes |
| temp_laps | Distributes maximum and minimum temperatures to each HRU by computing a daily lapse rate with temperature data measured at two stations. | DECL, INIT, RUN, and CLEAN | yes |
| temp_sta | Distributes maximum and minimum temperatures to each HRU by using a station data, adjusted for distance, measured at each station. | DECL, INIT, RUN, and CLEAN | yes |
| xyz_dist | Determines the form of precipitation and distributes precipitation and temperatures to each HRU by using a multiple linear regression of measured data from a group of measurement or simulated stations. | SETDIMENS, DECL, INIT, and RUN | |
| temp_dist2 | Distributes maximum and minimum temperatures to each HRU by using a basin-wide lapse rate applied to the temperature data, adjusted for distance, measured at each station. | DECL, INIT, RUN, and CLEAN | yes |
| ide_dist | Determines the form of precipitation and distributes precipitation and temperatures to each HRU based on measurements at stations with closest elevation or shortest distance to the respective HRU. | DECL, INIT, and RUN | |
| temp_map | Distributes maximum and minimum temperatures to each HRU as area-weighted averages based on time-series input files with adjustment factors to account for differences in altitude, spatial variation, and topography. | DECL, INIT, and RUN | |

| | | | |
|---------------|---|----------------------------|-----|
| precip_1sta | Determines the form of precipitation and distributes it from one or more stations to each HRU by using monthly correction factors to account for differences in altitude, spatial variation, topography, and measurement gage efficiency. | DECL, INIT, and RUN | |
| precip_laps | Determines the form of precipitation and distributes it to each HRU by using monthly lapse rates. | DECL, INIT, and RUN | |
| precip_dist2 | Determines the form of precipitation and distributes it to each HRU by using an inverse distance weighting scheme. | DECL, INIT, and RUN | |
| precip_map | Determines the form of precipitation to each HRU as area-weighted averages based on a time-series input file with adjustment factor to account for gage efficiency. | DECL, INIT, and RUN | |
| frost_date | Preprocess module to determine the latest killing frost date in the spring and the earliest date in the Fall for each HRU for the simulation time period when model_mode specified as FROST. | DECL, INIT, RUN, and CLEAN | |
| ddsolrad | Distributes solar radiation to each HRU and estimates missing solar radiation data using a maximum temperature per degree-day relation. | DECL, INIT, and RUN | |
| ccsolrad | Distributes solar radiation to each HRU and estimates missing solar radiation data using a relation between solar radiation and cloud cover. | DECL, INIT, and RUN | |
| transp_tindex | Determines whether the current time step is in a period of active transpiration by the temperature index method. | DECL, INIT, RUN, and CLEAN | yes |
| transp_frost | Determines whether the current time step is in a period of active transpiration by the killing frost method. | DECL, INIT, and RUN | |

| | | | |
|-------------------|---|----------------------------|-----|
| potet_jh | Computes the potential evapotranspiration by using the Jensen-Haise formulation. | DECL, INIT, and RUN | |
| potet_hamon | Computes the potential evapotranspiration by using the Hamon formulation. | DECL, INIT, and RUN | |
| potet_pan | Computes potential evapotranspiration by using pan-evaporation data. | DECL, INIT, RUN, and CLEAN | yes |
| potet_pt | Computes the potential evapotranspiration by using the Priestley-Taylor formulation. | DECL, INIT, and RUN | |
| potet_pm_sta | Computes the potential evapotranspiration for each HRU by using pan-evaporation data. | DECL, INIT, and RUN | |
| potet_pm | Computes the potential evapotranspiration by using the Penman-Monteith formulation. | DECL, INIT, and RUN | |
| potet_hs | Computes the potential evapotranspiration by using the Hargreaves-Samani formulation. | DECL, INIT, and RUN | |
| write_climate_hru | Preprocess module to write distributed air minimum and maximum temperature, precipitation, potential solar radiation and potential evapotranspiration by HRU to files for use by climate_hru module for the simulation time period when model_mode specified as WRITE_CLIMATE. | DECL, INIT, RUN, and CLEAN | |
| intcp | Computes volume of intercepted precipitation, evaporation from intercepted precipitation, and throughfall that reaches the soil or snowpack. | DECL, INIT, RUN, and CLEAN | yes |
| snowcomp | Initiates development of a snowpack and simulates snow accumulation and depletion processes by using an energy-budget approach. | DECL, INIT, RUN, and CLEAN | yes |

| | | | |
|-----------------|--|----------------------------|-----|
| glacr | Computes glacier dynamics using three linear reservoirs (snow, firn, and ice). | all | yes |
| srunoff_smidx | Computes surface runoff and infiltration for each HRU by using a nonlinear variable-source-area method allowing for cascading flow. | DECL, INIT, RUN, and CLEAN | yes |
| srunoff_carea | Computes surface runoff and infiltration for each HRU by using a linear variable-source-area method allowing for cascading flow. | DECL, INIT, RUN, and CLEAN | yes |
| soilzone | Computes inflows to and outflows from the soil zone of each HRU and includes inflows from infiltration, groundwater, and upslope HRUs, and outflows to gravity drainage, interflow, and surface runoff to down-slope HRUs. | DECL, INIT, RUN, and CLEAN | yes |
| gwflow | Sums inflow to and outflow from PRMS groundwater reservoirs; outflow can be routed to downslope groundwater reservoirs and stream segments; | DECL, INIT, RUN, and CLEAN | yes |
| routing | Defines and computes common streamflow routing values for <code>strmflow_in_out</code> , <code>muskingum</code> , <code>muskingum_mann</code> , and <code>muskingum_lake</code> . | DECL, INIT, RUN, and CLEAN | yes |
| strmflow | Computes daily streamflow as the sum of surface runoff, shallow-subsurface flow, detention reservoir flow, and groundwater flow. | DECL and RUN | |
| muskingum | Routes water between stream segments using Muskingum routing method. | DECL, INIT, RUN, and CLEAN | yes |
| muskingum_mann | Routes water between stream segments using Muskingum routing method based on Manning's channel roughness coefficient. | DECL, INIT, RUN, and CLEAN | yes |
| strmflow_in_out | Routes water between segments in the system by setting the outflow to the inflow. | DECL and RUN | |

| | | | |
|--------------------|---|----------------------------|-----|
| muskingum_lake | Routes flow between stream segments and on-channel lakes using Muskingum routing for stream segments with six options for lake outflow and storage. | all | yes |
| strmflow_character | Computes stream segment characteristics (width, depth, area, velocity, and residence time) with the stream_temp is active. | DECL, INIT, and RUN | |
| stream_temp | Computes stream temperature based on SNTMP method. | DECL, INIT, RUN, CLEAN | yes |
| basin_sum | Computes daily, monthly, yearly, and total flow summaries of volumes and flows for all HRUs. | DECL, INIT, RUN, and CLEAN | yes |
| water_balance | Computes water balance components when print_debug specified as 1. | DECL, INIT, RUN, and CLEAN | |
| map_results | Writes HRU summaries to a user specified target map at weekly, monthly, yearly, and total time steps. | DECL, INIT, RUN, and CLEAN | |
| subbasin | Computes streamflow at internal basin nodes and HRU variables by subbasin. | DECL, INIT, and RUN | |
| nhru_summary | Writes specified nhru , nssr , and/or ngw variables to time-series files. | DECL, INIT, RUN, and CLEAN | |
| nsub_summary | Writes specified nhru , nssr , and/or ngw variables summarized to subbasin to time-series files. | DECL, INIT, RUN, and CLEAN | |
| basin_summary | Writes specified basin variables to a time-series file. | DECL, INIT, RUN, and CLEAN | |
| nsegment_summary | Writes specified nsegment variables to time-series files. | DECL, INIT, RUN, and CLEAN | |
| prms_summary | Writes a set of basin variables to a time-series file. | DECL, INIT, RUN, and CLEAN | |

| | | | |
|----------------|---|--|--|
| convert_params | Preprocess and convert parameters changed between PRMS IV and PRMS5 when model_mode is specified as CONVERT | | |
|----------------|---|--|--|

FREQUENTLY ASKED QUESTIONS

CONTROLLING SCREEN OUTPUT

There can be a large amount of information printed to the screen, including general information, warning messages, and error messages during initialization of a simulation. Sometimes the volume of screen output can make it difficult to see error messages. There are three options to reduce screen output. Set control parameter **parameter_check_flag** to 0 in the Control File to minimize warning messages about parameter values falling outside the suggested range. Set control parameter **print_debug** to -2 (minimum output, including not producing the PRMS **model_output_file**) or -1 (less output). However, setting **parameter_check_flag** = 1 and **print_debug** = 0 is good practice during initial model development as all warning and error messages are printed. But, once warnings are deemed acceptable, **parameter_check_flag** should be set to 0 and **print_debug** to -1 or -2 to decrease execution time.

FLEXIBLE SPECIFICATION FOR PARAMETERS

There are several ways to specify parameters. Traditionally, a single value is specified per line in the Parameter File. However, multiple values can be specified per line with a limit of 12,000 characters, including spaces per line. Lines with multiple values cannot end with blank character(s). Use of multiple values per line can be used to specify parameter values as a grid of columns by rows with the upper left value specified for HRU 1 and the lower right value for HRU **nhru**.

Prior to version 4.0.1, parameters had to be specified with the number of values determined by the dimension(s) as defined in table 1.3 of the PRMS documentation. Dimensions are defined in table 1.1. See file **PRMS_tables_5.2.1.1.pdf** included in the 'doc' directory for the most recent version of these tables. Now the user has several options to specify the number of parameter values based on the spatial and temporal variability, available data, or for some other purpose.

Parameters can be specified by the dimension(s) defined in table 1.3 (referred to herein as the maximum dimension(s)) or using compatible dimensions with the maximum dimension(s).

There are 6 options for specifying a parameter with dimensions **nhru,nmonths**: 4 using a single dimension: **one**, **nmonths**, **nsub**, or **nhru**, and 2 using two dimensions: **nsub,nmonths**, and **nhru,nmonths**. There are 3 options for a parameter with dimension of **nhru**: **one**, **nsub**, and **nhru**. The dimension options for a parameter with a maximum dimension of **nssr** are **one**, **nsub**, and **nssr**. The dimension options for a parameter with a maximum dimension of **ngw** are **one**,

nsub, and **ngw**. PRMS reads the dimension, number of values, and values from the Parameter File. If the parameter is not specified at the maximum dimension(s), the parameter values will be automatically expanded to the maximum dimension by the code.

Using subsets of the maximum dimensions and/or multiple values on lines can significantly reduce the size and number of lines in a Parameter File. The most used option is to specify parameters with the dimension **one** or **nsub** values for parameters that have a constant value for all HRUs or subbasins, respectively.

Additionally, the maximum dimension(s) for some parameters have been increased since version 4.0.1. Increasing the maximum number of values was added to accommodate simulation of large model domains that required increased spatial and/or temporal distribution of parameter values. For example, some parameters having dimension of **nmonths** now have a maximum dimension of **nhru,nmonths** and some parameters having dimension of **nhru** now have a maximum dimension of **nhru,nmonths**. Note, that using different number of values may change results when dimensions are specified greater than dimension(s) defined for older models while allowing for increased ability to calibrate spatially and temporally.

Using different number of values may change results when dimensions are specified greater than the original dimension(s) of older models while allowing for increased ability to calibrate spatially and temporally.

INITIAL CONDITIONS FILES

The Initial Conditions File is read whenever control parameter **init_vars_from_file** is specified > 0. This file must be created by the same model executable that is used in a restart simulation. Various initial states can be updated for a restart simulation using initial value parameters as specified in the Parameter File depending on the value of **init_vars_from_file**:

- 0 = do not read Initial Conditions File and use all initial value parameters as read from Parameter File;
- 1 = read all initial value parameters;
- 2 = read **dprst_frac_init**, **snowpack_init**, **segment_flow_init**, **elevlake_init**, **gwstor_init**, (**soil_rechr_init**, **soil_moist_init**, **ssstor_init** for model_mode = PRMS) or (**soil_rechr_init_frac**, **soil_moist_init_frac**, **ssstor_init_frac** for model_mode = PRMS5), and **stream_tave_init**;
- 3 = read **snowpack_init**;
- 4 = read **elevlake_init**;
- 5 = read (**soil_rechr_init_frac**, **soil_moist_init_frac**, **ssstor_init_frac** for model_mode = PRMS5);
- 6 = read **gwstor_init**;
- 7 = read **dprst_frac_init**;
- 8 = read **stream_tave_init**.

Options 2 and 3 could be used, for example, to update the snowpack in a restart simulation by specifying values for **snowpack_init** to reflect an observed or model snow water equivalent

data set. Option 8 could be used, for example, to update the stream temperature in each segment in a restart simulation by specifying values for **stream_tave_init** to reflect an observed or modeled stream temperature data set.

Things that cannot change for a restart simulation include: a) surface depression storage simulation option; b) cascading flow simulation option; c) dimensions **nhru**, **nssr**, **ngw**, **nsegment**, **nhru**, **nlake**; d) the model mode; and e) use of modules `temp_1sta`, `temp_laps`, `temp_dist2`, `potet_pan`, `transp_tindex`.

MODEL MODES

The control parameter **model_mode** is used to specify a variety of simulation and output options. If **model_mode** is not specified, the default value is `PRMS5`. The available values of **model_mode** are:

`PRMS5` or `prms5` – These modes use the parameters **tmax_allrain_offset**, **soil_rechr_max_frac**, **soil_rechr_init_frac**, **soil_moist_init_frac**, **ssstor_init_frac**, **sro_to_dprst_perv**, and **dprst_frac**.

`PRMS`, `prms`, `PRMS4`, `prms4`, or `DAILY` – These modes use the parameters **tmax_allrain**, **soil_rechr_max**, **soil_rechr_init**, **soil_moist_init**, **ssstor_init**, **sro_to_dprst**, and **dprst_area**.

`CONVERT` – This mode computes and produces the file `PRMS_5.params` that contains parameters **tmax_allrain_offset**, **soil_rechr_max_frac**, **soil_rechr_init_frac**, **soil_moist_init_frac**, **ssstor_init_frac**, **sro_to_dprst_perv**, and **dprst_frac** used in a `PRMS5` simulation on the basis of an existing Parameter File used with a `PRMS4` simulation. This file can be added to the Parameter File or input as another Parameter File. Parameters **tmax_allrain**, **soil_rechr_max**, **soil_rechr_init**, **soil_moist_init**, **ssstor_init**, **sro_to_dprst**, and **dprst_area** can be removed from the existing Parameter File.

`CONVERT4` – This mode computes and produces the file `PRMS_4.params` that contains parameters **tmax_allrain**, **soil_rechr_max**, **soil_rechr_init**, **soil_moist_init**, **ssstor_init**, **sro_to_dprst**, and **dprst_area** used in a `PRMS4` simulation on the basis of an existing Parameter File used with a `PRMS5` simulation. This file can be added to the existing Parameter File or input as another Parameter File. Parameters **tmax_allrain_offset**, **soil_rechr_max_frac**, **soil_rechr_init_frac**, **soil_moist_init_frac**, **ssstor_init_frac**, **sro_to_dprst_perv**, and **dprst_frac** can be removed from the existing Parameter File.

`FROST` – This mode computes and writes the file `frost_date.param` of frost parameters (**spring_frost** and **fall_frost**) using the `frost_date` module that can be used by the `transp_frost` module in subsequent simulations. This file can be added to the existing Parameter File or input as another Parameter File. This mode reads input files (Data, CBH, Dynamic Parameter, and Water-Use) and computes temperature and precipitation processes. All other processes are not computed.

WRITE_CLIMATE – This mode computes and writes Climate-by-HRU (CBH) File(s) for all climate processes that have the control parameters **precip_module**, **temp_module**, **et_module**, **swrad_module**, and/or **transp_module** specified equal to **climate_hru**. The filenames for CBH Files are specified by a control parameter: **precip_day** (precipitation in units defined by **precip_units**); **tmax_day** and **tmin_day** (air temperature in units defined by **temp_units**); **potet_day** (potential evapotranspiration in inches/day); **swrad_day** (for solar radiation in Langleys); and **transp_day** (transpiration as values 0 (off) or 1 (on)). The generated CBH File(s) can be used by the **climate_hru** module in subsequent simulations. The simulation reads input files (Data, CBH, Dynamic Parameter, and Water-Use) and computes temperature, precipitation, solar radiation, transpiration, and potential evapotranspiration processes, and writes requested CBH files. All other processes are not computed.

CLIMATE – This mode computes climate processes only. The simulation reads input files (Data, CBH File, Dynamic Parameter, and Water-Use) and computes temperature and precipitation. All other processes are not computed.

POTET – This mode computes processes through potential evapotranspiration. The simulation reads input files (Data, CBH, Dynamic Parameter, and Water-Use) and computes temperature, precipitation, solar radiation, transpiration, and potential evapotranspiration processes. All other processes are not computed.

TRANSPIRE – This mode computes processes through transpiration (active growing season). The simulation will only read input files (Data, CBH, Dynamic Parameter, and Water-Use) and compute temperature, precipitation, solar radiation, and transpiration. All other processes are not computed.

ERROR CODES

When a simulation normally ends the return code is 0. If an error is encountered one of the following return codes is issued. When an error occurs an error message is issued, and the simulation stops.

| | |
|----------------------------|----|
| Open of output file error | -3 |
| Open of input file error | -2 |
| Write to output file error | -1 |
| Control File read error | 1 |
| Dimension error | 3 |
| Parameter error | 4 |
| Data File error | 5 |
| Simulation time error | 6 |
| Temperature error | 7 |
| Streamflow routing error | 8 |
| Basin parameter error | 9 |
| Climate-by-HRU read error | 10 |
| Cascade error | 11 |

| | |
|--------------------------|----|
| Initial Conditions error | 12 |
| Dynamic parameter error | 13 |
| Water use error | 14 |
| Read or declare error | 15 |
| Module error | 16 |
| Muskingum lake error | 17 |
| Interflow error | 18 |

=====

Version 5.2.1.1 – December 01, 2023

The `strmflow_character` module was added to compute new variables `seg_area`, `seg_width`, and `seg_velocity` when control parameter `stream_temp_flag` is specified equal to 1. Binary CBH Files are not supported, do not use control parameter `cbh_binary_flag`.

Modifications that are more than simply code formatting are described below.

- Fix to computation of solar radiation for days where the sun does not rise (polar night), such as in Northern Alaska. Polar night conditions resulted previously in divide by zero in `ddsolrad`, for this condition on any HRU, `swrad` is set to 0.0.
- Some version dates of modules were updated.
- Binary CBH Files are not supported (do not use control parameter `cbh_binary_flag`).
- Use “:” instead of 1 as first dimension of two-dimensional arrays passed as arguments to routine as this is more portable between FORTRAN compilers in `nhru_summary`.

BUG FIXES

routing

- Fixed case where `seg_slope` is specified < 0.0000001 , the segment velocity was computed incorrectly on first time step for `muskingum_mann`.

stream_temp

- Fix to not check `seg_tave_water` < -98.0 and reset `t_o` to `seg_tave_water` as all other cases are correctly caught.
- Added check for `seg_width` ≤ 0.000001 , if true set `shade` and `svi` to 0.0 to avoid divide by zero computing `seg_width`.
- The lateral groundwater and subsurface temperatures had been computed incorrectly; they were based only on the values from a single stream segment as opposed to all segments in the model domain
- Under specific circumstances, certain segment-based variables (i.e., “`seg_lat`”, “`seg_humidity`”, etc.) had been reinitialized to a value of zero during the simulation,

they now retain the previous values. This change produces a notable improvement in performance of the simulation of "seg_tave_water" and related variables.

nhru_summary

- Fixed yearly values computed without inclusion of the last day of the year.

NEW FUNCTIONALITY

streamflow_character

- New module that is only called with `stream_temp` is active (control parameter **stream_temp_flag** is specified equal to 1). It has code taken from `stream_temp` to compute `seg_width` plus computation of `seg_velocity`, `seg_depth`, and `seg_area`. Computations are based on the methods described in: Moody, John, and Troutman, Brent. (2002). Characterization of the spatial variability of channel morphology. *Earth Surface Processes and Landforms*. 27. 1251 - 1266. 10.1002/esp.403.

PARAMETER CHANGES

New Parameters read from the Parameter File:

pref_flow_infil_frac

- Fraction of soil infiltration and cascading flow partitioned to preferential-flow storage. Previously, this fraction was set to **pref_flow_den** that also was used to set the water-holding capacity of the preferential-flow reservoir as a fraction of gravity reservoir water-holding capacity (**sat_threshold**). If **pref_flow_infil_frac** is not specified it is set to **pref_flow_den** to provide downward compatibility with existing models.

depth_alpha

- Alpha coefficient in power function for stream segment depth calculation as computed when `stream_temp` is active.

depth_m

- M value in power function for stream segment depth calculation as computed when `stream_temp` is active.

seg_close

- Index of closest segment from elevation and latitude for each a segment when `stream_temp` is active. If not specified, **seg_close** defaults to the upstream segment.

NEW VARIABLES

stream_character

- `seg_area`, `seg_velocity`, `seg_res_time`, and `seg_width`; area, mean velocity, mean residence time, and width of each segment, respectively.

=====
Version 5.2.1 – February 08, 2022

Modifications that are more than simply code formatting are described below

- Version dates of modules were updated.
- Dimension **nsnow** moved from `obs` to `call_modules`.
- GSFLOW: variable `hru_storage` computes PRMS storage for GSFLOW mode that does not include groundwater storage.
- Binary CBH Files are opened as `FORM=UNFORMATTED` and `ACCESS=STREAM` for both Windows and Linux executables. Previously Windows executables opened with `FORM=BINARY`.

BUG FIXES

`precip_dist2`

- Parameter **max_psta** was declared as a real instead of integer. This did not affect computations.

`temp_dist2`

- Parameter **max_tsta** was declared as a real instead of integer. This did not affect computations.

`intcp`

- `gain_inches` is now set to the unit water depth in the canopy instead of based on how the water is applied. `gain_inches_hru` is the unit water depth over the HRU.
- `basin_changeover` was declared incorrectly as dimensioned by **nhru** instead of **one**.

`cascade`

- **gw_up_id** was set to a single value of **hru_up_id**. Now all upstream values are used when **hru_segment** is used to define cascading flow (control parameter **cascade_flag** = 2).

`intcp`, `srunoff_smidx`, `srunoff_carea`, and `water_balance`

- The `use_sroff_transfer` flag was used to determine if `net_apply` from `intcp` was set to 1 when the canopy application is read from `water_use_read`, which was set whenever `water_use_read` is active. However, the `use_intcp_transfer` flag is set to 1 only when canopy irrigation is active. This latter flag is now used so that the code is slightly more efficient.

`potet_pm`, `potet_pt`, and `climate_hru`

- **humidity_cbh_flag** (flag to specify to read a CBH file with humidity values) and **humidity_day** (filename of the humidity CBH file) control parameters were ignored.

potet_pm and climate_hru

- **windspeed_cbh_flag** (flag to specify to read a CBH file with windspeed values) and **windspeed_day** (filename of the windspeed CBH file) control parameters were ignored.

stream_temp

- Computation of *seg_tave_lat* is moved before computation of the water temperature at the beginning of the time step. This change may lead to significantly different results from previous versions.

NEW FUNCTIONALITY

snowcomp

- The computation of approximate cloud cover as the ratio of measured radiation to potential radiation was based on basin variables, it can be optionally computed based on HRU variables, which could be important for large model domains, when control parameter **snow_cloudcover_flag** is specified equal to 1. The HRU equation is:

$$orad = swrad(ihru)*Hru_coss(ihru)*Soltab_horad_potsw(Jday,ihru))/Soltab_potsw(Jday,ihru)$$

$$cloud\ cover = orad/Soltab_horad_potsw(Jday,ihru)$$

- A daily snow albedo time series can be input from a Climate-by-HRU (CBH) file, the CBH filename is specified by control parameter **albedo_day** and is read when control parameter **albedo_cbh_flag** is specified equal to 1.

climate_hru

- Added reading of albedo and cloud cover CBH Files.

PARAMETER CHANGES

New Parameters read from the Control File:

albedo_cbh_flag

- Flag to indicate if snowpack albedo is read from a CBH File (0=no; 1=yes)

albedo_day

- Filename of snowpack albedo CBH File

snow_cloudcover_flag

- Flag to indicate if approximation of cloud cover for snowpack computations is computed using HRU dimensioned variables (0=no; 1=yes)

cloud_cover_cbh_flag

- Flag to indicate if cloud cover for use in `ccsolrad` is read from a CBH File (0=no; 1=yes)

cloud_cover_day

- Filename of cloud cover CBH File

NEW VARIABLES

`intcp`

- *gain_inches* and *gain_inches_hru* – application water to the canopy as a) depth in canopy and b) depth over the HRU, respectively. Both have units of inches.

`climate_hru`

- *albedo_hru* – Snowpack albedo of each HRU read from CBH File, units of decimal fraction.
- *cloud_cover_cbh* – Cloud cover of each HRU read from CBH File, units of decimal fraction.

`water_use_read`

- *soilzone_gain_hru* – Irrigation added to soilzone as depth over each HRU in units of inches.

Version 5.2.0 – January 20, 2021

This major release (PRMS version 5.2.0) adds new functionality for a) glacier dynamics (module `glacr_melt` and associated major changes to module enhancements to module `snowcomp`); glacier dynamics and two examples are described in Van Beusekom and Viger (2015), b) The continuous frozen ground (CFG) dynamics was added, which involved changes to modules `soilzone`, `srunoff_carea`, and `srunoff_smidx`; the CFG method is described in Mastin (2009), and c) distribution of air-temperature and precipitation on the basis of area-weighted mapping from input datasets, such as a gridded data sets (modules `temp_map` and `precip_map`).

There have been numerous changes to the `stream_temp` module since the previous release to address bugs. These include improved calculations of: 1) stream temperatures from stream flow coming from upstream segments; 2) water temperatures from lateral flows from adjacent land surfaces (i.e. lateral components of flow from adjacent HRUs); and 3) water temperatures due to the daily energy fluxes on the stream segments. This version of the `stream_temp` module will give significantly different simulation results than previous versions of the module. Any modeling work done with previous versions of this module should be redone with this (or subsequent) releases. Minor changes were made to several modules to improve code readability.

Modifications that are more than simply code formatting are described below.

- Initial Condition Files (i.e., Restart Files or antecedent conditions files) generated by previous versions of GSFLOW are not compatible with this version, thus they must be regenerated. Previous versions are not compatible because many basin area-weighted variables from prior versions of Restart Files are not needed to restart a simulation and are no included in the Initial Conditions Files.
- New files are: `prms_constants.f90` (contains constant values that are used by many modules that are used to improve code readability and consistency of numerical constants; some constants are new and others moved from `call_modules.f90` and `basin.f90`); `glacr_melt.f90` (glacier dynamics module); and `precip_map.f90` and `temp_map.f90` (precipitation and temperature distribution modules, respectively, on the basis of mapping from input file to HRUs).
- Changed how module version dates and descriptions are printed to screen and increased consistency in module declarations.
- Water use information applied in associated PRMS process modules instead of in module `water_use_read`. For example, transfers to/from PRMS lakes are applied in `muskingum_lake` and transfers to/from surface depression storage are applied in `srunoff_smidx` and `srunoff_carea`. The transfers were already applied in `soilzone`, `intcp`, and `gwflow`.
- There have been numerous changes to the `stream_temp` module since the previous release to address bugs. This version of the module will give significantly different simulation results than previous versions. Any modeling work done with previous versions of this module should be redone with this (or subsequent) releases.

BUG FIXES

`dynamic_parameter_read`

- Dynamic parameters `soil_moist_max`, `soil_rechr_max`, and `soil_rechr_max_frac` were ignored.

`muskingum` and `muskingum_mann`

- Restart File was incorrect as the string length of the module name was checked using a different string length.

`snowcomp`

- Fixed possibility of divide by zero when setting maximum snow-water equivalent value (variable `ai`) and computing the fraction of maximum snow-water equivalent (variable `frac_swe`). The former can happen when the maximum snow-water equivalent threshold (parameter `snarea_thresh`) value is 0.0 on an HRU. The latter can occur when values of `ai` are small (<0.1). variable `ai`).
- Variable `ai` is reset when snowpack disappears instead of every timestep.
- Variable `ai` is saved in the Restart File.
- Variables `scrsv`, `pksv`, `pk_den`, and `frac_swe` are reset when snowpack disappears during a timestep.

`stream_temp`

- Improved calculations of stream temperatures from stream flow coming from upstream segments.
- Improved calculations of water temperatures from lateral flows from adjacent land surfaces (i.e. lateral components of flow from adjacent HRUs).
- Improved calculations of water temperature due to the daily energy fluxes on the stream segments.

`mmf.c`

- Removed an extra argument to three usages of routine `fprintf` that caused warning messages to be issued during compilation.

NEW FUNCTIONALITY

New files are: `prms_constants.f90` (contains constant values that are used by many modules that are used to improve code readability and consistency of numerical constants; some constants are new and others moved from `call_modules.f90` and `basin.f90`); `glacr_melt.f90` (glacier dynamics module); `precip_temp_map.f90` (precipitation and temperature distribution modules on the basis of mapping from input file to HRUs).

`prms_constants.f90`

- This file defines constants used by many PRMS Modules. These constants are named to increase readability of the FORTRAN code; they do not affect model input, such as specified in the Parameter and Control Files. For example, the constant FAHRENHEIT is set equal to 0 and CELSIUS is set equal to 1 to use in module code to check the value of parameter **temp_units**, if the user specifies as 0 for Fahrenheit and 1 for Celsius in a Parameter File. Similarly, constants SAND is set equal to 1, LOAM = 2, and CLAY = 3 to use in modules that check the value of parameter **soil_type**. Another example is the named constants *ON* and *OFF* that are set to 1 and 0, respectively. Some values were moved from other files, mostly from files `call_modules.f90` and `basin.f90`.

precip_map

- This module distributes precipitation to each HRU using precipitation data specified in a Map File as a time series of gridded or other spatial units using an area-weighted method and a correction factor to account for differences in altitude, spatial variation, topography, and data accuracy between the spatial scale of the values specified in the Map File and HRUs. The module requires daily input, thus, any temporal discrepancies (i.e., the values in the Map File are valid for noon one day to noon of the second day are not considered. Values are assumed to be valid for each full day. The Map File is a text file with each day specified by a date and time (year, month, day, hour, minute, second) followed by **nhru** values in order of HRU 1 through **nhru**. Each value can be separated by a space and/or comma. The values for hour, minute and second are specified as 0. For example, the date and time of 2021/1/20 12:15:00:00 can be specified as: 2021 1 20 12 15 0 0 0. Any number of lines can be used to specify each day. For example, if the HRUs are a grid, one way to specify a day is the date on one line followed by values in a gridded format with the number of lines equal to the number of rows in the grid and the number of values on a line equal to the number of columns in the grid. Each HRU is associated with one or more values in the Map File as a fraction based on an intersection of the HRU map and gridded or other map. Use of this option can increase execution speed by reducing the volume of input read during a simulation for models that would require very large climate-by-HRU (CBH) Files that are typically pre-processed distributions of gridded data. Typically, the source gridded data file is much smaller than a CBH File. Additionally, the module allows for calibration adjustments using parameters. See below and/or in the file `PRMS_tables_5.2.pdf` for a description of the required dimensions and parameters, each are labeled with `precip_map` (dimensions **nmap** and **nmap2hru**, parameters **hru2map_id**, **hru2map_pct**, **map2hru_id**, and **precip_map_adj**)

temp_map

- This module distributes maximum and minimum temperatures to each HRU using precipitation data specified in a Map File as a time series of gridded or other spatial units using an area-weighted method and a correction factor to account for differences

in altitude, spatial variation, topography, and data accuracy between the spatial scale of the values specified in the Map File and HRUs. The module requires daily input, thus, any temporal discrepancies (i.e., the values in the Map File are valid for noon one day to noon of the second day) are not considered. Values are assumed to be valid for each full day. The Map File is a text file with each day specified by a date and time (year, month, day, hour, minute, second) followed by **nhru** values in order of HRU 1 through **nhru**. Each value can be separated by a space and/or comma. The values for hour, minute and second are specified as 0. For example, the date and time of 2021/1/20 12:15:00:00 can be specified as: 2021 1 20 12 15 0 0 0. Any number of lines can be used to specify each day. For example, if the HRUs are a grid, one way to specify a day is the date on one line followed by values in a gridded format with the number of lines equal to the number of rows in the grid and the number of values on a line equal to the number of columns in the grid. Each HRU is associated with one or more values in the Map File as a fraction based on an intersection of the HRU map and gridded or other map. Use of this option can increase execution speed by reducing the volume of input read during a simulation for models that would require very large climate-by-HRU (CBH) Files that are typically pre-processed distributions of gridded data. Typically, the source gridded data file is much smaller than a CBH File. See below and/or in the file **PRMS_tables_5.2.pdf** for a description of the required dimensions and parameters, each are labeled with `precip_map` (dimensions **nmap** and **nmap2hru**, parameters **hru2map_id**, **hru2map_pct**, **map2hru_id**, and **temp_map_adj**)

`glacr_melt`

- This module computes glacier dynamics using three linear reservoirs (snow, firn, ice) with time lapses and ability to advance or retreat according to volume-area scaling. The altitude of HRUs can change due to glacial dynamics on any time step, so climate distribution methods that are based on lapse rates use the altitude computed on the previous time step of glacier HRUs. This affects modules `xyz_dist`, `temp_laps`, `precip_laps`, `temp_1sta`, `temp_dist2`, `ide_dist`, and `basin`. The addition of glacier dynamics required significant changes to the `snowcomp` module. New variables were added for glacier runoff to the stream network and from HRUs. An HRU that is or might become glaciated during a simulation is specified by setting the value of parameter **hru_type** to 4.

Frozen ground dynamics

- Code was added to the modules `basin`, `water_balance`, `srunoff_smidx`, `srunoff_carea`, and `soilzone` to include the continuous frozen ground index (CFG) method. This addition did not require a new module.

Irrigation application to the canopy – `intcp`

- A value for parameter **irr_type** is specified for each HRU that is used to select how irrigation water, as input to the `water_use_read` module, is applied within and HRU. The meaning of each **irr_type** value follows. Two options for **irr_type** have been added with this release. The first new option (**irr_type**=3, sprinkler application) applies the specified amount of water across the whole HRU, which allows the specified irrigation water to be applied to the plant canopy and non-covered areas, which allows for interception and throughfall across the HRU. The existing options, **irr_type**=0 and **irr_type**=1, sprinkler and ditch/drip application, respectively, apply the specified irrigation water only to the canopy. For **irr_type** = 1, 2, and 3 the irrigation water is specified as an HRU-area weighted average value. The second new option (**irr_type**=4, living filter application) allows for the irrigation water amount to be specified as the amount of water applied to the plant canopy, i.e., not an HRU-area average value. Note, **irr_type**=2 signals to ignore any specified irrigation water.

Stop Conditions

- ERROR messages issued by modules have been reworded to be more consistent in format. Additionally, in ERROR messages and at the termination of a simulation a value is output. A non-zero value indicates an ERROR was detected in the simulation. The values are output according to the following list:

-4 = read input error
-3 = open output file error
-2 = open input file error
-1 = write output error
0 = no error
1 = control parameter error
2 = variable range error
3 = dimension range error
4 = parameter range error
5 = data file input error
6 = timestep error
7 = air temperature range error
8 = streamflow range error
9 = basin module error
10 = Climate-by-HRU (CBH) input error
11 = Cascade input error
12 = Restart file error
13 = Dynamic parameter error
14 = Water-use error
15 = parameter or variable error
16 = module error
17 = lake error
18 = soilzone error

NEW DIMENSIONS

nmap

- Number of spatial units in mapped climate, used in modules `temp_map` and `precip_map`.

nmap2hru

- Number of intersections between HRUs and spatial units in mapped climate, used in modules `temp_map` and `precip_map`

four

- Number of glacier variables in integer array, fixed at 4, used in module `glacr_melt`.

nglres

- Number of reservoirs in a glacier, fixed at 3, used in module `glacr_melt`.

seven

- Number of glacier variables in real array, fixed at 7, used in module `glacr_melt`.

PARAMETER CHANGES

New Parameters read from the Control File

frozen_flag

- Flag to indicate if continuous frozen ground index simulation is computed (0=no; 1=yes)

glacier_flag

- Flag to indicate if glacier simulation is computed (0=no; 1=yes)

mbInit_flag

- Flag to indicate the method used for initial mass balance of glaciers (0=no optimization; 1=use first year of climate data; 2=constant mass balance gradient above and below equilibrium line altitude (ELA))

stream_temp_shade_flag

- Flag to indicate how shade is used in the `stream_temp` module (0 = compute shade; 1 = specified as a constant)

outputSelectDatesON_OFF

- Switch to indicate if `nhru_summary` output files are generated for a specified set of dates (0=no, output time series on basis of `nhruOut_freq`; 1=yes, specify dates in file specified by `selectDatesFileName`)

selectDatesFileName

- String to define the filename of the set of dates to output values of `nhru_summary` output files in chronological order with dates specified as YEAR MONTH DAY with a space(s) and/or comma separating YEAR and MONTH and MONTH and DAY (e.g. 1959 09 01)

New Parameters: read from Parameter Files

See the file 'PRMS_tables_5.2.0.pdf' for descriptions of the 16 new parameters related to the simulation of glacier dynamics. These are identified by highlighted red text in the Glacier and frozen ground computations section of Table 1-3.

hru2map_id – used in modules `temp_map` and `precip_map`.

- HRU identification number associated with each intersection between the HRU map and grid or other spatial unit map with **nmap2hru** number of values and maximum value **nhru**.

hru2map_pct – used in modules `temp_map` and `precip_map`.

- Portion of HRU associated with each intersection between the HRU map and grid or other spatial unit map with **nmap2hru** number of values, expressed as a decimal fraction.

map2hru_id – used in modules `temp_map` and `precip_map`.

- Grid or other spatial unit identification number associated with each intersection between the HRU map and grid or other spatial unit map with **nmap2hru** number of values with maximum value **nmap**.

precip_map_adj – used in module `precip_map`.

- Monthly (January to December) multiplicative adjustment factor to mapped precipitation to account for differences in elevation, and so forth.

tmax_map_adj – used in module `temp_map`.

- Monthly (January to December) additive adjustment factor to maximum air temperature for each mapped spatial unit estimated on the basis of slope and aspect.

tmin_map_adj – used in module `temp_map`.

- Monthly (January to December) additive adjustment factor to minimum air temperature for each mapped spatial unit estimated on the basis of slope and aspect.

cfgi_decay – used in frozen ground simulation option.

- Continuous frozen ground index (CFG I) daily decay index, value of 1.0 is no decay.

cfgi_thrshld – used in frozen ground simulation option.

- Continuous frozen ground index (CFG I) threshold value indicating frozen soil.

Updated Parameters read from a Parameter File

hru_type

- A value of 4 specifies that the HRU is or can be glaciated.

adjust_rain and adjust_snow

- The maximum suggested value was increased to 3.0. They are used in modules `xyz_dist` and `ide_dist`.

rain_adj

- The maximum suggested value was increased to 10.0. It is used in module `precip_1sta`.

ssr2gw_rate

- The units were corrected to be inches/day and the maximum suggested value increased to 999.0. See description of deprecated parameter **ssrmax_coef** in table 1.3, page 53 of the PRMS documentation report for the formulation of computing gravity drainage with **ssr2gw_rate**. The parameter **ssrmax_coef** was replaced with the constant 1.0, with units of inches.

width_alpha

- The units were corrected to be meters and the maximum suggested value increased to 1000.0 and the default value changed to 1.0. It is used in the `stream_temp` module.

irr_type

- Added two options (3 and 4) for application method of irrigation water for each water-use plant canopy time-series. Values are specified for each HRU with one of the following: 0 = sprinkler method with interception only; 1=ditch/drip method with no interception; 2=ignore; 3=sprinkler across whole HRU with interception and throughfall; and 4=sprinkler method with amount of water applied on the basis of cover density, such as a living filter. Note, for options 1, 2, and 3 the irrigation water is specified as an HRU-area weighted average value as cubic feet per second.

NEW VARIABLES

See the file '**PRMS_tables_5.2.0.pdf**' for descriptions of the 72 new variables related to the glacier dynamics and 3 new variables for frozen ground computations. These are identified by highlighted **red** text in Glacier and frozen ground computations section of Table 1-5.

gwflow

- **lakein_gwflow** – Groundwater flow received from cascading upslope GWRs for each Lake GWR in units of acre-inches.

basin

- *hru_elev_ts* – HRU elevation for timestep, which can change for glaciers.

Version 5.1.0 – May 01, 2020

Modifications that are more than simply code formatting are described below. Parameter Files for example problems were converted to use the new PRMS5 parameters instead of the equivalent PRMS4 parameters. Initial Condition Files (i.e., Restart Files or antecedent conditions files) generated by previous versions of PRMS are not compatible with this version, thus they must be regenerated. Note, the simulation time period for the antecedent simulation is written into the file and printed as well as additional variables are now retained.

Modules and utilities

This major release adds new functionality for simulation of stream temperature (module *stream_temp*), and output summary for HRU and segment dimensioned variables optionally can be output in a gridded CSV format, computation of Muskingum routing on the basis of computing the Muskingum routing equation coefficients using the Manning’s N equation (module *muskingum_mann*), and soil-water evapotranspiration computed based on the potential evapotranspiration (PET) rate instead of the unsatisfied PET rate as computed in module *soilzone*. This latter change means that models calibrated using previous versions may have significant changes to results as the soil-water evapotranspiration can be greater than previous versions, which affects states and fluxes of the soil zone. Also, corrected major bugs in the *dynamic_param_read* module, where the dynamic parameter time series files were sometimes not being read correctly and the potential evapotranspiration coefficients were being reset every timestep instead of only when a new set of dynamic parameters were available for a given timestep. Note, variable *wind_speed* when specified in the Data File must be specified in units of meters per second (not miles per hour) for use with module *potet_pm_sta*.

BUG FIXES

dynamic_param_read and *utils_prms.f90*

- Dynamic parameter files were not always read correctly. The code now verifies that a line beginning with ##### starts each new set of values.

dynamic_param_read

- Variables *soil_moist_tot*, *basin_soil_rechr*, and *basin_soil_moist* were not always set correctly; no other computations were affected. Note, these were computed correctly by the *soilzone* module, thus they were correct at the end of a timestep.
- The potential evapotranspiration coefficients were being reset every timestep instead of only when a new set of dynamic parameters were available for a given timestep.

`cascade`

- Fortran compiler error to pass a function argument to another routine. This was not an error in earlier versions of compilers used to build PRMS.

`climateflow`

- Variable *orad* was always initialized to 0.0 instead of being set by value in the Restart File, if used. This doesn't affect any other computations.

`srunoff_smidx` and `srunoff_carea`

- Variable *hru_imperv_stor* was always initialized to 0.0 instead of being set by value in the Restart File, if used. This omission might have affected some water balance computations for restart simulations.
- Water-use input was not added to variable *infil* if there was also cascading flow.
- A rare, small, water balance issue was found for the conditions that canopy storage exists in an HRU on the day that the transpiration period changes (i.e., a change of growing season) and there is a decrease in canopy density, there is snowmelt, and there is not a mixed precipitation event. The excess canopy storage was added for the computation of soil infiltration and surface runoff. If all these conditions happened, it is likely the water balance for that day and that HRU would be off by very small amount, such as less than 0.003 inches. The amount would depend on the canopy cover density differences and maximum storage capacity in the canopy. This will only happen when the difference between **covden_sum** and **covden_win** is positive, with canopy storage, and snow on the ground at the growing season end, which often people have set as October 1, the old default value for **transp_end** when using module `transp_tindex`. Similarly, it could happen if the difference between **covden_win** and **covden_sum** is positive under the same conditions.

`potet_pm_sta`

- Variable *wind_speed* as specified in the Data File must be specified in units of meters per second, not miles per hour as documentation previously stated in error. This is not a bug in the code, but an error in the documentation.

CHANGES THAT CAN AFFECT SIMULATION RESULTS

`soilzone`

- Values of soil-water evapotranspiration (ET) are computed based on the potential evapotranspiration (PET) rate instead of the unsatisfied ET rate (PET rate less canopy, snowpack, impervious storage, and surface-depression storage ET) when control parameter **soilzone_aet_flag** is specified equal to 1. This change may significantly alter results of existing models compared to using previous versions of PRMS. The change typically would increase soil-water ET and reduce soilzone storage, recharge rate, and groundwater storage and fluxes. If **soilzone_aet_flag** is not specified equal to 1, then

soil-water ET is computed as done in previous versions, i.e., based on the unsatisfied PET rate and fraction of the upper zone of the total capillary reservoir water-hold capacity, thus maintaining downward compatibility for existing models. It is recommended that **soilzone_aet_flag** be specified equal to 1 for new models.

- If any lake evaporates at greater than the computed PET rate, then the PET rate is set equal to the lake evaporation rate for the lake HRU and variable *basin_potet* is recomputed. This can occur if **lake_evap_adj** is specified greater than 1.0.

`utils_prms.f90`

- Open statements for binary files must specify UNFORMATTED instead of BINARY for Linux-based computers. This is a code difference between Windows and Unix versions. A second version of `utils_prms.f90`, named `utils_prms_linux.f90` is provided for use on Linux-based computers.

NEW FUNCTIONALITY

`muskingum_mann`

- Specifying control parameter **strmflow_module** to `muskingum_mann` provides an additional method to compute **K_coef** values, which are used along with values of parameter **x_coef** to compute coefficients for the Muskingum streamflow routing method. Values of **K_coef** are computed in `routing.f90` based on the values of new parameters **mann_n**, **seg_length**, **seg_depth**, and **seg_slope**.

$$velocity = (1.0 \div \mathbf{mann_n}(i)) \times \sqrt{\mathbf{seg_slope}(i)} \times \mathbf{seg_depth}(i)^{2/3}$$

$$\mathbf{K_coef}(i) = \mathbf{seg_length}(i) \div (velocity \times 60 \times 60)$$

K_coef values computed greater than 24.0 are set to 24.0, values computed less than 0.01 are set to 0.01, and the value for lake HRUs is set to 24.0. Note, **K_coef** values are specified as a parameter when **strmflow_module** is specified as `muskingum`

`snowcomp`

- Snow depletion curves optionally can be specified using an equation on the basis of new parameters **snarea_a**, **snarea_b**, **snarea_c**, and **snarea_d** when control parameter **snarea_curve_flag** is specified equal to 1. Otherwise, the snow depletion curves are specified as in previous versions using parameters **hru_deplcrv** and **snarea_curve**. Each of 11 values of the depletion curve are computed as for each HRU (index *i*):

$$snarea_curve(j, i) = (snarea_a(i) - snarea_d(i)) \div \left(1 + \left(x^{(snarea_b(i))} \div snarea_c(i) \right) \right) + snarea_d(i)$$

where variable x equals 0.0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, and 1.0 as index j increments from 1 to 11. Note, **snarea_a** is the minimum value of snowpack water equivalent (SWE) and defaults to 0 and values can have a maximum value of 1.0.

`nhru_summary`

- output summary optionally can be output in a gridded CSV format with number of columns of values specified by control parameter **nhruOutNcol**. If **nhruOutNcol** is specified equal to 0 or not specified each output line contains all **nhru** values as in previous versions.

`strmflow_in_out`

- Parameter **segment_flow_init** applied in routing.f90 to allow initialization of flows in all segments instead of always starting with zero flows, code changes made in `muskingum`, `muskingum_lake`, `muskingum_mann`, and `routing.f90`.

`dynamic_param_read`

- Control parameter **dynamic_param_log_file** added to allow the name of the log file to be specified rather than hard-coded. This allows multiple simulations to be executed in a single Windows directory as multiple log files can be open when different names are specified in each Control File.

PARAMETER CHANGES

New Control Parameters

soilzone_aet_flag

- Flag to specify whether to compute soil-water evapotranspiration (ET) based on unsatisfied potential ET (PET) (0=compute soil-water ET based on unsatisfied ET; 1=based on PET); set to 0 for downward compatibility of old models though it is recommended setting to 1 for new models.

dynamic_param_log_file

- Specifies the name of the log file written when the `dynamic_param_read` module is active.

nhruOutNcol

- Specifies the number of columns written per line for `nhru_summary` output, which can be used to generate gridded output. If not specified or set to 0, all values for each timestep are written on a single line as in previous versions.

stream_temp_flag

- Flag to activate simulation of stream temperature using the `stream_temp` module (0=off; 1=on).

strmtemp_humidity_flag

- Flag to specify where humidity information is read for use by the `stream_temp` module (0=CBH File specified by control parameter **humidity_day**; 1=parameter **seg_humidity**; 2=Data File with values assigned based on parameter **seg_humidity_sta**).

snarea_curve_flag

- Flag to specify whether to compute snow depletion curves for each HRU using an equation on the basis of new parameters **snarea_a**, **snarea_b**, **snarea_c**, and **snarea_d** when control parameter **snarea_curve_flag** is specified equal to 1. (0=specify snow depletion curves using parameters **hru_deplcrv** and **snarea_curve**; 1=compute snow depletion curves).

Updated Control Parameters

csvON_OFF

- If specified equal to 2, only simulated and measured streamflow pairs are written to PRMS CSV File specified by control parameter **csv_output_file**.

print_debug

- If specified equal to -2, screen output is very limited, and the PRMS water budget file specified by control parameter **model_output_file** is not generated and the `basin_sum` module is not used. Thus, all computed variables unique to `basin_sum` are not available.

`strmflow_module`

- New option: `muskingum_mann`, where Muskingum routing parameter **K_coef** is computed as described above.

Updated Parameters

lake_evap_adj

- Maximum value changed to 1.5 to allow lakes to evaporate at greater than potential evapotranspiration (PET) rate, such as during winter months when lake water temperature may be greater than air temperature.

den_init, den_max, settle_const

- These snow parameters now have a maximum dimension of **nhru**. Previously, they were scalar values (dimension of **one**).

New Parameters

See the file '**PRMS_tables_5.1.0.pdf**' for descriptions of the 27 new parameters related to the stream temperature module. These are identified by highlighted **magenta** text in the Stream temperature simulation section of Table 1-3.

ppt_zero_thresh – changes in `climateflow`, `climate_hru`, and `obs`.

- Sets the minimum value for precipitation values specified in the Data File specified by control parameter **data_file** or CBH File specified by control parameter **precip_day**. Precipitation values below this threshold are set to 0.0. Default value is 0.0. An example use case of this functionality is to control for drizzle associated with some downscaled general circulation model climate inputs.

mann_n – added to `routing`.

- Specifies the Manning’s roughness coefficient for each segment as a dimensionless value for use by module `muskingum_mann`. Default value is 0.04.

seg_slope – added to `routing`.

- Specifies the surface slope of each segment as approximation for bed slope as a decimal fraction for use by module `muskingum_mann`. Default value is 0.0001.

seg_length – added to `routing`.

- Specifies the length of each segment in meters for use by module `muskingum_mann`. Default value is 1.0.

seg_depth – added to `routing`.

- Specifies the segment depth at bank full of each segment in meters for use by module `muskingum_mann`. Default value is 1.0.

NEW VARIABLES

See the file ‘**PRMS_tables_5.1.0.pdf**’ for descriptions of the 13 new variables related to the stream temperature module. These are identified by highlighted magenta text in Stream temperature simulation section of Table 1-5.

`soilzone`

- *soil_saturated* – set to 1 if capillary zone is saturated by an infiltration event, otherwise set to 0.

SMALL CHANGES THAT DO NOT AFFECT ANY COMPUTATIONS

`muskingum`, `muskingum_lake`, and `routing`

- Parameter **segment_flow_init** applied in `routing` and so code is not duplicated in Muskingum modules.

`climateflow`

- Add variables *basin_potsw* and *basin_humidity* to the Restart File.

=====

Version 5.0.0 – May 30, 2019 - doi:10.5066/P91FBZOB

This major release adds new functionality for:

- input of dynamic parameters and water use data;
- Muskingum streamflow routing with simulation of lakes;
- output of subbasin, stream segment, and basin variables to Comma-Separated-Variable (CSV) files by activating modules `nsub_summary`, `nsegment_summary`, and/or `basin_summary`;
- an option to compute potential evapotranspiration by using the Penman-Monteith formulation on the basis of specified windspeed and humidity data in the Data File; and
- distribution of air temperature on the basis of specified minimum and maximum data in the Data File.

Also, corrected major bugs in the `potet_pm` and `potet_pt` modules and minor bugs in the `soilzone` and `gwflow` modules. See “**Update of PRMS PET modules.pdf**” file in the ‘doc’ subdirectory for corrections to PRMS-IV documentation report regarding the potential evapotranspiration modules.

Restart Files generated by previous versions are not compatible with the current version, thus they must be regenerated. The simulation time period for the antecedent simulation is written into the file and printed after it is read.

Several PRMS parameters are deprecated and replaced by new parameters that were added to facilitate automated model calibration. Most of the deprecated parameters were codependent with other parameters and were specified as a depth per unit area. The new parameters are specified as a fraction of or offset to the related deprecated parameter. To use the new parameters, specify **model_mode** as `PRMS5`. To retain downward compatibility, to use the deprecated parameters, specify **model_mode** as `PRMS`. Parameter Files for example problems were converted to use the new `PRMS5` parameters instead of the equivalent `PRMS4` parameters. A new module was added to facilitate adding the new parameters to an existing model. To activate this module, specify control parameter **model_mode** as `CONVERT` to produce a file of the new parameters. Similarly, specifying **model_mode** as `CONVERT4` will produce a file of the old parameters based on a model using the new parameters. Once the new parameters are added to a Parameter File it is recommended the old parameters be removed.

See the file ‘**tm6b8_PRMS_enhancements.pdf**’ (Regan and LaFontaine, 2017) in the ‘doc’ subdirectory for documentation on the dynamic parameters; water-use, lake simulation, and HRU summary options.

INITIAL CONDITIONS FILES

- Initial Condition Files made with previous PRMS versions are not compatible with this version; thus, they must be regenerated. The simulation time period for the antecedent

simulation is written into the file and printed when used. The new files are about 75 percent smaller as only variables needed to maintain a water balance are stored.

Modules with fewer values saved are: `snowcomp`, `soilzone`, `srunoff_smidx`, `srunoff_carea`, `routing`, `gwflow`, `intcp`, and `muskingum`.

- Restriction for changing to or from modules `potet_pt`, `potet_pm`, `potet_pm_sta`, `ide_dist`, and `xyz_dist` for restart simulations has been removed.
- Restriction for changing the content of Data File(s) for restart simulations has been removed.
- Options that cannot change for a restart simulation include: a) surface depression storage simulation option; b) cascading flow simulation option; c) dimensions **nhru**, **nssr**, **ngw**, **nsegment**, **nhruccell**, **nlake**; and d) the model mode (PRMS or PRMS5); and e) use of modules `temp_1sta`, `temp_laps`, `temp_dist2`, `potet_pan`, `transp_tindex`.
- Various states can be updated for a restart simulation by using new options as specified by control parameter `init_vars_from_file` (0 = do not read initial value parameters; 1 = read all initial value parameters; 2 = read **dprst_frac_init**, **snowpack_init**, **segment_flow_init**, **elevlake_init**, **gwstor_init**, (**soil_rechr_init**, **soil_moist_init**, **ssstor_init** for `model_mode` = PRMS) or (**soil_rechr_init_frac**, **soil_moist_init_frac**, **ssstor_init_frac** for `model_mode` = PRMS5); 3 = read **snowpack_init**; 4 = read **elevlake_init**; 5 = read (**soil_rechr_init_frac**, **soil_moist_init_frac**, **ssstor_init_frac** for `model_mode` = PRMS5); 6 = read **gwstor_init**; 7 = read **dprst_frac_init**). Options 2 and 3 could be used, for example, to update the snowpack based on observed values of snowpack water equivalent by restarting a simulation and specifying values for **snowpack_init** to reflect an observed or model snow water equivalent data set.

BUG FIXES

snowcomp

- When a snowpack is melting and there is a new snowfall, the code saves the point on the depletion curve (variable `snowcov_areasv`) and then depletes the snowpack from **snarea_curve**(11,k) over the subsequent time steps until the snow cover is less than or equal to `snowcov_areasv` on the basis of linear interpolation. See Figure 1-4, page 97 of the PRMS-IV documentation report (TM6-B7, Markstrom and others, 2015) for a depiction of how to compute snow-water equivalent (SWE) using a depletion curve after a secondary snowfall. However, `snowcov_areasv` was set to **snarea_curve**(11,k), the maximum value of a snow depletion curve, instead of current value of `snowcov_area`. This issue was fixed. This change can affect results of the snowpack depletion for secondary snowfalls as depletion begins at the maximum value of the depletion curve instead of returning to the point of departure from the depletion curve from which it

was melting prior to the snowfall. Thus, there will be no change for many simulations, but noticeable changes could occur for some simulations.

- Variable *frac_swe* was not computed for all time steps, this was corrected, and the variables were changed to single precision; this change did not affect other computations.
- Variable *tcal* was not reset to 0.0 for all time steps, which might have meant values were carried over after a snowpack melted, this was corrected; this change did not affect other computations.
- Initial snow cover area was computed incorrectly, this would only affect the first timestep.

temp_dist2

- Values for parameter **tmax_adj** and **tmin_adj** were not read from the Parameter File and were likely set to zero or very small values.

climate_hru

- Corrected check that looked for first simulation time step in CBH Files that failed if simulation start month and year were earlier than the first date in the CBH File.

soilzone

- Parameters **soil_moist_max**, **soil_rechr_max**, and **soil_rechr_max_frac** could have values specified equal to 0, which would cause divide by zero in several equations. To prevent divide by zeros and to allow for some minimum storage in capillary reservoirs to receive cascading flow, the code was modified to issue an error if values for these parameters are specified less than 0.00001. If control parameter **parameter_check_flag** is specified equal to 0, a warning message is issued, and the value is set to 0.00001.
- Parameters **slowcoef_lin**, **slowcoef_sq**, **fastcoef_lin**, and **fastcoef_sq** can have values specified equal to 0. However, under rare conditions, doing so could cause a divide by zero. The code was modified to trap for possible divide by zero and ensure a valid value is computed for interflow. Also, for some combinations of these parameters and a large gravity storage value it was possible to compute very small negative values of interflow due to floating point precision round off error. The code was modified to set any computed negative values of interflow to 0.

prms_summary

- If values for optional parameter **poi_gage_segment** were greater than 999999 values in the header row were truncated at 7 digits. This has been corrected. Additionally, the format of the output values was changed from a fixed 10-digit exponential to values with 4 decimal places with as many values to the left of the decimal places as required.

routing

- Values for solar radiation and potential evapotranspiration could be computed incorrectly for segments that did not have associated HRUs, this has been fixed to assign values from closest upstream segment.

CHANGES THAT CAN AFFECT SIMULATION RESULTS

snowcomp

- For calculations of emissivity and energy related to convection or condensation, the code checks if there is precipitation on an HRU instead of anywhere in the model domain to adjust these values based on precipitation and cloud cover.
- Snow depletion curves must be specified, previous versions allowed snow depletion curves to not be specified when dimension **ndep1** was specified equal to 0.
- Several checks for small negative round-off errors were removed to reduce bias in round-off error. Thus, it is possible for some variables to have very small negative values. This should be a rare occurrence.

soilzone

- Values of **ssr2gw_rate** specified less than 0.000001 were treated as 0. Now, all **ssr2gw_rate** values > 0.0 are used to compute gravity drainage. In general, specifying parameter values < 0.000001 are going to produce results within or below the limits of floating-point precision, so they will be adding more noise and increased execution time than useful results.

intcp

- Previously, if there was canopy storage at the changeover of a transpiration period (winter to summer or summer to winter) and the canopy could not hold the antecedent water content, this water was added to *net_rain*. This water is now kept track of in variables *intcp_changeover* and *basin_changeover* and added in the same manner as *net_rain* in the *srunoff_smidx* and *srunoff_carea* modules. Overall results don't change, except that *net_rain* is consistent with the total amount of precipitation.

NEW FUNCTIONALITY

dynamic_param_read

- Read and makes available dynamic parameters by HRU from pre-processed files.
- Dynamic parameters include those that specify impervious surface fraction and storage capacity; storage capacity of the capillary and recharge reservoirs of the soil zone; total surface-depression storage and open surface-depression fractions, depth, pervious and impervious surface-runoff capture fraction, and storage threshold for open depressions to spill; canopy type, density, and storage capacity; plant transpiration period; and solar radiation transmission and potential evapotranspiration (ET) computation coefficients.

water_use_read

- Read and makes available water-use data (diversions and gains) from pre-processed files.
- Water can be withdrawn from five sources: (1) stream segment flow, (2) groundwater reservoir storage, (3) open surface-depression storage, (4) external locations, and (5) lake storage. Source water can be transferred to any of eight destinations: (1) stream segments, (2) groundwater reservoir storage, (3) open surface-depression storage, (4) external locations, (5) lake storage, (6) capillary reservoir storage, (7) internal consumptive-use locations, and (8) plant canopy storage. Water transfers can be any source/destination combination. Multiple transfers can originate from each source, and each destination can receive water from multiple sources.
- Modules `intcp`, `soilzone`, `srunoff_smidx`, `srunoff_carea`, `gwflow`, `strmflow_in_out`, `muskingum`, and `muskingum_lake` were modified to account for water-use transfers.

`potet_pm_sta`

- Computes the potential evapotranspiration by using the Penman-Monteith formulation (Penman, 1948; Monteith, 1965) using specified windspeed and humidity in the Data File.

`muskingum_lake`

- Routes water between segments in the system using Muskingum routing and on-channel water body storage and flow routing.

`temp_sta`

- Similar temperature distribution to `temp_1sta` except that no adjustment is made using lapse rates. The value of the associated temperature from a station by parameter `hru_tsta` is adjusted using parameters `tmax_adj` and `tmin_adj`.

`nhru_summary`

- Added output yearly total and mean yearly time series on the basis of control parameter `nhruout_freq` (1 = daily, 2 = monthly, 3 = both, 4 = mean monthly, 5 = mean yearly, 6 = yearly total); daily files have the suffix `.csv`; monthly files have the suffix `_monthly.csv`; mean monthly have the suffix `_meanmonthly.csv`; and mean yearly and yearly total have the suffix `_yearly.csv`.
- Added the option to output of NHM HRU identification number (parameter `nhm_id`) to CSV files when control parameter `nhruOutON_OFF` is specified equal to 2.
- Added the capability to output integer variables in addition to real and double variables.
- Added the option to output using different formats using new control parameter `nhruOut_format` (1 = scientific notation with 4 significant digits (default); 2 = 2 decimal places; 3 = 3 decimal places; 4 = 4 decimal places; 5 = 5 decimal places).
- Parameter `prms_warmup` is now specified in the Control File.

nsub_summary

- Summary output module that operates similar to `nhru_summary` and with similar control parameters, except that it is used to write values of variables dimensioned with **nsub** and variables dimensioned with the value of **nhru** when parameter **hru_subbasin** is specified to separate CSV files at daily, monthly, mean monthly, mean yearly, and yearly total time steps when control parameter **nsubOutON_OFF** is specified equal to 1.
- Added the capability to output integer variables in addition to real and double variables.
- Added the new control parameter **nsubOut_format** for outputting different number formats (1 = scientific notation with 4 significant digits (default); 2 = 2 decimal places; 3 = 3 decimal places; 4 = 4 decimal places; 5 = 5 decimal places).

nsegment_summary

- New summary output module that operates similarly to `nhru_summary` and with similar control parameters except that it is used to write values of variables dimensioned with **nsegment** to separate CSV files at daily, monthly, mean monthly, mean yearly, and yearly total time steps when control parameter **nsegmentOutON_OFF** is specified equal to 1.
- Added the new control parameter **nsegmentOut_format** for outputting different number formats (1 = scientific notation with 4 significant digits (default); 2 = 2 decimal places; 3 = 3 decimal places; 4 = 4 decimal places; 5 = 5 decimal places).

basin_summary

- New summary output module that operates like `nhru_summary`, with similar control parameters, except that it is used to write values of variables dimensioned with **one** to separate CSV Files at daily, monthly, mean monthly, mean yearly, and yearly total time steps when control parameter **basinOutON_OFF** is specified equal to 1.

map_results

- Parameter **prms_warmup** is now specified in the Control File.

potet_pt, potet_pm, and potet_pm_sta

- Allows humidity data to be specified using new parameter **humidity_percent** that has maximum dimensions **nhru** by **nmonths** as an alternative to specifying humidity in a CBH file. Note, previous versions of the `potet_pt` module did not require humidity data.

cascade

- Parameter **hru_segment** can now be used to specify simple one-to-one HRU to stream segment cascade paths instead of specifying all cascade parameters with **cascade_flag** set equal to 2. This option assumes **ncascade = ncascdgw = nhru** and indicates that parameters **hru_up_id, hru_strmseg_down_id, hru_down_id, hru_pct_up, gw_up_id,**

gw_strmseg_down_id, **gw_down_id**, **gw_pct_up**, **cascade_tol**, **cascade_flg**, and **circle_switch** are not specified.

`convert_params`

- Produces an output file of replacement parameters added to facilitate calibration efforts. To activate this module, specify control parameter **model_mode** as **CONVERT** to produce a file of the new parameters (**tmax_allrain_offset**, **soil_rechr_max_frac**, **soil_rechr_init_frac**, **soil_moist_init_frac**, and **ssstor_init_frac**). Similarly, specifying **model_mode** as **CONVERT4** will produce a file of the old parameters (**tmax_allrain**, **soil_rechr_max**, **soil_rechr_init**, **soil_moist_init**, and **ssstor_init**) based on a model using the new parameters.

Temperature modules

- To make a consistent check for valid temperature ranges the constants *MAXTEMP* (value = 200.0) and *MINTEMP* (value = -150) were added to `basin`. Distributed values are compared to these values to determine if they are “valid”. Values outside this range are treated as missing values. Previously, some modules used the range 150.0 to -99.0.

MODULE REMOVED

`strmflow_lake`

- This module (files `strmflow_lake.f90` and `lake_route.f90`) was replaced by the `muskingum_lake` module with all functionality retained in the new module, which includes routing of streamflow using the Muskingum method.

PARAMETER CHANGES

Notes: there are several ways to specify parameters. Traditionally, a single value is specified per line. However, multiple values can be specified per line if fewer than 12,000 characters are specified and there are no trailing blanks. This might be useful to specify a parameter as a grid of values as **ncol, nrow** with the upper left value specified for column 1 row 1 and the bottom right value specified for column **ncol**, row **nrow**. See the section of flexible dimension option described below under release version 4.0.1 for a simplified method of specifying parameters with constant values for any dimension of a parameter.

print_debug

- If specified equal to -2 screen output is very limited and the water budget file specified by control parameter **model_output_file** is not generated and the `basin_sum` module is not used. Thus, all computed variables unique to `basin_sum` are not available.

prms_warmup

- This parameter is now a Control Parameter to allow it to be changed more easily. If specified in the Parameter File, it is ignored. This parameter is used in `nhru_summary`,

`map_results`, `nsub_summary`, `nsegment_summary`, and `basin_summary` to designate a portion of a simulation to not include in the output file(s) for these modules.

gw_seep_coef

- The dimension is now **ngw** instead of **nlake**.

humidity_percent

- This new parameter can be used as an alternative to specification of humidity in a CBH file for modules `potet_pt`, `potet_pm`, and `potet_pm_sta`. It has maximum dimensions **nhru** by **nmonths**.

obsout_segment

- This new parameter is used to specify a replacement flow for outflow of a segment. This is like **obsin_segment** that can be used to specify a replacement flow for the inflow to a segment. Both parameters can be used with modules `strmflow_in_out`, `muskingum`, and `muskingum_lake`, which are available in PRMS or PRMS5 simulation modes. Replacement flows are specified in the Data File and used to assign measured flows to segments instead of the simulated flow. Use of replacement flows breaks conservation of mass but might be useful to set flows below a managed water body.

segment_type

- Specifies type of segment (0 = normal; 1 = headwater; 2 = lake; 3 = replacement flow; 4 = inbound to nation; 5 = outbound from nation; 6 = inbound to region; 7 = outbound from region; 8 = drains to ocean; 9 = sink (terminus to soil); 10 = inbound from Great Lakes; 11 = outbound to Great Lakes; 12 = ephemeral; + 100 user updated; 1000 user virtual segment 100 = user normal; 101 - 108 = not used; 109 sink. This parameter can be used with modules `strmflow_in_out`, `muskingum`, and `muskingum_lake`, with the sole purpose of accumulating total flows for each segment type.

Parameters used when `model_mode = PRMS5`

| | |
|-----------------------------|---|
| tmax_allrain_offset | Equals old parameter <code>tmax_allrain</code> – <code>tmax_allsnow</code> |
| soil_rechr_max_frac | Equals old parameter <code>soil_rechr_max</code> / <code>soil_moist_max</code> |
| soil_rechr_init_frac | Equals old parameter <code>soil_rechr_init</code> / <code>soil_rechr_max</code> |
| soil_moist_init_frac | Equals old parameter <code>soil_moist_init</code> / <code>soil_moist_max</code> |
| ssstor_init_frac | Equals old parameter <code>ssstor_init</code> / <code>sat_threshold</code> |
| sro_to_dprst_perv | Equals old parameter <code>sro_to_dprst</code> |
| dprst_frac | Equals old parameter <code>dprst_frac_hru</code> |

Parameters used when model_mode = PRMS

| | |
|--|---|
| tmax_allrain | Replaced by tmax_allrain_offset |
| soil_rechr_max | Replaced by soil_rechr_max_frac |
| soil_rechr_init | Replaced by soil_rechr_init_frac |
| soil_moist_init | Replaced by soil_moist_init_frac |
| ssstor_init_init | Replaced by soil_moist_init_frac |
| sro_to_dprst | Name change to sro_to_dprst_perv |
| dprst_area or dprst_frac_hru | Replaced by dprst_frac |

NEW VARIABLES

strmflow_in_out, muskingum, and muskingum_lake

- Added support for additional segment types using the parameter **segment_type** that provides output by category. These are *flow_to_lakes*, *flow_to_ocean*, *flow_to_great_lakes*, *flow_out_region*, *flow_out_NHM*, *flow_in_region*, *flow_terminus*, *flow_in_nation*, *flow_headwater*, *flow_in_great_lakes*, *flow_replacement*.

intcp

- *intcp_changeover* and *basin_changeover*

REMOVED VARIABLES

- *cascade_interflow*, *cascade_dunnianflow*, *interflow_max*, *cpr_stor_frac*, *pfr_stor_frac*, *gvr_stor_frac*, *soil_moist_frac*, *soil_rechr_ratio*, *snowevap_aet_frac*, *perv_avail_et*, and *cap_upflow_max*.

SMALL CHANGES THAT DO NOT AFFECT ANY COMPUTATIONS

Determination of Muskingum routing variables moved from source file `muskingum.f90` to `routing.f90` so that the `muskingum` and `muskingum_lake` modules could share the same code.

PRMS UTILITIES

- If an error is encountered reading a Parameter File an error message is issued and the file is no longer read instead of trying to continue reading the file.
- The delimiter between specification of multiple values on a line in a Parameter File was changed from a comma to a space. Trailing blanks cannot be specified on a line as this produces a read error.
- The end of a line for parameter values is determined by either a new line or null character instead of just a new line.
- Possible security issues addressed related mostly to buffer overflow and underflow.

=====

Version 4.0.3 – May 05, 2017

This release corrected major bugs in the `potet_pm` and `potet_pt` modules and minor bugs in the `soilzone` and `gwflow` modules. Screen and Model Output File output updated for readability and output of additional information. See the updated tables for updates to parameters, variables, modules, and dimensions at:

ftp://brrftp.cr.usgs.gov/pub/mows/software/prms/4.0.3/PRMS_tableUpdates_4.0.3.pdf

BUG FIXES – by module:

snowcomp

- When a snowpack is melting and there is a new snowfall, the code is supposed to save the point on the depletion curve (variable `snowcov_areasv`) and then deplete the snowpack from `snarea_curve(11,k)` over the subsequent time steps until the snow covered area is less than or equal to `snowcov_areasv` on the basis of linear interpolation. See Figure 1-4, page 97 of the PRMS-IV documentation report (TM6-B7, Markstrom and others, 2015) for a depiction of how the code was supposed to compute snow-water equivalent (SWE) using a depletion curve after a secondary snowfall. However, `snowcov_areasv` was set to `snarea_curve(11,k)`, the maximum value of a snow depletion curve. This fix can change results of the snowpack depletion for secondary snowfalls as depletion begins at the maximum value of the depletion curve instead of returning to the point of departure from the depletion curve from which it was melting prior to the snowfall. Thus, there will be no change for many snowpacks, but, noticeable change to results for some. Variable `frac_swe` was not computed for all time steps, this was corrected, and the variables was changed to single precision; this change did not affect other computations.

potet_pt

- The computation of the net long wave radiation was corrected.

potet_pm

- The computation of the net long wave and net radiation coefficients used to compute potential ET were corrected.

srunoff

- The computation of pervious and impervious capture of pervious and impervious surface runoff into depressions did not account for the fraction of pervious and impervious to compute actual inflow, which lead to the possibility of excess water to the stream network.

muskingum

- If **K_coef** was set < 1.0, it was possible to get a divide by 0 under rare conditions, this was corrected.

temp_dist2

- Values for parameter **tmax_adj** and **tmin_adj** were not read from the Parameter File and were likely set to zero or very small values.

soilzone

- Changed declared dimensions from **nhru** to **one** for variables *basin_cpr_stor_frac*, *basin_gvr_stor_frac*, *basin_pfr_stor_frac*, *basin_soil_lower_stor_frac*, *basin_soil_rechr_stor_frac*, and *basin_sz_stor_frac*. This change does not affect any computations but could cause unpredictable results for output of these variables in statvar and animation files and runtime graphs.
- Computation of *basin_pfr_stor_frac* was computed incorrectly using *pref_flow_stor* instead of *pfr_stor_frac*. This does not affect any other computations.

gwflow

- The determination of whether to add storage on the basis of the value of **gwstor_minarea** is done after adding recharge instead of before.

basin

- If an HRU had open and closed surface-depression storage portions, computations were incorrect; this was corrected.

SMALL CHANGES THAT DO NOT AFFECT ANY COMPUTATIONS

call_modules

- Updated output to screen and to the model output file for improved readability and added output of the Parameter File name.

cascade

- Removed checks for specification of farfield flow as farfield computations are no longer supported.

subbasin

- Changed units in variable descriptions for *subinc_wb* and *subinc_deltastor* from cfs to inches.

map_results

- Messages for incomplete or excess accounting for mapping between HRU map and target map includes more information.

basin

- Summary statistics for areal portions and date and times reformatted.

NEW FUNCTIONALITY

nhru_summary

- Added output yearly total and mean yearly time series on the basis of control parameter **nhruout_freq** (1 = daily, 2 = monthly, 3 = both, 4 = mean monthly, 5 = mean yearly, 6 = yearly total); daily files have the suffix `.csv`; monthly files have the suffix `_monthly.csv`; mean monthly have the suffix `_meanmonthly.csv`; and mean yearly and yearly total have the suffix `_yearly.csv`.

NEW VARIABLES

- Added variable *basin_swrad*, which is set equal to *basin_potsw*. This change impacts modules *ccsolrad*, *ddsolrad*, *climate_hru*, and *climateflow*.
- Added subbasin variables: *subinc_rain*, *subinc_snow*, *subinc_stor*, *subinc_recharge*, *subinc_szstor_frac*, and *subinc_capstor_frac*.
- Added *basin_sum* variables: *basin_swrad_yr*, *basin_swrad_tot*, and *basin_swrad_mo*, which are added to summaries in the **model_output_file** on the basis of selected print options.

Version 4.0.2 – July 29, 2016

This release added new parameters and variables, corrected bugs, added more checks for valid input values, included general code clean up, mostly to reduce mixed floating-point computations by changing some variables to double precision, some to single precision, and added FORTRAN intrinsic functions to convert variables prior to mixed-precision computations. Additional information about input and output files and simulation period are printed to the screen. See the updated tables for updates to parameters, variables, modules, and dimensions at:

ftp://brrftp.cr.usgs.gov/pub/mows/software/prms/4.0.2/PRMS_tableUpdates_4.0.2.pdf

BUG FIXES

potet_pt

- The code incorrectly used the value of the average HRU air temperature in degrees Fahrenheit when it was supposed to be in degrees Celsius in one equation. The equation is correct in the PRMS-IV documentation report.

potet_pm

- The equation is different from the PRMS-IV documentation report.

potet_hs

- The kt coefficient was first being computed each day using an equation based on average temperature as described in https://www.zohrabsamani.com/research_material/files/Hargreaves-samani.pdf. Then this value was multiplied by the **hs_krs** parameter. Now, only the **hs_krs** parameter is used in the Hargreaves-Samani equation, which matches the PRMS-IV documentation. The kt coefficient equation can be used to estimate the **hs_krs** parameter: $coef_kt = 0.00185*(temp_dif**2) - 0.0433*temp_dif + 0.4023$, where *temp_dif* is the difference between the HRU maximum and minimum temperature in units of degrees Celsius.

precip_laps

- Arrays for parameters **rain_adj_lapse** and **snow_adj_lapse** were not allocated causing application to fail.

routing

- Variables *seginc_potet*, *seginc_gwflow*, *seginc_ssflow*, *seginc_sroff*, *seginc_swrad*, *seg_gwflow*, *seg_ssflow*, and *seg_sroff* were computed if the cascading flow option was active, which was an error if parameter **hru_segment** was not specified. These variables are not computed if the cascading flow option is active.
- The value of *seg_lateral_inflow* was not set correctly when the cascading flow option was active; it is now set to *strm_seg_in*.

subbasin

- Subbasin storage did not include surface-depression or lake storage.

climate_hru

- Variable *basin_obs_ppt* was set to 0.0 if precipitation values are not input in a CBH file; thus, an error occurred if parameter **precip_module** was not specified equal to *climate_hru*.

map_results

- Yearly output was not computed when parameter **mapvars_freq** = 5.
- Corrected IF blocks that determine whether or not parameters **gvr_cell_pct** and **gvr_hru_id** were needed; **gvr_cell_pct** needed when **nhrucell** not equal **ngwcell** and **gvr_hru_id** needed when **nhru** not equal **nhrucell**.

gwflow

- Variable *basin_lake_seepage* was computed incorrectly by using incorrect values of **hru_area**.

basin_sum

- The value of the yearly observed streamflow or monthly value of computed basin streamflow and monthly observed streamflow was not printed for **print_type** = 2.
- Detailed output did not have the right line length, thus missing a value.
- Yearly detailed output now includes evaporation for lakes and interception storage.

ide_dist

- Computations of inverse distance and elevation allowed to be less than 0 for precipitation computations so that they are consistent with computations for temperature computations.

srunoff_smidx and srunoff_carea

- Variable *contrib_fraction* was declared as dimension **one** and data type double when it should be dimension **nhru** and data type single. This error could have caused memory problems if the variable was output in a Statistics Variable (statvar) or Animation File, or using the PRMS GUI runtime plots, but would not affect any computations.

soilzone

- Computation of variable *soil_lower_ratio* was set incorrectly to *soil_moist/soil_moist_max* instead of *soil_lower/soil_lower_stor_max* and values of *soil_lower_ratio* for lake and inactive HRUs were not initialized to 0. No other computations are affected.
- In the `compute_soilmoist` routine, the check for infiltration water in excess of **soil_moist_max** minus *soil_to_gw* (local variable *excs*) was $> infil$ should have been a check for $excs > infil * perv_frac$ as *excs* is computed for the whole HRU area and *infil* for only the pervious area on an HRU; this condition was not likely to have occurred.
- Make sure any flow from gravity to preferential-flow reservoirs is set to 0 or current value (previous versions could have used value from previous HRU if current HRU in loop does not have preferential flow reservoir).

basin

- Corrected code to ensure a divide by zero is not permitted for the condition that there are closed depressions but not open depressions; that is, if any values for parameter **dprst_frac_open** are specified = 0.
- If the first value of parameter **dprst_area** was specified < 0 or not included in the Parameter File, the values of **dprst_frac_hru** (default value = 0) were ignored if specified. Thus, if **dprst_frac_hru** was not included in the Parameter File no surface-depression storage would be simulated; this check should have been reversed. Use of parameter **dprst_area** is now deprecated, so users should now use **dprst_frac_hru** and specify values ≥ 0 . The default value of **dprst_frac_hru** is now -1.0.

snowcomp

- Added check to be sure *snowcov_area* is not equal to zero when *pkwater_equiv* is greater than 0. This would be very rare and only possible when the second value of a snow-depletion curve was specified equal to zero.
- Checks were added to be sure *pkwater_equiv* is set to 0.0 if it is computed as a very small negative value, which would be very rare.
- Added check for when *pkwater_equiv* < 1.0E-10 and *snowcov_area* > 0; if true, set *snowcov_area* to 0. This is possible when the energy is enough to melt the snowpack on the previous time step. This bug affected computations for impervious and surface-depression storage evaporation for days without snow and snow depletion curves that specified snow-covered area exists when the snow-water equivalent is equal 0.
- In `calin` function, *snowcov_area* was set to 0 when it should not be because it is the snow cover after adding precipitation and before any melt or sublimation; this condition affects computations for impervious and surface-depression storage evaporation for days with snow.
- If snowpack exists and the snowpack density (*pk_den*) <= 0, be sure *pk_den* and the snowpack depth (*pk_depth*) have a value based on parameter **den_max** in `run` function and `calin` function; this condition would be rare.
- In routine `calin`, added check for the value of *freeh2o - pwcap* > *pkwater_equiv*; if so, use the value of *pkwater_equiv*. This condition would be rare.
- In routine `calin`, the local variable *apk_ice* did not have a value if *snowcov_area* <= 0; if true, it is set to 0. This condition would be rare.

`water_balance`

- Full array for *hru_sroffp* and *hru_sroffi* instead of HRU value printed for water-budget issue for **srunoff** with cascades active.
- Variable *soil_to_ssr* was not included in HRU **soilzone** water-budget computation. This variable is needed because the variable *cap_waterin*, actual water into capillary reservoir, replaced *cap_water_maxin*, the maximum potential water into the capillary reservoir.

UPDATES THAT MIGHT PRODUCE SLIGHT CHANGES IN ASSOCIATED COMPUTATIONS – general:

- Some single-precision variables were changed to double-precision variables and vice versa; also, most modules now use FORTRAN intrinsic functions to explicitly designate mixed-precision computations. These changes are intended to limit the possibilities of different results on different computers and compilers, to provide more consistent floating-point comparisons, and to have more consistent round-off issues. These updates could change memory requirements and execution time very slightly. Modules affected: `obs`, `cascade`, `ccsolrad`, `ddsolrad`, `climate_hru`, `temp_dist2`, `precip_dist2`, `ide_dist`, `xyz_dist`, `potet_hamon`, `intcp`, `snowcomp`,

`srunoff_smidx`, `srunoff_carea`, `soilzone`, `gwflow`, `routing`, `water_balance`, `nhru_summary`, `map_results`, `prms_summary`, `subbasin`, `climateflow`, and `basin`.

- Small values (>0.0 and $< 1.0E-05$) of precipitation are used in computations; previously these values were assumed to be below round-off tolerance and set to 0. This affects modules `obs`, `precip_1sta`, `climate_hru`, `ide_dist`, `xyz_dist2`, and `precip_laps`.
- Small values (>0.0 and $< 1.0E-06$) of computed potential evapotranspiration were considered to be round-off error and set to 0; now those values are used in computations. This change affects modules `potet_hamon`, `potet_hs`, `potet_jh`, `potet_pan`, `potet_pm`, and `potet_pt`.
- `climateflow` module: Small values (>0.0 and $< 1.0E-06$) of computed mixed precipitation were considered to be round-off error and the event was set to all snow or all rain depending on the precipitation form, now those values are used in computations.
- Computation of saturation vapor pressure for module `potet_pm` now uses an equation by Irmak and others (2012; Journal of Hydrology, v. 420-421, p. 228), to be consistent with module `potet_pt`. This can reduce execution time.
- Small values (>0.0 and $< 1.0E-04$) specified for `hru_percent_imperv` and `dprst_area` are used in computations; previously these values were assumed to be below round-off tolerance and set to zero.
- Values of canopy interception computed between 0.0 and $1.0E-05$ were considered to be round-off error and set to 0.0; these values are now left in the canopy. Module affected: `intcp`.
- Double precision values $< 1.0D-15$ are treated as zero instead of $< 1.0D-10$.
- Module `cascade`: changed check for excess GWR cascade fraction so that any values > 1 set to 1 instead of only > 1.00001 . This change makes the check consistent with the HRU cascade fraction check.
- Module `snowcomp`:
 - instead of using $< -1.0E-10$ to check for round-off issues in some computations, < 0.0 is now used. Instead of using $> 1.0E-06$ to check for round-off issues in some places, $> 1.0E-09$ is now used.
 - values of snowpack water equivalent (`pkwater_equiv`) computed between 0.0 and $1.0E-09$ were considered to be round-off error and set to 0.0; these values are now used.
 - Values < 0.0 are set to 0.0 with a warning message printed when control parameter `print_debug` > -1 . This condition accounts for negative round-off error due to mixed precision computations and may occur under rare conditions.

NEW FUNCTIONALITY

The values of all parameters specified in the Parameter File are now checked to determine if they fall within the suggested minimum and maximum range. If values are specified outside the range, a warning message is issued. If the user wants to specify values out of the range, set control parameter **parameter_check_flag** = 0 to deactivate these checks. Previously, select parameters were checked within individual modules.

nhru_summary

- Added functionality to output monthly and mean monthly time series based on the value of new control parameter **nhruout_freq** (1 = daily, 2 = monthly, 3 = both, 4 = mean monthly), daily files have the suffix `.csv`; monthly files have the suffix `_monthly.csv`, and mean monthly have the suffix `_meanmonthly.csv`.

gwflow and cascade

- Added option to allow GWRs to be swales with new control parameter **gwr_swale_flag** (0 = not allowed; 1 = groundwater flow routed to groundwater sink; 2 = groundwater flow routed to stream network).

cascade

- Allow groundwater-reservoir cascades to be equal to HRU cascades with **cascadegw_flag** = 2.

call_modules

- Specification of control parameter **print_debug** = -1 reduces amount of screen output.

ccsolrad

- Removed restart subroutine so `ccsolrad` can be used in a restart simulation if `ddsolrad` was used for the antecedent simulation. The switch from `ddsolrad` to `ccsolrad` is still allowed.

snowcomp

- Code added to initialize snow states based on **snowpack_init** and related parameters in the “init” procedure.

water_balance

- Code related to GSFLOW removed.

basin_sum

- Labeled first value of reports as initial storage.
- Added print of water balance values to reports when **print_type** = 1
- Added print of *basin_intcp_stor* and *basin_lakeevap_yr* to yearly report when **print_type** = 2

map_results

- Stop if negative mapping fraction specified.
- Allow values > 0.0 and 1.0E-06 for parameter **gvr_cell_pct** instead of treating them as 0.0.

MODULES REMOVED

check_nhru_params code for module moved to function in file `utils_prms.f90` that is called within `call_modules`.

cloud_cover code returned to module `ccsolrad`.

INPUT SPECIFICATION CHANGES:

obs and climate_hru Values in Data File or CBH File are not checked for being specified as not a number (NaN), thus user must ensure such values are not specified.

climate_hru Precipitation values specified in CBH Files less than 0.0 are flagged as an ERROR.

precip_dist2 Values specified for parameter **psta_mon** less than or equal to 0 are flagged as an ERROR.

OUTPUT FILE REMOVED

The `prms.log` file is not generated as it is redundant with information written to the model output file. The log was present to produce a similar file as output by GSFLOW and included description and version of PRMS and modules.

=====

Version 4.0.1 – March 11, 2015

This release added new functionality, parameters, and variables, fixed bugs, added more checks for valid input values, general code clean up. The primary change is the addition of the flexible dimension option described below that allows flexibility for specification the spatial and temporal distribution of parameter values.

NEW MODULES (code taken mostly from existing modules)

potet_pm Penman-Monteith potential evapotranspiration computation and distribution module, activated using control parameter **et_module**.

check_nhru_params select **nhru**-dimensioned parameter values are checked to see if specified values are within the suggested range.

prms_time module for time related computations, such as current time step, Julian day, and whether in summer or winter.

`routing` computes variables used by stream flow modules, such as code related to fluxes associated with each segment.

`lake_route` reads most lake related dimensions, parameters, and computes some of variables used with lake computation modules.

`water_balance` debug module that checks that water balances are maintained for the overall water budget, soil-zone computations, canopy interception computations, snow computations, surface runoff and impervious computations, and groundwater computations. Active when **print_debug** is specified equal to 1.

`nhru_summary` produces output files of daily computed results for user-selected **nhru**-dimensioned variables in a CSV format. Results for each selected variable are written to a separate file.

GENERAL

- Initialize procedure is completed prior to stopping for input parameter range errors. Previously, the simulation would stop after finding the first invalid parameter value. Thus, more invalid values can be caught in a single execution. This is activated using new control parameter **parameter_check_flag**, which is described below.
- Updated many parameter and variable descriptions to be consistent with PRMS documentation manual.
- Initialize procedure is completed prior to stopping for input parameter range errors. Previously, the simulation would stop after finding the first invalid parameter value. Thus, more invalid values can be caught in a single execution. This is activated using new control parameter **parameter_check_flag**, which is described below.
- Updated many parameter and variable descriptions to be consistent with PRMS users' manual.
- Use of initial conditions options (activated using control parameters **init_vars_from_file** and **save_vars_to_file**) does not write parameter values to the Initial Condition File. Parameter values specified in the Parameter File are read and used in a restart simulation. Storage initialization parameter values, parameters **soil_moist_init**, **soil_rechr_init**, **snowpack_init**, **ssstor_init**, and **gwstor_init**, are ignored in a restart simulation. Writing to and reading from Initial Conditions Files are removed from modules `potet_hamon`, `transp_frost`, `potet_jh`, `smbal_prms`, `ssflow_prms`, `soltab`, `precip_dist2`, `hru_sum_prms`, `ccsolrad`, `ddsolrad`, `precip_1sta_laps`, `prms_summary`, `subbasin`, `basin`, `cascade`, and `map_results`. Thus, these modules do not have to be active in a restart simulation if active in a spin-up (or antecedent) simulation, except for `basin`, which is always active.

- New variable (*IGNOREPPT*=1.0E-5) added. It is used to check for values of measured or computed precipitation values that are considered too small to be actual precipitation. If a precipitation value is less than *IGNOREPPT* the value is set to 0.0.
- New variable (*SMALLPARAM*=1.0E-4) added. It is used to check a few parameter values for being too small to be used and thus set to 0 a warning message is printed if **parameter_check_flag** specified equal to 0. Parameters checked include **pmn_mo**, **psta_mon**, and **lake_coef**. An error message is issued, and execution stops if control parameter **parameter_check_flag** is specified equal to 1 for this check.
- Code related to computations of far field flows (flow leaving the model domain boundary not through the stream network) was removed. Adding an extra stream segment to send flow outside the domain is the recommended replacement.

NEW FUNCTIONALITY ADDED TO MODULES

Flexible dimension option: Previously, parameters had only one option for the number of values (dimension(s)) specified in the Parameter File. Now, many parameters can be specified using the original dimension(s) or using compatible dimensions up to a maximum number of values based on the specified dimension(s). For example, some parameters having dimension of **nmonths** now have a maximum dimension of **nhru,nmonths**. Flexible dimensions for a parameter with a maximum dimension of **nhru,nmonths** are **one**, **nmonths**, **nsub**, **nsub,nmonths**, **nhru**, and **nhru,nmonths**. Flexible dimensions for a parameter with a maximum dimension of **nhru** are **one**, **nsub**, and **nhru**. Flexible dimensions for a parameter with a maximum dimension of **nssr** are **one**, **nsub**, and **nssr**. Flexible dimensions for a parameter with a maximum dimension of **ngw** are **one**, **nsub**, and **ngw**. PRMS will read the dimension, number of values, and values from the Parameter File. If the parameter is not specified at the maximum dimension, the parameter values will be automatically expanded to the maximum dimension by the code. Thus, the user has several options to specify the number of parameter values based on the spatial and temporal variability, available data, or for some other purpose. The maximum number of values for most parameters has not changed. Maximum parameter dimensions are identified in PRMS-IV updated tables 1-1 and 1-3 (ftp://brrftp.cr.usgs.gov/pub/mows/software/prms/4.0.1/PRMS_tableUpdates_4.0.1.pdf). The flexible dimension option was added to accommodate simulation of large model domains that required increased spatial and/or temporal distribution of parameter values. Additionally, the number of lines in Parameter Files can be significantly reduced by specifying a single (dimension **one**) or **nsub** values for parameters that have a constant value for all HRUs or subbasins. This capability may change results when dimensions are specified greater than the original dimension(s). If the parameter dimensions are not changed, results should be the same. However, some computations in *ddsolrad* and *ccsolrad* are based on variables for each HRU rather than basin-wide variables, so the potential solar radiation (variable *swrad*) can be significantly different than previous versions for large model domains.

Parameters affected with maximum dimension indicated are: **hamon_coef(nhru,12)** in module `potet_hamon`, **jh_coef(nhru,12)** in module `potet_jh`, **radadj_intcp(nhru,12)**, **radadj_slope(nhru,12)**, **dday_intcp(nhru,12)**, **dday_slope(nhru,12)**, **tmax_index(nhru,12)**, and **radmax(nhru,12)** in module `ddsolrad`, **radadj_sppt(nhru)**, **radaj_wppt(nhru)**, **ppt_rad_adj(nhru,12)**, **crad_coef(nhru,12)**, **crad_exp(nhru,12)**, and **radmax(nhru,12)** in module `ddsolrad`, **epan_coef(nhru,12)** in modules `potet_pan` and `intcp`, **potet_sublim(nhru)** in modules `snowcomp` and `intcp`, **frost_temp(nhru)** in module `frost_date`, **tmax_lapse(nhru,12)** and **tmin_lapse(nhru,12)** in module `temp_laps`, **tmax_adj(nhru,12)** and **tmin_adj(nhru,12)** in modules `temp_1sta`, `temp_dist2`, `ide_dist`, `xyz_dist2` and `temp_laps`, **tmax_allrain(nhru,12)**, **tmax_allsnow(nhru,12)**, and **adjmix_rain(nhru,12)** in modules `precip_1sta`, `precip_dist2`, `climate_hru`, `ide_dist`, `xyz_dist` and `precip_laps`, **adjust_snow(nhru,12)** and **adjust_rain(nhru,12)** in modules `ide_dist` and `xyz_dist` **melt_look(nhru)**, **melt_force(nhru)**, **tstorm_mo(nhru,12)**, **cecn_coef(nhru,12)**, **emis_noppt(nhru,12)**, and **freeh2o_cap(nhru,12)** in module `snowcomp`

Parameters **adj_by_hru**, **hru_subbasin**, **rain_sub_adj**, and **snow_sub_adj** that were specified for module `climate_hru` were removed as the flexible dimension option makes these unnecessary. **rain_adj** and **snow_adj** can have the dimensions (**nsub,nmonths**), so are used instead of **rain_sub_adj**, and **snow_sub_adj**. Parameter **hru_subbasin** is required if module `subbasin` is active.

An example of parameter with a maximum number of values equal to **nhru** that might have the same value for all HRUs is **carea_max**. In this case, values for each HRU can be specified to the default value as:

```
####
carea_max
1
one
2
0.6
```

map_results added option to output daily mapped results (parameter **mapvars_freq** specified equal to 7). Notes: the units of output variables are equal to the units of the variable for **mapvars_units** specified equal to 0. Units for variables could be, for example, inches, inches/day, degrees Fahrenheit, and degrees Celsius. However, when the **mapvars_units'** value is specified greater than 0, the units of all selected **map_results** output variables as specified by control parameter **mapOutVar_names** must have units of either inches or inches/day as the code only converts inches to a metric unit.

climate_hru CBH files can be input as binary files with the identical information when new control parameter **cbh_binary_flag** specified equal to 1. Humidity and wind speed

data can be input as CBH files. Potential ET can be adjusted from values input in CBH files using new parameter **potet_cbh_adj**.

strmflo_w_lake the order of stream segments and lakes was specified by parameters input to the `cascade` module with **wtrbdy** prefix-named parameters. The module now uses the same parameters as other stream network routing modules, that is, **tosegment**, **hru_segment**, and **obsin_segment**. This change requires that each lake includes a stream segment as well as being specified as a lake HRU. A segment within a lake is specified using **segment_type**.

obs and **call_modules** store dimension values in Initial Conditions Files for a spin-up simulation and are checked to be sure they are equal to the dimensions for a restart simulation.

prms_summary added output of the first value of the variable *streamflow_cfs* array to the CSV file (control parameter **csvON_OFF** specified equal to 1); if the value of dimension **nobs** is specified equal to 0, then the value 0.0 is output for *streamflow_cfs*.

NEW PARAMETERS

Parameters specified in the Control File

parameter_check_flag 0 means treat some parameter range checks as WARNINGS as done for most parameters in previous versions, if specified as 1 these checks are treated as ERRORS, if specified as 2 the parameters are checked and then the simulation stops even if no ERRORS, default = 1.

cbh_check_flag 0 means do not check values in CBH file; 1 means to check for invalid values, such as NaN, character strings, < lower bound, and > upper bound, plus end of file during a simulation and non-sequential time series, such as not having the correct number of days in each year, default = 1. Specifying **cbh_check_flag** equal to 0 should only be done after the CBH file(s) are verified using **cbh_check_flag** specified equal to 1. Setting **cbh_check_flag** equal to 0 can reduce execution time.

cbh_binary_flag 0 means CBH files are text files as in the past; 1 means the CBH files are in binary format with same order of values as text file version.

nhruOutVar_names array of variable names to write to CSV files each day.

nhruOutBaseFileName string to define the prefix for each output file for the `nhru_summary` module, one for each variable; this can be a full or relative path.

nhruOutON_OFF flag to activate `nhru_summary` module (0 means do not use module; 1 activates module, default = 0).

nhruOutVars number of output variables, i.e., the number of variable names specified using **nhruOutVars_names**.

csv_output_file pathname of output file written by the `prms_summary` module.

csvON_OFF flag to activate the `prms_summary` module (0 means do not use module; 1 activate module, default = 0).

humidity_cbh_flag flag to specify to read a CBH file with humidity values (0 = no; 1 =yes, default = 0).

humidity_day file name of the humidity CBH file; this can be a full or relative path.

windspeed_cbh_flag flag to specify to read a CBH file with wind speed values (0 = no; 1 = yes, default = 0).

windspeed_day file name of the wind speed CBH file; this can be a full or relative path.

print_debug: new option (**print_debug** specified equal to -1) added to this existing parameter that minimizes warning messages and other messages printed to the screen during a simulation, such as when values of variables `slow_stor` are computed greater than `pref_flow_thrsh`. This can increase execution efficiency.

Parameters specified in the Parameter File(s)

dprst_et_coef(nhru): surface-depression evaporation adjustment factor, range 0.0 to 1.0, default = 1.0.

sro_to_dprst_imperv(nhru): impervious surface runoff fraction captured by surface depressions within each HRU. Related parameter **sro_to_dprst(nhru)** is pervious surface runoff capture fraction captured by surface depressions within each HRU, range 0.0 to 1.0, default = 0.2.

segment_flow_init(nsegment): initial flow rate in each segment, in cfs, range 0.0 to 1.0E07, default = 0.0.

segment_type(nsegment): Segment type 0 = segment; 1 = diversion; 2 = lake; 3 = replace inflow, default = 0.

hs_krs(nhru,nmonths): calibration coefficient for module `potet_hs`; replaces removed parameter **potet_coef_hru_mo(nhru,nmonths)**, range 0.005 to 0.06, default = 0.0135.

pt_alpha(nhru,nmonths): calibration coefficient for module `potet_pt`; replaces removed parameter **potet_coef_hru_mo(nhru,nmonths)**, range 1.0 to 2.0, default = 1.26.

potet_cbh_adj(nhru,nmonths): calibration coefficient for values specified in a **potet_day** CBH file, range 0.5 to 1.5, default = 1.0.

snowpack_init(nhru): initial snowpack-water equivalent, in inches, range 0.0 to 500.0, default = 0.0.

NEW COMPUTED VARIABLES (available depending on which computation options are active):

canopy_covden(nhru): current value of cover density fraction for each HRU based on whether HRU is in transpiration mode.

hru_intcpevap(nhru): canopy evaporation for each HRU, in inches.

hru_storage(**nhru**): sum of all storage for all water-holding reservoir for each HRU, in inches.

lake_seepage_gwr(**nhru**): the seepage from lakes to each GWR in units of inches.

gw_seep_lakein(**nhru**): dimensioned changed from **nhru** to **nlake**, in inches.

dprst_stor_hru(**nhru**): average surface depression storage for each HRU, in inches.

basin_contrib_fraction: basin-area weighted average contributing area fraction of pervious area.

contrib_fraction(**nhru**): contributing area fraction of the pervious area of each HRU.

basin_lake_stor: basin-area weighted average precipitation into all lakes, in inches.

basin_lakeevap: basin-area weighted average evaporation from all lakes, in inches.

unused_potet(**nhru**): unsatisfied potential evapotranspiration after all ET computations, in inches.

basin_segment_storage: basin-area weighted average total storage in each segment, in inches.

segment_delta_flow(**nsegment**): cumulative difference of flow into minus outflow for each stream segment, in cfs.

seginc_potet(**nsegment**): potential ET associated with each segment, in inches.

lake_inflow(**nlake**): total inflow into each lake, in cfs.

lake_outflow(**nlake**): total evaporation and seepage from each lake, in cfs.

lake_lateral_inflow(**nlake**): total lateral flow into each lake, in cfs.

hru_streamflow_out(**nhru**): total flow to stream network for each HRU, in cfs.

hru_hortn_cascflow(**nhru**): name change for variable *hru_hortonian_cascadeflow*, in inches.

snowdepth(**nsnow**): name change of variable *snow*, in inches.

lake_outcfs(**nsegment**): name change of variable *lake_outq*, in cfs.

BUG FIXES

snowcomp: Computation of snowpack density and snowpack depth are computed based on a finite difference approximation, which produced slightly incorrect results for days when new snow falls when a snowpack does not exist. This bug could produce significant error when the new snow fall is large compared to the existing snowpack. There was the possibility that the snowpack water equivalent was computed as a value < 0 when the amount of free water was less than the computed amount of free water that the snowpack could hold. Though this condition is likely very rare, it could have resulted in very slight differences in results in the value of variables *pkwater_equiv*, *pk_depth*, and *snowmelt*.

`ide_dist` and `xyz_dist`: measured precipitation values were modified from those in the Data File, thus output values in runtime graphs or files could be different than those in the Data File; a local array is used instead.

`basin_sum`: water balance computations did not include water in stream segments when using Muskingum flow routing or surface depression storage, if any. Water balance computations are only computed when control parameter **print_debug** = 1. Used variable `basin_stflow_in` instead of `basin_stflow_out` to set the basin outflow variable `basin_cfs`, this bug only occurred when the `muskingum` module was active.

`basin`: The contributing area to each stream segment was computed incorrectly for some cases. Error check added for specification of any **tosegment** value equal to that segment, if this were done the code would go into an infinite loop. Checks added for valid values of **tosegment**; error if **> nsegment**, **< 0**, or equal to the segment id. Setting of local variable `hru_elev_feet` was not set when parameter **elev_units** was specified as 1; this only affected computations when module `potet_pt` is active. Print of fraction of impervious, pervious, and depression storage were labeled as area instead of as fractions of the active basin area.

`gwflow`: Values of parameter **gwflow_coef** specified less than 1.0 are allowed and if specified **> 1.0** a warning is issued. Any water added due to specified values of parameter **gwstor_min** was added twice. Error message for the condition that an HRU is specified as a lake and the associated value of parameter **lake_hru_id** is specified equal to 0, printed the incorrect GWR Identification number. If groundwater discharge to a lake was computed greater than the available groundwater storage, the value was not limited by the available storage; now the discharge is set to the available groundwater storage and a warning message is issued. Computation of lake seepage was removed from the initialize procedure, so the initial lake elevation and storage is based only on input parameters instead of after lake elevation and groundwater discharge computations as computed in the run procedure. Warning checks of parameters used incorrect array index. If any HRUs were specified as inactive then the last number of inactive HRUs values were not checked. Seepage from lakes used the incorrect array index, thus, was set incorrectly. `basin_lake_seep` was divided by the total active area of the model domain twice; thus the value was incorrect.

`soilzone`: Error check added for interflow computation of the equation $\text{SQRT}(\text{coef_lin}^{**2.0} + 4.0 * \text{coef_sq} * \text{ssres_in}) = 0.0$, if true a divide by 0 would have occurred, this would be a very rare condition. Corrected setting of variable `soil_zone_max` to account for parameter **soil_moist_max** only being applicable to the pervious area of each HRU, this does not affect other soilzone computations, just the values of variables `soil_zone_max` and `soil_moist_frac`, which are computed results that are not used in other computations. Water balance check when control parameter **print_debug** = 1 was incorrect when swale HRUs are present.

`ccsolrad`, `ddsolrad`, `ccsolrad_prms`, and `ddsolrad_prms`: assumed it was always winter for Southern Hemisphere applications.

`write_climate_hru`: if a transpiration CBH file was specified and the value for control parameter **transp_module** was specified as **climate_hru_mo**, the CBH file was not correctly produced.

`frost_date`: write of parameter names was incomplete as the output string was not allotted enough characters. Fix was made in functions `write_integer_param` and `write_real_param` that are found in the file `utils_prms.f90`. If a spring or fall frost was not found in a year a divide by zero error was possible. The values for output parameters **spring_frost** and **fall_frost** were output as solar days instead of calendar day, i.e., 10 days are now added to the computed solar day. Function `julian_day`, found in the file `utils_prms.f90`, incorrectly computed solar day.

`transp_frost`: Function `julian_day`, found in the file `utils_prms.f90`, incorrectly computed solar day.

`lake_route` and `strmflow_lake`: if an HRU is a lake, the value for the local variable `gwr_type` for that HRU was incorrectly set to 2; it is now set to 1.

`srunoff_smidx` and `srunoff_carea`: The amount of water used to compute Hortonian runoff from cascading surface runoff was computed as a value on pervious areas only instead of the amount of water from the entire contributing HRUs; thus, could produce significant error when impervious fraction of HRUs is large. The values of variables `hru_sroffi` and `basin_sroffi` were not set correctly when parameter **imperv_stor_max** was specified equal to 0.0 for impervious portions of HRUs.

CHANGES THAT MIGHT PRODUCE SLIGHT CHANGES IN ASSOCIATED COMPUTATIONS – general:

- Most double precision variables changed to single precision to provide more consistent floating-point comparisons and have more consistent round-off issues. Change reduces memory requirements up to 10% and slight decrease in execution time.
- Changed variables `seginc_ssflow`, `seginc_sroff`, `seginc_gwflow`, `seginc_swrdr`, `seg_outflow`, `seg_inflow`, `lake_area`, `dprst_sroff_hru`, `dprst_seep_hru`, and `hortonian_lakes` changed from single to double precision as they are sums for sets of HRUs. Only `seg_outflow` and `seg_inflow` are used in computations in multiple modules, while; the others only are computed for output purposes.
- Changed check for very small values from 5.0E-6 to 1.0E-6 to better represent round-off error.

CHANGES THAT MIGHT PRODUCE SLIGHT CHANGES IN ASSOCIATED COMPUTATIONS – by module:

`cascade`: tolerance used to check for the fraction leaving an HRU or GWR adding up to exactly 1.0 changed from 1.00001 to 1.001. If this check finds an issue the cascade links are adjusted.

`potet_pan`, `potet_jh`, `potet_hamon`, `potet_hs`, `potet_pt`, and `potet_pm`: now sets potential evapotranspiration to 0.0 for values computed less than 1.0E-6 instead of only when a computed value was negative. Thus, very small computed potential evapotranspiration values are ignored.

`potet_pt`: constant used to compute saturation vapor pressure changed from 17.269 to 17.26939. Equation to compute the latent heat of vaporization were computed in units of Calories/gram and then converted to kilojoules/kilogram. Now they are computed in units of kilojoules/kilogram.

`ccsolrad`: now sets computed canopy density to 0.0 for values < 1.0E-6 instead of only if computed value was negative. Thus, very small, computed canopy density values are ignored.

`intcp`: values of parameters **`covden_win`** or **`covden_sum`** specified < 1.0E-4 and some computations that result in values very < 1.0E-5 are not reset to 0.0 as previously done.

`snowcomp`: set some and compares other computations to being less than 1.0E-6 instead of less than 0.0, which can allow for very small values of some variables. Canopy density on each HRU for each time step is used in computations instead of only values of parameter **`covden_win`**. If parameters **`den_init`** and/or **`den_max`** values are specified less than 1.0E-06, they are set to 1.0E-06 instead of 0.1 and 0.6, respectively.

`srunoff`: value of variable `hru_hortn_cascflow` was not reset to 0.0 for each time step; computed value is not used in other computations and is only available when cascading flow is active. Removed check for computed values of `imperv_stor` less than 0.0 and then reset to 0.0 to allow for round-off error bias to be reduced.

`gwflow`: computation of surface-depression storage fractions for round-off issues would sometimes produce very small, closed depression storage fractions, which is now fixed.

`soilzone`: Added checks for computed infiltration less than 0.0 and computed interflow coefficient equal to 0.0, these would not likely occur.

`ddsolrad`: if computed radiation adjustment factor based on parameters **`dday_slope`** and **`dday_intcp`** is greater than the value of parameter **`radmax`**, it is set to **`radmax`** rather than as computed.

`frost_date`: the sum of local variables `fallFrostSum` and `springFrostSum` computed as floating-point values instead of integer prior to rounding to nearest integer. These values were set to the truncated integer values, they are now rounded, that is, set to the nearest integer. Maximum value of the fall frost changed from 366 to 365 and minimum value of spring frost changed from 0 to 1. Computation of the `basin_fall` and `basin_spring` uses rounding of the integer value instead of truncation.

`transp_tindex`: all computations use degrees Fahrenheit instead of checking `temp_units` and converting computations to Fahrenheit, this should not produce a noticeable change in results, but does increase execution efficiency. When the value of parameter **`transp_end`** equals the current month and the current day is the first day of the month

transpiration is turned off (variable *transp_on* is set to 0) and the related local variables, *transp_check* and *tmax_sum*, are set to 0. After this check, if the current month equals the value of parameter **transp_beg**, *transp_check* and *tmax_sum* are checked to determine if transpiration needs to be turned on if the value of *tmax_sum* is greater than the value of parameter **transp_tmax**. If true variable *transp_on* is set to 1, *transp_check* is set to 1 and, *tmax_sum* is set to 0. Previously, the checks were reversed, which could keep transpiration on for a few days in a month, depending on the value of *tmax_sum* when the value of **transp_beg** and **transp_end** were specified equal to each other.

muskingum: allow specification of parameter **K_coef** to be less than 1.0, if found a warning message is issued instead of an error message when control parameter **parameter_check_flag** is specified greater than 0. If computed Muskingum flow coefficient (*c2*), based on parameters **K_coef** and **x_coef**, for a segment is < 0.0, this means the travel time through segment is small, thus outflow is primarily equal to inflow for the segment. If this condition is true, the computed Muskingum coefficient *c1* is decreased by the computed value of coefficient *c2* and *c2* is set to 0.0. If the computed value of Muskingum coefficient *c0* is < 0.0 then outflow from a segment would be greater than a day, the maximum travel time, which is mainly dependent on yesterday's flows. If this condition is true, the value of *c1* is decreased by *c0* and *c0* is set to 0.0. Previously, those Muskingum equation coefficients were not adjusted based on these conditions.

temp_1sta and **temp_laps**: initial value used to replace a missing value changed from 50.0 **tmax_allrain**(*start_month*), this only affects the first time step.

basin: reordered code to determine variables *hru_perv*, *hru_imperv*, *dprst_frac_hru*, *dprst_area_max*, *dprst_frac_open*, *dprst_frac_clos*, *dprst_area_clos_max*, *dprst_area_open_max* to maintain restriction that the fraction of the HRU that is pervious is at least 0.0001. This change might produce slight changes in results for rare combinations of input parameters.

map_results: **gvr_cell_pct** values specified less than 1.0E-6 are set to 0.0, previously the lower limit was 1.0E-10.

obs: measured precipitation values specified less than 0.0001 are set to 0.0.

INPUT SPECIFICATION CHANGES – by module:

ccsolrad and **ddsolrad**: check added to be sure at least one value of parameter **hru_solsta** is specified greater than 0 when dimension **nsol** is specified greater than 0. If all values of **hru_solsta** were specified equal to 0 an array would be referenced beyond its memory limit.

basin_sum: the default value for parameter **print_freq** changed from 1 to 3.

basin: error check added to be sure dimensions **nhru** = **nssr** = **ngw** when using the surface-depression storage computation option. Error check added for values of

parameter **op_flow_thres** specified greater than 1.0. Added check for values of parameter **hru_percent_imperv** specified less than 0.0 or greater than 0.999. Previously, if either of these conditions were true, the values were set to 0.0 and 0.999, respectively; now an error message is printed, and execution stops. Added check for HRUs not connected to a stream segment as specified using parameter **hru_segment**. This check is applicable only when stream-segment routing and/or cascading flow routing are inactive; a warning message is issued to the screen and written in the Model Output File identifying any HRUs not connected. Added check for values of parameter **dprst_area** specified greater than the corresponding value of **hru_area** for any HRU; an error message is printed, and execution stops. Added check for isolated stream segments, that is a segment that does not receive inflow or flow to another segment as specified by parameter **tosegment**); error unless control parameter **parameter_check_flag** is specified equal to 0. Added checks to be sure valid values of **elev_units** and **cov_type** are specified; if an invalid value an error message is printed, and execution stops. Values of parameters **soil_moist_max** and **soil_rechr_max** are set to 0.0001 if less than 0.0001 instead of set to 0.001 if less than 0.001. Values of parameters **hru_percent_imperv**, **dprst_area**, **op_flow_thres** and computed values of **dprst_area/hru_area** are set to 0.0 if less than 0.0001 with warning message issued.

gwflow: checks added for values of parameter **gwflow_coef** specified greater than 1.0 or GWRs specified as being a swale; if these conditions are found a warning message issued.

srunoff_smidx and **srunoff_carea:** added check for values of parameter **carea_max** specified greater than 1.0; if true an error message is printed, and execution stops. Added check for the computation of local variable **carea_max** for **srunoff_smidx** based on parameters **smidx_coef**, **smidx_exp**, and **soil_moist_max** results in a value greater than 2.0; warning message is printed if control parameter **parameter_check_flag** specified equal to 1. Added checks for values of parameters **dprst_flow_coef**, **dprst_seep_rate_open** and **dprst_seep_rate_clos** specified greater than 1.0; if true an error message is printed, and execution stops.

soilzone: don't reset parameters **ssr2gw_rate**, **soil_moist_init**, **soil_rechr_init**, **ssstor_init**, **sat_threshold**, **slowcoef_lin**, **slowcoef_sq**, **fastcoef_lin**, and **fastcoef_sq** if they are specified as invalid, instead if true an error message is printed, and execution stops. Specification of **soil_rechr_max>soil_moist_max**, **soil_moist_init>soil_moist_max**, **soil_rechr_init>soil_moist_max**, **ssres_stor>sat_threshold**, **soil_rechr_init>soil_rechr_max**, **soil_moist_max<0.0001**, and **soil_rechr_max<0.0001** are treated as warnings and reset to valid values instead of errors when control parameter **parameter_check_flag** specified equal to 0, previously these always were treated as errors. Added checks for **slowcoef_sq**, **slowcoef_lin**, **fastcoef_sq**, and **fastcoef_lin** specified equal to 0 as this could cause a divide by zero; if true an error message is printed and execution stops unless **parameter_check_flag** is specified equal to 0, for which a warning message is printed and any values less than 0.0001 are set to

0.0001. Check added for specifying valid values of **soil_type**, which can be 1, 2, or 3; if any invalid values are specified an error message is printed and execution stops.

climateflow: make sure parameters **basin_solsta** and **basin_tsta** are always assigned a valid value, which is needed as they are written to the restart file. Added check for computed values of *tmaxf* greater than *tminf*; if true a warning message is printed, and execution continues.

potet_pan: added check to be sure pan evaporation time series is included in Data File, if values of parameter **hru_pansta** are specified greater than dimension **nevap** or equal to 0 an error message is printed, and execution stops.

intcp: if a values of parameter **epan_coef** are specified less than 0 an error message is printed, and execution stops. This check is made only when pan evaporation data are included in the Data File. If any values of parameters **covden_win** or **covden_sum** is specified less than 0 or greater than 1 an error message is printed, and execution stops.

xyz_dist and **ide_dist**: added checks to be sure data for at least 2 temperature and precipitation measurement stations are specified to be used in computations.

xyz_dist: added check for specifying values of parameters **x_div**, **z_div**, **y_div**, **ppt_div**, **tmax_div**, and **tmin_div** equal to 0.0, as 0.0 would cause a divide by 0.0. If true an error message is printed, and execution stops.

potet_jh: added check for values of parameter **jh_coef_hru** specified greater than 150 or less than -50 and values of **jh_coef** specified greater than 10 or less than -1; if true a warning message is printed when control parameter **parameter_check_flag** is specified equal to 0; else an error message is printed and execution stops.

map_results: added check to be sure the type of selected output variables is either real or double. Added check for selected output variables dimensioned by a value not equal to dimension **nhru**. Added checks for specification of **gvr_cell_id** values greater than dimension **ngwcell** and **gvr_hru_id** values specified greater than dimension **nhru**. If any of these checks are true an error message is printed, and execution stops. If the value of parameter **mapvars_freq** is specified equal to 0 then the **map_results** module is not active even if control parameter **mapOutON_OFF** is specified equal to 1. If dimensions **nhru** and **nhrucell** are specified with equal values, then parameters **gvr_hru_id** and **gvr_cell_pct** are not required and ignored if specified in the Parameter File(s).

temp_1sta and **temp_laps**: if too many missing values (greater than parameter **max_missing**) were found an error message is printed and the execution stops instead of continuing.

call_modules: added checks for deprecated module names, if found a warning message is printed, but allow to maintain downward compatibility for older applications the module name is set to the current name.

OUTPUT CHANGES

- Print of list of valid modules with longer and more consistent descriptions.
 - When `climate_hru` is active for more than one type of CBH file, the module description is printed for each climate type. For example, if `climate_hru` is used to input temperature and precipitation values, a line is printed with the `climate_hru` version identification for the active Temperature Distribution and Precipitation Distribution modules. Previously, the identification was printed once no matter how many climate types input were using `climate_hru`.
 - HRU identification numbers are printed allowing for seven digits instead of six throughout the code.
 - File: `temp_1sta_laps.f90` added print of module version identification as it was missing.
 - File `srunoff.f90` print of module version identification changed to indicate whether using `srunoff_smidx` or `srunoff_carea` method.
 - `basin_sum`: when control parameter **print_debug** value is specified equal to 4, some debug values were summed instead of printed individually. Write variable `basin_potsw` instead of `orad` in summary tables. Printing of water balance values changed from F9.4 to F9.3.
 - New function `print_date` added in file `utils_prms.f90`, which is used to print the current time step in consistent formats for warning and error messages: modules affected: `potet_pan`, `ddsolrad`, `precip_dist2`, `ccsolrad`, `temp_dist2`, `obs`, `ide_dist`, `snowcomp`, `gwflow`, `climateflow`, and `soilzone`.
 - New functions `check_param_value`, `check_param_limits`, `checkint_param_limits`, `checkdim_param_limits`, `check_param_zero`, and `check_restart_dimen` added in file `utils_prms.f90` so that duplicate code is reduced for checking many parameters for valid input values and to make warning and error messages more consistent.
 - `soilzone`: message for values of variables `slow_stor > pref_flow_thrsh` can be turned off as well as many warning messages for other modules if control parameter **print_debug** is specified equal to -1; this message was printing for very small differences.
 - `call_modules`: allow the same file name to be used control parameters **save_vars_to_file** and **init_vars_from_file**, need to be careful as this means the values stored when the file was first generated are overwritten. The start and end clock date and time and the elapsed time at end of simulation are output to the screen in the Model Output file.
 - `prms_summary`: changed output format of variable values from F12.6 to PE14.6.
-

Version 3.0.5 – April 24, 2012

This release mainly focused on general code clean up and bug fixes.

General

MMF declmodule replaced with Fortran print_module.

MMF write and open of **model_output_file** replaced with Fortran routines (opstr replaced with write_outfile). Affected modules: hru_sum_prms, basin_sum, basin, and call_modules.

MMF functions isleap and julian replaced with Fortran functions leap_day and julian_day.

MMF function getstep replaced with an internal counter the current time stop (variable *Timestep*) is set to 0 in basin and incremented in obs.

Parameter checks in initialize procedure only performed for active HRUs.

Restart capability added to all except: potet_hs, potet_pt, potet_hamon_prms, temp_2sta_prms, ccsolrad_prms, ddsolrad_prms, hru_sum_prms, frost_date, write_climate_hru.

Files precip_1sta.f90 and precip_laps.f90 combined into single file: precip_1sta_laps.f90.

Files temp_1sta.f90 and temp_laps.f90 combined into single module: temp_1sta_laps.f90.

Files srunoff_smidx.f and srunoff_carea.f combined into single file: srunoff.f90.

transp_frost: parameters **spring_frost** and **fall_frost** only checked for active HRUs to set initial values of *basin_transp_on* and *transp_on*.

write_climate_hru: changed output format from E10.2 to E12.4.

ddsolrad: determination if the simulation time is in the summer based on equinox for the Northern and Southern Hemisphere is determined in the obs module instead of this module so that this code is in on location.

Files temp_dist2.f, precip_dist2.f, strmflow_lake.f, soilzone.f, climateflow.f, call_modules.f converted to F90: temp_dist2.f90, precip_dist2.f90, strmflow_lake.f90, soilzone.f90, climateflow.f90, and call_modules.f90.

obs: make sure **runoff_units** has a value when **nobs = 0**; set *summer_flag*, increment *Timestep*.

`utils.f90`: added check to be sure when reading *orad* that the variable name is *swrad*, which is the variable name used by `write_climate_hru`. This could be a problem for people who generated their own *swrad* CBH file and used a different variable name.

`basin`: changed NEARZERO from 1.0E-7 to 5.0E-6; DNEARZERO from 1.0D-12 to 1.0D-10 to better represent round-off error. Removed parameter **basin_area**. Segment routing order computation moved to here and removed from streamflow routing modules to reduce duplicate code.

`cascade`: code related to water-body cascades removed. Instead, the **tosegment** is used and a stream segment must be associated with each lake if present.

New module: `strmflow_in_out`, which routes flow through the stream network without assuming a routing travel time; thus, outflow from a stream segment equals the sum of the inflow from any upstream segments and any lateral flows from associated HRUs.

File `potet_jh.f90`: merge of files `potet_jh.f90` and `potet_jh_hru.f90`.

File `srunoff.f90`: merge of files `srunoff_smidx.f` and `srunoff_carea.f`. New parameter **dprst_et_coef(nhru)** was added to adjust evaporation potential from surface depressions. Evaporation from open depressions is computed prior to evaporation from closed. Both are computed at the potential rate, limited by unsatisfied ET. Unsatisfied ET is reduced after computing open evaporation to then limit closed evaporation. This was being done in a complicated way, which is now streamlined.

`strmflow_lake`: routing strategy using cascade water body code replaced with **tosegment** order, which requires a stream segment to be associated with each lake. Code that computes fluxes by segment, such as *seginc_gwflow*, *seginc_ssflow*, *seginc_sroff*, *seginc_swrad*, *seg_lateral_inflow*, and *hru_outflow*. Module was reorganized and has had little testing.

BUG FIXES

`potet_pan`: check dimension **nevap** > 0 in declare procedure instead of initializing to avoid memory error. CRITICAL BUG FIX: module would not run as return code set to 1 instead of 0. If **nevap** < 1, simulation stops with error message. Valid values for **hru_pansta** checked for active HRUs only.

`transp_index`: changed maximum value from 12 to 13 so module works with `paramtool` fix option. Set *transp_end_12* for each HRU so that there is a value so as to write the variable to the restart file.

`basin_sum`: **print_freq** = 6 did not produce monthly and yearly tables, now does. Variables *basin_runoff_ratio* and *basin_runoff_ratio_mo* were in units of inches/cfs, changed to inches/inches (decimal fraction).

`snowcomp`: allow **cov_type** to be > 2 to designate trees, was limited to **cov_type** = 3

gwf`flow`: minimum `elevlake_init` changed from 0.0 to -10000.0 feet. BUG FIX: with `strmflow_lake` active with weirs or gates, `seepage_gwr` was in inches when it needed to be in acre-inches.

muskingum: default for variable `TS` was set to 0.0 instead of 1.0, which for `K_coef` values < 1.0 would cause `x_max` to be set to 0.0 (not sure if this was a bug, Michael identified this as a problem). Checks were added for `K_coef` > 24.0. If `parameter_check_flag` = 1, this is an error, else a warning message is issued and `K_coef` is set to 24. Check added for `C2`<NEARZERO, if so, `C1` set to `C1 + C2` and `C2` set to 0.0 (short travel time). Check added for `C0`<NEARZERO, if so, `C1` set to `C1 + C0` and `C0` set to 0.0 (long travel time). BUG FIX: the routing loop was modified to properly include `streamflow_cfs(obsin_segment(iorder))` in the current inflow of a segment and to set the `seg_upstream_inflow` to 0.0 for each internal time step. This module needs more verification. BUG FIX: `obsin_segment` was not working when `K_coef` was not equal to 1.0, the value was divided by the timestep instead of using the input value.

soilzone: all preferential flow computations only performed when `pref_flow_den` > 0.0 for an HRU, previously some were always computed when at least one HRU had a preferential flow reservoir. BUG FIX: the Dunnian flow from the gravity reservoir was not set correctly if a preferential flow reservoir was not present, this was only an issue when computing the soil zone water balance when `print_debug` = 1. This did not affect the results of the soil zone computations.

=====
Version 3.0.4 – January 15, 2012

This release mainly focused on bug fixes and changes to warning and error messages.

BUG FIXES

- muskingum: Value of NaN was produced for streamflow if value of `K_coef` < 1.
- musroute: `seginc_swrad` for first segment when no HRU contributes to that segment is set to second segment instead of leaving it set to 0.0.
- climate_hru: CBH files are checked to be sure first time step is valid and if end-of-file or missing day found during a simulation.
- srunoff_carea and srunoff_smidx: amount of pervious and impervious surface runoff from open and closed depressions computed incorrectly resulting in too small of surface depression storage surface runoff.
- basin_sum: water balance and `basin_stflow_tot` computed and outflow from basin printed using `basin_stflow_in` instead of `basin_stflow_out`; added variable `basin_runoff_ratio = basin_ppt/basin_cfs`.
- Input error checking changed to get through reading Parameter File (mostly) before stopping on error condition instead of stopping at first input error.

Version 3.0.3 – November 29, 2012

This version was prepared but never released because it failed the test cases.

Version 3.0.2 – September 22, 2012

This release mainly focused on bug fixes with a few minor changes to some input/output files, and parameters.

BUG FIXES

`soilzone:`

- limit flows produced in each reservoir to maximum capacities instead of antecedent storage + all inflow to a reservoir; this fix may result in substantial changes in results and is consistent with the PRMS conceptualization of the soil zone.
- set available potet for the average depth over the pervious portion instead of the whole HRU, this bug may have generated increased ET used by the capillary reservoir when impervious surfaces and surface depression storage are present in an HRU.
- *basin_recharge* was computed incorrectly; it was only set to the recharge value of the last HRU. D)if using `strmflow_lake` and the parameter `lake_hru_id` was not specified an invalid memory access could take place which would cause evaporation from lakes to be computed incorrectly.

`strmflow_lake:` flow out of lakes based on gate openings were computed using values specific to a single lake model, this was changed to be applicable to any model.

`cascade:` when greater than 2 cascades from a source to a destination, one or more of these cascades could have been ignored and fraction of cascade computed incorrectly. This would be a rare occurrence and was true for HRU and GWR cascade specifications.

`intcp:` A) if pan evaporation data are in Data File (`nevap>0`) and the ET module is not `potet_pan` then they are ignored rather than used as *potet*; B) allow winter cover density to be greater than summer density; previously if winter density was specified > summer, winter density was set to summer.

`map_results:` the number of output rows were computed incorrectly, if the dimension `ngwcell` was not equal to `ngwcell/ncol` and if `nhru` does not equal `nhru/ncol`.

`obs:` negative input values of observed runoff were set to -11; they are not changed from the values specified in the Data File; this could have caused problems with automated calibration programs.

OUTPUT AND INPUT ISSUES

- Some variables changed from single precision to double precision, this might cause a very slight change in results that may have been due to round-off error - in modules: `precip_dist2`, `temp_dist2`, `xyz_dist`, `strmflow_lake`, `basin_sum`, and `map_results`.
- A list of available and active modules is output to the user's screen.
- Module `climate_hru` – new functionality: can input whether an HRU is in a transpiration day in a CBH file (0=no or 1=yes), previously the transpiration period was fixed for the entire simulation time period.

PARAMETER NAME CHANGES

- temperature adjustment parameters were changed from **tmax_adj** and **tmin_adj** to **tmax_cbh_adj** and **tmin_cbh_adj** to avoid possible duplicate use of the parameter values. Similarly, precipitation adjustment parameters were changed from **rain_adj** and **snow_adj** to **rain_cbh_adj** and **snow_cbh_adj**. Check the messages about unused **tmax_adj**, **tmin_adj**, **rain_adj**, and/or **snow_adj** parameters and **tmax_cbh_adj**, **tmin_cbh_adj**, **rain_cbh_adj** and/or **snow_cbh_adj** are required but not specified. The value of `solrad_tmax` and `solrad_tmin` is now always set to `basin_tmax` and `basin_tmin` instead of using `tmax(basin_tsta)` and `tmin(basin_tsta)` when `ntemp>0`; this can produce differences in results.
- Data File: A) missing temperature value indicator changed from less than -89 to less than -99 for modules: `temp_laps`, `temp_1sta`, `temp_dist2`, and `xyz_dist`.
- Data File: B) added in variables *humidity* and *wind_speed* and dimensions **nwind** and **nhumid**.
- Data File and Climate-by-HRU (CBH) files: Values are checked to see if any are specified as NaN (not a number), which results in an error message and stop of the execution. If any values in a CBH files are missing, the number of missing values and data type are output to the user's screen and the execution stops.
- Module `strmflow_lake`: Parameter and variable names using "sfres" or "res" as part of their name, changed to use "lake" instead. The dimension **nsfres** changed to **nlake**. If the dimension **nsfres** is specified, a list of all parameter names that need to change is output to the user's screen and execution halts.
- Module `temp_dist2` - if no valid temperature values found, include in a warning message to indicate that the last valid temperature values is used for that time step.
- Module `hru_sum_prms` has been deprecated and is only active if one or more of the following deprecated modules are active: `potet_hamon_prms`, `ddsolrad_prms`, `ccsolrad_prms`, and `soltab_prms`. If module `hru_sum_prms` is not active, parameters **pmo** and **moyrsum** are not needed.

- Variable *basin_stflow* is replaced with *basin_stflow_in*, the total amount of lateral flow into the stream network. Variable *basin_stflow_out* was added, which is the total amount streamflow out of the model domain.
- Module *map_results* –Added check to be sure the mapping specification is complete (*gvr_cell_id(i)>0*, *gvr_hru_id(i)>0*, and *gvr_cell_pct>1.0E-10*) from the HRU map to the target map; a warning message is output to the user’s screen if this condition is detected. This check produces a warning message, as in some cases it might be desirable to map only a portion of an HRU to a target map spatial unit, such as, at a model boundary where the HRU map and target map have different spatial extents.
-

Version 3.0.1 – February 06, 2012

This release mainly focused on improving the messages that come to the command line window. Many users of PRMS were ignoring the error and warning messages because that they could not be understood. Also, users were uncertain about which modules were active in the runs they were making. The new messages will help with both of these cases.

- There were some changes made to increase the precision of the snow and soil moisture module algorithms. Some of the FORTRAN variables were changed from single precision to double precision floating points. The consequence of this is some changes in the results in the simulation of snowpack storage and melt, and soil-moisture storage and recharge. These changes are evident in (sometimes) the 4th and (usually) the 5th significant digit.
- No changes were made in this version which impact the format or content of the input and output files in any way.
-

Version 3.0.0 – November 15, 2011

This version of PRMS has been designed as a stand-alone program that can be executed on a Linux or Microsoft Windows platform. In some ways, this version may appear to return to the concepts and design of the earliest versions of PRMS. Much of the support functionality provided by MMS has been stripped away in favor of a “batch execution” mode for maximum application flexibility and computational efficiency. This approach also supports maximum portability between computers running the Windows and Linux operating systems. Focus has been placed on ease of deployment, installation, and reliability over the MMS concepts of “model building.” However, the module and function library developed for the MMS version of PRMS have been shown to be useful and have been retained.

MMS Version MMS-windows – January 26, 2007

The MMS version of PRMS was ported to PCs running the Windows operating system using Cygwin.

MMS Version 1.0.0 through 1.2.1 (1991 through 2002)

These were UNIX only releases. Although computationally efficient, the procedure required to add hydrologic-process algorithms to the original code was less than adequate. As a result, the architecture and modular structure of PRMS were redesigned to allow better integration and hydrologic-process algorithm-development capabilities. This new structure was the USGS Modular Modeling System (MMS), an integrated system of computer software developed for simulating a variety of water, energy, and biogeochemical processes that included PRMS.

The basic hydrologic-process algorithms in PRMS were maintained in the MMS version; however, the use of MMS enabled the addition of new process algorithms and the enhancement of many of the features and capabilities in the original PRMS. These additions included graphical systems and networked data systems that took advantage of increased computational power.

Version 2.1 – January 17, 1996

This was the pre-MMS version of PRMS. It was precompiled for computers running the DOS and DG UNIX operating systems.

Pre-version 2.0 – (1983 – 1996)

PRMS originally was developed as a single FORTRAN 77 program composed of algorithms encoded in subroutines, each representing an individual physical process of the hydrologic cycle.

For the processes related to temperature distribution, solar-radiation distribution, evaporation, transpiration, and surface runoff, two or more different algorithms were encoded, each representing a different conceptual approach. A specific algorithm was selected at run time by setting values in the input file. This modular-design concept enabled the creation and application of a model that was most appropriate for a given study and supported the long-term goal to expand the available process-simulation capabilities of PRMS.

This version of PRMS uses “punch card” formats for input files, line-printer-generated output plots, use of the USGS’s National Water Data Storage and Retrieval system, and the job-control language specifications necessary to execute PRMS on the Amdahl and Prime computer systems.